
Modeling Complex Systems in the Situation Calculus: A Case Study Using the Dagstuhl Steam Boiler Problem

Todd G. Kelley

Department of Computer Science
University of Toronto
Toronto, Canada M5S 1A4
email: tgtk@cs.toronto.edu

Abstract

The situation calculus is showing considerable promise as a formal framework for modeling the dynamical worlds encountered in real life. We take advantage of the results of [Rei96] to show that the situation calculus is a powerful and practical modeling language. The paper provides a brief overview of the concurrent temporal situation calculus and how it is used to specify physical behavior. It then presents the Dagstuhl steam boiler problem as an example of a complex physical system of interest in the real world. The problem was the focus of the Dagstuhl meeting, “Methods for Semantics and Specification”, whose goal was to develop criteria by which to compare advantages and drawbacks of formal methods for practical applications. The paper presents the situation calculus specification of the focus of the problem, the steam boiler controller. It then discusses the theoretical foundation of a PROLOG technology simulator, which, together with the specification, form an implementation of the controller. The paper concludes with an evaluation of the situation calculus solution to the problem, using the criteria which emanated from the Dagstuhl meeting.

1 Introduction

The situation calculus language ([MH69]) has received much attention from the Cognitive Robotics Group at the University of Toronto in recent years. The language is showing considerable promise as a formal framework for modeling the dynamical worlds encountered in real life.

The challenges facing such a framework are numerous. For example, it must facilitate the representation of time, continuous processes, actions performed by agents with “free will”, actions performed by Na-

ture, non-deterministic actions of chance, knowledge-producing actions and the mental state of agents, concurrent or simultaneous actions, etc. The framework must also be conducive to various types of reasoning, including prediction, planning, diagnosis, and hypothetical reasoning. A single formal theory of action and time that satisfies these conditions is the ongoing objective of the Cognitive Robotics Group.

Encouraging progress towards this long-range objective using the situation calculus as the framework has been achieved [Rei91, Pin94, LRL⁺96, LLL⁺96, SL93]. This paper concentrates specifically on the results of [Rei96] which make it possible to formally model the behavior of physical systems as complex as a steam boiler controller. These physical systems (the toilet of [Kel96] is another example) involve time, continuous processes, and simultaneous natural actions (those dictated by the laws of physics). The situation calculus of [Rei96] provides a knowledge representation framework that is conducive to the specification and simulation of such systems, while explicitly embodying a solution to the frame problem.

As a specification language, the situation calculus boasts many desirable properties. For example, a situation calculus model of a physical system is a truly logical specification of that system. Hence, items of interest, such as behaviors of parameters, are *logical consequences* of the specification. This feature of the situation calculus is clearly conducive to formal verification. Furthermore, the foundational axioms of the situation calculus provide a firm theoretical foundation for a situation calculus-based PROLOG simulator of situation calculus specifications. The behavioral properties of a situation calculus specification can be obtained automatically by directly executing the specification on the simulator. *Hence, a specification in situation calculus form is also an implementation whose behavioral properties are automatically formally verified against the specification.*

To illustrate that the situation calculus is a practical modeling language, we have formalized the controller

specification for the Dagstuhl steam boiler [Abr94]. The original text from which the specification is derived was written by LtCol. J. C. Bauer for the Institute for Risk Research of the University of Waterloo, and submitted as a competition problem to be solved by the participants of the International Software Safety Symposium organized by the Institute for Risk Research. The Dagstuhl steam boiler problem, solved in this paper, stems from that original text. The problem was the focus of the Dagstuhl meeting, “Methods for Semantics and Specification”, whose goal was to develop criteria by which to compare advantages and drawbacks of formal methods for practical applications. Hence, the problem is ideal for exhibiting the features of the situation calculus. In this paper, I present an evaluation of the situation calculus solution to the problem, using the criteria which emanated from the Dagstuhl meeting [ABL95].

2 Situation Calculus Ontology

The situation calculus is designed to formalize the behavior of dynamically changing worlds. Intuitively there are two facets to the ontology itself: 1) distinguishing between different courses of action, and 2) determining the state of the world after different courses of action. There are two additional facets of the situation calculus: 3) axioms which specify which courses of action can happen, and 4) axioms which specify the results of courses of action.

2.1 Naming Courses of Action

The mechanism for all change in such worlds is one or more agents, perhaps including Nature, performing named, instantaneous, *actions*. *Situations* are histories of concurrent action occurrences, each denoting a different possible evolution of the world. A concurrent action is a set of simultaneous simple actions. The constant symbol S_0 denotes the initial situation in which no actions have yet occurred. Other than S_0 , all situations have names of the form, $do(\alpha, \sigma)$, intuitively meaning the result of doing action α in situation σ . Actions are denoted by functions, with time t being the last parameter. For example, consider the situation

$$do(\{stop_talking(T_2)\}, \\ do(\{begin_walking(T_1), begin_talking(T_1)\}, S_0),$$

which denotes the world history in which an agent begins walking and talking at time T_1 , and then stops talking at time T_2 . The agent would not be talking in this situation, but she would still be walking. The first concurrent action performed is $\{begin_walking(T_1), begin_talking(T_1)\}$, which is the set consisting of two simple actions $begin_walking(T_1)$, and $begin_talking(T_1)$. Given any situation, the order

of action occurrences is obtained by scanning the situation from right to left. So, this situation denotes a world history corresponding to the action sequence

$$\{begin_walking(T_1), begin_talking(T_1)\}, \\ \{stop_talking(T_2)\}.$$

2.2 The State of the World

The state of a world resulting from a certain course of action is determined by the values of *fluents*.

Relational fluents are denoted by predicate symbols taking a situation term as their last argument. These relations represent what is true about the world after carrying out the course of action specified by their situation argument. For example, the fluent, $happy(p, s)$ might mean that person p is happy in s . Note that technically a situation is not a state, but a history of action occurrences; so in this context, we should take “ p is true in s ” to mean, “ p is true *after carrying out, in order, all and only the actions specified by s* ”.

Functional fluents are functions whose value varies from one situation to another. For example, $const_position(ball, s)$ might denote the real-valued constant position of a ball in situation s .

Continuous processes are represented using functional fluents. The important idea, due to Pinto [Pin94], is that although a continuous process involves continuous change in the values of one or more parameters, the values of the parameters can be modeled by equations which do not change in a particular situation. We say that the *behavior* of the parameter is constant. Unlike the QSIM-style qualitative reasoners (e.g. [Kui86]), which abstract change over points and intervals from the continuous change of a parameter, a situation calculus treatment abstracts behavior from the continuous change. This treatment of continuous processes is in the spirit of Sandewall’s work [San89]. This work introduces the idea of using differential equations to represent the behavior of parameters, and using logic to specify which differential equations model the behavior of a parameter during the different phases of the evolution of a dynamical system.

Consider a ball’s position, which varies with time in s . The $position(ball, s)$ fluent has as its value a function of time. Also consider the function, $val(f, t)$, which takes as arguments a function of time, f , and a time, t , and whose value is the value of f at t . We take $f(t)$ to be an abbreviation for $val(f, t)$, and we could write¹ $position(ball, s)(t) = x_0 - 1/2gt^2$, meaning that the value of the position function of the ball at time t in situation s is $x_0 - 1/2gt^2$. The position function in a certain situation might be defined

¹In this paper, lower case Roman characters denote variables. Also, free variables are implicitly universally prenex quantified.

on the entire real line, as it is in this case, but it is only relevant to the model on some half-open interval: $[start(s), \infty)$, or $[start(s), start(do(c, s))]$ for some c , where $start(do(c, s))$ is defined to be $time(c)$, and $time(c)$ denotes the time at which c occurs.

In the situation calculus, all change must be the result of some action occurrence, and functional fluents are consistent with this. In the case of the ball, although the ball's position varies in s , its position follows a single function in s . The behavior represented by the $position(x, s)$ fluent remains unchanged until some action (perhaps $catch(x, t)$) takes place to change it.

2.3 Specifying Which Courses of Action Can Happen

Precondition axioms determine the conditions under which an action is possible. A formalization of a world includes one precondition axiom for each action. For example, the precondition axiom for the $bounce(ball, t)$ action states that the ball bounces iff it is falling and it is at the floor.

Consider the function, $\frac{d}{dt}(f)$, which takes a function of time, f , as its argument and has as its value the function which is the time rate of change of f . We write $\frac{d}{dt}(position(ball, s))(t) < 0$ to say that the value of the time rate of change of the position function of the ball at time t in s is less than 0. In other words, the ball is falling at time t . Hence, the precondition axiom for the $bounce(ball, t)$ action is

$$\begin{aligned} Poss(bounce(ball, t), s) \equiv \\ t \geq start(s) \wedge position(ball, s)(t) = 0 \wedge \\ \frac{d}{dt}(position(ball, s))(t) < 0 \end{aligned} \quad (1)$$

where $Poss(a, s)$ means that action a is possible in situation s .

Natural actions, such as $bounce(ball, t)$, are a special case: when a natural action can possibly occur at time t , it *does* occur, unless some other action (perhaps $catch(ball, t)$) occurs sooner. In worlds where no agent has "free will", all actions are natural. Intuitively, an agent has "free will" if it is impossible to predict what actions the agent will perform, or, at least, *when* the agent will perform some action. Nature is taken to be characterized by all of the scientific laws that scientists strive to know, and to the extent that those laws exist and do not change, Nature has no "free will".

In worlds where all actions are natural, if certain conditions are met, it is possible to simulate the evolution of the world. Simulation is possible when in every situation it is possible to determine whether and when actions will occur. In effect, the world evolves deterministically according to the laws of Nature (e.g. Newton's laws). When this is the case, there is only one legal path through the tree of situations.

2.4 The Results of Courses of Action

The ways in which the values of fluents are affected by action occurrences are determined by *successor state axioms*. A formalization of a world includes one successor state axiom for each fluent. The axiom specifies all individual conditions under which the fluent will change, and how the fluent changes under those conditions.

Consider a world where a ball can bounce, and it can be caught, and no other actions can affect it. The successor state axiom for the $position(ball, s)$ fluent would state that if the concurrent action c is possible in s , then the value of $position(ball, do(c, s))$ depends upon what simple actions are in c . If c contains a *bounce* and not a *catch*, the ball's velocity reverses. If c contains a *catch*, the ball's position becomes constant where it is caught. If c contains neither a *bounce* nor a *catch*, the behavior of the ball's position remains unchanged.

The axiom is

$$\begin{aligned} Poss(c, s) \supset position(ball, do(c, s)) = f \equiv \\ [(\exists t') bounce(ball, t') \in c \wedge catch(ball, t') \notin c \wedge \\ time(c) = t_0 \wedge \\ (\forall t) f(t) = 0 - \frac{d}{dt}(position(ball, s))(t')(t - t_0) - \\ 1/2g(t - t_0)^2] \\ \vee \\ [(\exists t') catch(ball, t') \in c \wedge \\ (\forall t) f(t) = position(ball, s)(t')] \\ \vee \\ [(\forall t) bounce(ball, t) \notin c \wedge catch(ball, t) \notin c \wedge \\ f = position(ball, s)] \end{aligned} \quad (2)$$

where the surface on which the ball bounces is taken to be at position 0, and $g > 0$ is the acceleration due to gravity. Successor state axioms such as this embody Reiter's [Rei91] solution to the frame problem.

3 The Dagstuhl Steam Boiler

In this section, we attempt merely to introduce the Dagstuhl steam boiler problem in enough detail for the purposes of this paper, rather than reproduce the specification. See [Abr94] for the complete specification.

The Dagstuhl steam boiler system consists of the following units:

- the steam boiler with a water level which is kept preferably within the normal operating range, but certainly must be kept within the safe range,
- a device to measure the quantity of water in the steam boiler (denoted by *water_Level*),

- four pumps which are either off or on to provide the steam boiler with water (we use $pump(i)$ to denote the i th pump),
- one controller to supervise each pump (four in all), reporting on its water flow (we use $pump_control(i)$ to denote the i th pump controller),
- a device to measure the quantity of steam exiting the steam boiler (denoted by $steam_rate$),
- an operator desk, from which a *STOP* message can be sent to the controller,
- a message transmission system used for all communication between the controller and the steam boiler components.

We attempt to keep our notation consistent with the original problem description, [Abr94]. Messages are denoted by functions and constants with upper case names. Mandatory messages must be present in every transmission. There are roughly four classes of messages:

Control messages : The controller sends messages to the physical units to direct their actions, and the physical units send messages to the controller to indicate the actual state of the steam boiler.

The control messages sent by the controller to the physical units are

- *VALVE*: sent in *initialization* mode to request the opening and then the closure of the valve for evacuation of water from the steam-boiler,
- *OPEN_PUMP*(n): sent to activate $pump(n)$,
- *CLOSE_PUMP*(n): sent to deactivate $pump(n)$.

The control messages sent by the physical units to the controller are

- *PUMP_STATE*(n, b): sent to indicate that the state of $pump(n)$ is b , which may be 0 or 1, meaning open or closed, mandatory,
- *PUMP_CNTRL_STATE*(n, b): sent to indicate that the flow of water from $pump(n)$ is b , which may be 0 or 1, meaning there is flow or there is no flow, mandatory,
- *LEVEL*(v): sent to indicate that the level of water in the boiler is v , mandatory,
- *STEAM*(v): sent to indicate that steam is exiting the boiler at rate v , mandatory.

Fault Detection and Repair messages : When the controller infers that a component is defective (a pump claims to be operating, but there is no water flow, for example), the controller sends a fault detection message. When the a defective component has been repaired, a repair message is sent to the controller.

The controller sends the following fault detection messages:

- *PUMP_FAIL_DET*(n): sent (until acknowledgement is received) to indicate that the controller has detected the failure of $pump(n)$.
- *PUMP_CNTRL_FAIL_DET*(n): sent (until acknowledgement is received) to indicate that the controller has detected the failure of $pump_control(n)$,
- *LEVEL_FAIL*: sent (until acknowledgement is received) to indicate that the controller has detected the failure of the water level measuring unit,
- *STEAM_FAIL*: sent (until acknowledgement is received) to indicate that the controller has detected the failure of the unit that measures the rate of steam exiting the boiler.

The controller receives the following repair messages:

- *PUMP_REPD*(n): sent (until acknowledgement is received) to indicate that $pump(n)$ has been repaired,
- *PUMP_CNTRL_REPD*(n): sent (until acknowledgement is received) to indicate that $pump_control(n)$ has been repaired,
- *LEVEL_REPD*: sent (until acknowledgement is received) to indicate that the water level measuring unit has been repaired,
- *STEAM_REPD*: sent (until acknowledgement is received) to indicate that the unit that measures the rate of steam exiting the boiler has been repaired.

Acknowledgement messages : The physical units send the controller a corresponding acknowledgement message for each fault detection message. For example, *PUMP_FAIL_ACK*(n) is sent to the controller to acknowledge the receipt of a *PUMP_FAIL_DET*(n) message. Similarly, the controller sends the physical units a corresponding acknowledgement message for each repair message. For example, *PUMP_REPD_ACK*(n) is sent to the physical units to acknowledge a *PUMP_REPD*(n) message.

Other messages : There are also messages that have somewhat administrative purposes.

The controller sends the following administrative messages to the physical units:

- *PROGRAM_READY*: sent (until acknowledgement is received) in *initialization* mode to indicate that the controller is ready to assume control of the steam boiler,
- *MODE*(m): sent to indicate that the program's current mode of operation is m (see

below for the modes of operation), mandatory,

- *EMERGENCY_STOP*: sent to immediately transfer control of the steam boiler to the operators.

The physical units send the following administrative messages to the controller:

- *STOP*: when the controller receives this message three times in a row, the program goes into *emergency_stop* mode,
- *STEAM_BOILER_WAITING*: sent in *initialization* mode to trigger the start of the program,
- *PHYSICAL_UNITS_READY*: sent in *initialization* mode to acknowledge a *PROGRAM_READY* message.

A solution to the steam boiler problem is an implementation of a controller program that will keep the water level in the boiler within the normal operating range by receiving and sending messages through the message system. If for some reason the water level threatens to go outside of the safe operating range, the controller should immediately transmit an *EMERGENCY_STOP* message, and halt.

The operation of the program is cyclic. Every five seconds, the program receives the incoming messages from the steam boiler components. It then computes the set of messages that should be sent out to the components, and transmits those messages. In each cycle, all messages are assumed to be received or transmitted simultaneously.

Components of the steam boiler can become defective. Defective components determine (for the most part) the operation mode of the controller. The operation modes and their corresponding conditions (mostly) are:

initialization : the steam boiler is not yet operating;

normal : no component is defective;

degraded : any component except the water level monitor is defective;

rescue : the water level monitor is defective, but the steam monitor is not. In *rescue* mode, the controller estimates upper and lower bounds on the water level, based on the dynamics of the boiler. If the controller calculates that either bound will be outside the safe operating range at the next cycle, then the water level is considered to be outside the safe range.

emergency_stop : the water level and steam monitors are both defective, or the water level is threatening to go outside the safe range.

When the program detects that a component is faulty, it sends an appropriate message to the operator desk.

After the component is repaired, an appropriate message is sent to the controller to inform it of the repair.

4 The Situation Calculus Language

The instantiation of McCarthy's [MH69] situation calculus language used in this paper to formalize the steam boiler controller is due to Reiter [Rei96], largely influenced by Pinto's [Pin94] work on concurrency and continuous processes. The language has the following ontology:

- a sort *situation*, and a distinguished situation constant symbol S_0 .
- a sort *time* ranging over the reals.
- a sort *action* of *simple* actions. All actions are instantaneous, and are denoted by a family of functions that take a parameter in the last argument position denoting the time of the action's occurrence. Variables a, a' , etc. are used for simple actions.
- a sort *concurrent* of concurrent actions which are sets of simple actions. Variables c, c' , etc. are used for concurrent actions.
- a function symbol $time : action \rightarrow \mathfrak{R}$, where $time(a)$ denotes the time of the action a .
- a function symbol $start : situation \rightarrow \mathfrak{R}$, where $start(s)$ denotes the start time of the situation s .
- a function symbol $do : action \times situation \rightarrow situation$.
- The predicate symbol $Poss$, where $Poss(a, s)$ means that the simple action a is possible in situation s (and similarly for any concurrent action c).
- The predicate symbol $<$, where $s < s'$ means that s' is reachable from s through the execution of a sequence of possible actions (simple or concurrent).
- The foundational axioms for the concurrent temporal situation calculus, provided in [Rei96], which are generalizations of those provided in [LR94] and [Rei93] for the nonconcurrent situation calculus. These axioms include unique names axioms for situations, a definition for $<$, a coherency criterion for concurrent actions, and an induction axiom.

4.1 Axiomatizing Application Domains

Levesque *et al.* [LRL⁺96] list the general types of axioms required to formalize an application domain in the situation calculus. In particular, our axiomatization consists of the following axioms:

- For each *simple* action A , a single action precondition axiom of the form

$$Poss(A(\vec{x}, t), s) \equiv start(s) \leq t \wedge \Phi(\vec{x}, t, s)$$

where $\Phi(\vec{x}, t, s)$ is any first order formula with free variables among \vec{x} , t , and s whose only term of sort *situation* is s .

- For each fluent f (except for *defined fluents*, which are defined in terms of other fluents), a single successor state axiom. The form of a successor state axiom for a relational fluent, F , is

$$Poss(c, s) \supset F(\vec{x}, do(c, s)) \equiv \gamma_F^+(\vec{x}, c, s) \vee F(\vec{x}, s) \wedge \neg \gamma_F^-(\vec{x}, c, s)$$

where $\gamma_F^+(\vec{x}, c, s)$ and $\gamma_F^-(\vec{x}, c, s)$ denote the conditions under which c , if performed in s , results in $F(\vec{x}, do(c, s))$ becoming true and false, respectively.

For a functional fluent, f , the form of the successor state axiom is

$$Poss(c, s) \supset f(\vec{x}, do(c, s)) = y \equiv \gamma_f(\vec{x}, y, c, s) \vee y = f(\vec{x}, s) \wedge \neg(\exists y') \gamma_f(\vec{x}, y', c, s)$$

Here, $\gamma_f(\vec{x}, y, c, s)$ is a first order formula whose free variables are among \vec{x} , y , c , s . In the case of Successor State Axiom 2, $\gamma_{position}(\vec{x}, f, c, s)$ is

$$\begin{aligned} & [(\exists t') bounce(ball, t') \in c \wedge catch(ball, t') \notin c \wedge \\ & time(c) = t_0 \wedge \\ & (\forall t) f(t) = 0 - \frac{d}{dt}(position(ball, s))(t')(t - t_0) - \\ & \quad 1/2g(t - t_0)^2] \\ & \vee \\ & [(\exists t') catch(ball, t') \in c \wedge \\ & (\forall t) f(t) = position(ball, s)(t')] \end{aligned}$$

- Unique names axioms for the primitive actions.
- Axioms describing the initial situation.
- The foundational axioms mentioned in the previous section.

5 Formalizing the Steam Boiler Specification

The first step in implementing a steam boiler controller with the situation calculus is to reconcile the inherently procedural operation of a steam boiler controller with the inherently declarative nature of the situation calculus.

The issue is the following. The axiomatizer cannot completely specify what the behavior of the controller will be after it is put into service, because the information comprising the incoming messages that will be received at run-time is not available to her at the time of specification. She cannot write down, for example, that at time t , the controller will receive message m , and do x .

Knowledge-producing actions are required to handle this issue properly (see, for example, [LLL⁺96, SL93]). The receipt of a message would be represented by the execution of a knowledge-producing action. The axiomatizer would be able to write down that at time t , the controller will receive a message, and if the message is m_1 , the controller will do x_1 , but if the message is m_2 , the controller will do x_2 , etc.

In order to keep the particular implementation presented in this paper as simple as possible, we do not use knowledge producing actions. We deal with the issue of incoming messages non-logically, and in order to not completely betray one of the main benefits of the situation calculus approach to the steam boiler problem, namely, that the the approach is logical, we must be careful about these non-logical properties.

We define a predicate $input(m, t)$, which asserts that message m is ready to be received by the controller at time t . We handle incoming messages with a **PROLOG assert** statement, which updates the definition of the $input(m, t)$ predicate as messages are received. When executing a specification that is continually updated in this way, using the **assert** statement, the logical consequences actually used by the controller are all and only those logical consequences that would be used by the controller if all knowledge about future incoming messages were known and specified before the controller is put into service.

The general operation of the situation calculus implementation is as follows:

1. Every five seconds, a set of messages are received from the steam boiler. For each of these messages, m , $Poss(receive(m, t), s)$ is now true at the current time t in the current situation s .
2. The concurrent action consisting of the complete set of $receive(m, t)$ actions is performed, and the values of the fluents are affected accordingly.
3. The new values of the fluents make more actions possible immediately. Since all the actions are natural, any action that is possible (and not prevented by an earlier action) is carried out.
4. The first actions to become possible are those that change the mode of operation of the controller, if any.
5. After the mode has stabilized, a complex action consisting of a set of $transmit(m, t)$ actions will be possible, and carried out.
6. The situation resulting from transmitting messages is stable, and the next actions to be possible are the actions to receive the messages in the next cycle.

In the following sections, we show what such a specification looks like. Rather than present the entire specification, we present enough to show the reader how it

can be constructed.

5.1 Actions

The following actions are sufficient to model the steam boiler:

- *receive*(m, t): receive message m at time t
- *transmit*(m, t): transmit message m at time t
- *switch_to_mode*(m, t): switch to operation mode m at time t .

These are all natural actions.

5.2 Fluents

The fluents described in this section comprise a sufficient notion of the state of the system. The names of fluents are chosen to be consistent with the original steam boiler specification. The various quantities (e.g. the water throughput of a pump) are considered to be within an upper and lower bound, and each bound has three values associated with it: a *claimed* value, which is the corresponding sensor reading, a *calculated* value, which is calculated by the controller using its knowledge of the dynamics of the boiler, and a *best estimate*, which is the same as the claimed value if the sensor is not defective, and the same as the calculated value if the sensor is defective. Note that the upper and lower bounds on a quantity are both equal to the sensor reading of that quantity if the corresponding sensor is not defective.

mode(s) = z : the controller's mode of operation is z , one of {*initialization*, *normal*, *degraded*, *rescue*, *emergency_stop*}

cur_receive_time(s) = z : the controller will next receive messages at time z

waiting_begin_flow(n, s) = z : z is the number of transmissions received since pump n was turned on, and pump controller n has not yet confirmed the flow starting (if the pump has not been turned on, $z = -1$)

waiting_stop_flow(n, s) = z : z is the number of transmissions received since pump n was turned off, and pump controller n has not yet confirmed the flow ceasing (if the pump has not been turned off, $z = -1$)

q(s) = z : the last transmission contained a message claiming the quantity of water in the boiler was z

v(s) = z : the last transmission contained a message claiming the quantity of steam exiting the boiler was z

qc1(s) = z : z , a function of time, is the calculated lower bound on the quantity of water in the boiler

qc2(s) = z : z , a function of time, is the calculated upper bound on the quantity of water in the boiler

pa1(s) = z : z is the best estimate of the lower bound on the (constant) throughput of the pumps.

pa2(s) = z : z is the best estimate of the upper bound on the (constant) throughput of the pumps.

pc1(s) = z : z is the calculated lower bound on the (constant) throughput of the pumps.

pc2(s) = z : z is the calculated upper bound on the (constant) throughput of the pumps.

vc1(s) = z : z , a function of time, is the calculated minimum rate of steam leaving the boiler

vc2(s) = z : z , a function of time, is the calculated upper bound on the rate of steam leaving the boiler

qa1(s) = z : z is the best estimate of the lower bound on the quantity of water in the boiler at the start of s

qa2(s) = z : z is the best estimate of the upper bound on the quantity of water in the boiler at the start of s

va1(s) = z : z is the best estimate of the lower bound on the rate of steam leaving the boiler at the start of s

va2(s) = z : z is the best estimate of the upper bound on the rate of steam leaving the boiler at the start of s

transmitted(m, s) : message m was transmitted at the start of s

received(m, t, s) : message m was received at time t in s

transmission_error(s) : a transmission error occurred at the start of s (e.g. a mandatory message was missing from a transmission)

defective(x, s) : component x is defective

steam_boiler_waiting(s) : the steam boiler is waiting for the controller to indicate it is ready to come on-line

program_ready(s) : the program is ready to come on line

physical_units_ready(s) : the steam boiler is ready for control to begin

pump_state(n, b, s) : *pump*(n) has been shut off ($b = 0$), or turned on ($b = 1$)

pump_control_state(n, b, s) : the last transmission contained a message claiming that water from *pump*(n) was ($b = 1$) or was not ($b = 0$) flowing

valve_open(s) : the valve to let water drain out of the steam boiler is open

waiting_ack(m, s) : the controller is waiting for acknowledgement message m

send_ack(x, s) : the controller should send acknowledgement message m in the next transmission

5.3 Initial Situation

The situation is S_0 when the controller is turned on: $mode(S_0) = initialization$, $q(S_0) = 0$, $pa1(S_0)(t) = 0$, $pa2(S_0)(t) = 0$, $v(S_0)(t) = 0$, $\neg defective(x, S_0)$, etc.

5.4 Precondition Axioms

In practice, it is possible to receive a message when that message arrives, and we know that messages will arrive approximately every five seconds. The PROLOG simulator that executes the situation calculus specification is responsible for controlling the timing of the transmit/receive cycle.

To ensure the program detects the absence of a transmission, we invent a message, *tick*, which is guaranteed to be received every five seconds. The value of the *transmission_error(s)* fluent is determined by considering what messages were received with each tick. The theorem prover (we use PROLOG) updates the definition of the *input(m, t)* predicate (using the PROLOG **assert** statement) as messages arrive. The *input(m, t)* predicate asserts that message m is ready to be received at time t .

The following axiom characterizes when messages are actually received (rather than only ready to be received):

$$\begin{aligned} Poss(receive(m, t), s) \equiv \\ t \geq start(s) \wedge t = cur_receive_time(s) \wedge \\ [input(m, t) \vee m = tick] \end{aligned} \quad (3)$$

The precondition axiom for the *transmit(m, t)* action is such that messages are transmitted exactly when they are appropriate for proper operation of the controller. The axiom ensures that the controller's mode has stabilized before any messages are transmitted. If the controller is in *emergency_stop* mode, only the message $MODE(emergency_stop)$ should be transmitted. Also, is not possible to transmit a message that was just transmitted. These conditions are dictated by the following defined fluent:

$$\begin{aligned} transmit_cond(m, t, s) \equiv \\ t \geq start(s) \wedge mode(s) \neq emergency_stop \wedge \\ \neg[(\exists t') \neg Poss(switch_to_mode(m', t'), s)] \wedge \\ \neg transmitted(m, s) \end{aligned}$$

In addition, the decision to switch the pumps on or off is characterized by the following defined fluent:

$$\begin{aligned} need_pumps(s) \equiv \\ mode(s) \neq initialization \wedge \\ [[qa1(s) < N_1 \wedge qa2(s) < N_1] \vee \\ [qa1(s) < N_1 \wedge N_1 < qa2(s) \wedge qa2(s) < N_2]], \end{aligned}$$

where N_1 and N_2 are the upper and lower limits, respectively, of the normal operating range for the water level in the boiler. Control strategies other than

this one are possible; however, this one is proposed in [Abr94] as a reasonable candidate.

Given these two defined fluents, the precondition axiom for the *transmit(m, t)* action is:

$$\begin{aligned} Poss(transmit(m, t), s) \equiv \\ m = MODE(emergency_stop) \wedge t \geq start(s) \wedge \\ mode(s) = emergency_stop \wedge \neg transmitted(m, s) \\ \vee \\ m = MODE(mode(s)) \wedge transmit_cond(m, t, s) \\ \vee \\ m = PROGRAM_READY \wedge \\ transmit_cond(m, s, t) \wedge \\ mode(s) = initialization \wedge program_ready(s) \\ \vee \\ m = VALVE \wedge transmit_cond(m, s, t) \wedge \\ mode(s) = initialization \wedge \\ steam_boiler_waiting(s) \wedge \\ [\neg valve_open(s) \wedge q(s) > N_2 \vee \\ valve_open(s) \wedge q(s) > N_1] \\ \vee \\ (\exists n)m = OPEN_PUMP(n) \wedge \\ transmit_cond(m, s, t) \wedge \\ need_pumps(s) \wedge \\ [n = 1 \vee n = 2 \vee n = 3 \vee n = 4] \wedge \\ \neg defective(pump(n), s) \wedge pump_state(n, 0, s) \\ \vee \\ (\exists n)m = PUMP_FAIL_DETN(n) \wedge \\ waiting_ack(PUMP_FAIL_ACK(n), s) \wedge \\ transmit_cond(m, s, t) \wedge defective(pump(n), s) \\ \vee \dots \\ \vee \\ m = STEAM_REPD_ACK \wedge \\ transmit_cond(m, s, t) \wedge \\ send_ack(STEAM_REPD_ACK) \end{aligned} \quad (4)$$

The precondition axiom for the *switch_to_mode(m, t)* fluent governs the mode state changes of the controller. The axiom says, for example, that the controller switches to mode *normal* if nothing is defective, and either the mode is *initialization* and the physical units are ready, or the mode is *rescue*, or the mode is *degraded*.

$$\begin{aligned} Poss(switch_to_mode(m, t), s) \equiv \\ t \geq start(s) \wedge \\ [m = normal \wedge \neg defective(x, s) \wedge \\ [mode(s) = initialization \wedge \\ physical_units_ready(s) \vee \\ mode(s) = rescue \vee mode(s) = degraded]] \end{aligned}$$

$$\begin{aligned}
& \vee \\
& m = degraded \wedge \\
& [mode(s) = normal \vee mode(s) = rescue] \wedge \\
& [(\exists x)defective(x, s)] \wedge \\
& [(\forall x)defective(x, s) \supset x \neq water_level] \\
& \vee \\
& m = rescue \wedge \\
& [mode(s) = degraded \vee mode(s) = normal] \\
& \wedge defective(water_level, s) \\
& \vee \\
& m = emergency_stop \wedge \\
& [mode = initialization \wedge \\
& [defective(steam_rate, s) \vee \\
& defective(water_level, s)] \vee \\
& transmission_error(s) \vee water_level_risk(s) \vee \\
& mode(s) = rescue \wedge [defective(steam_rate, s) \vee \\
& (\exists n)defective(pump_control(n), s)]]] \quad (5)
\end{aligned}$$

5.5 Successor State Axioms

We present just the most interesting, representative successor state axioms.

The successor state axiom for the $mode(s) = m$ fluent is straightforward. The only action that can affect the mode of the program is a $switch_to_mode(m, t)$ action:

$$\begin{aligned}
Poss(c, s) \supset mode(do(c, s)) = m & \equiv \\
switch_to_mode(m, time(c)) \in c & \vee \quad (6) \\
switch_to_mode(m', time(c)) \notin c \wedge mode(s) = m &
\end{aligned}$$

The successor state axiom for $defective(x, s)$ characterizes the conditions under which a component is considered defective. It says, among other things, that $pump(n)$ is defective if it changes state spontaneously, or if an $OPEN_PUMP(n)$ or $CLOSE_PUMP(n)$ message were sent in the previous cycle, but the flow has not yet started or stopped, respectively.

$$\begin{aligned}
Poss(c, s) \supset defective(x, do(c, s)) & \equiv \\
(\exists n)x = pump(n) \wedge & \\
[[[(\exists b)receive(PUMP_STATE(n, b), time(c)) \in c & \\
\wedge (\exists a)pump_state(n, a, s) \wedge a \neq b] \vee & \\
pump_state(n, 0, s) \wedge & \\
waiting_begin_flow(n, s) = 1 \vee & \\
pump_state(n, 1, s) \wedge & \\
waiting_stop_flow(n, s) = 1] \vee & \\
receive(PUMP_STATE(n, b), time(c)) \notin c \wedge & \\
defective(x, s)] & \\
\vee \dots & \quad (7)
\end{aligned}$$

5.6 Defined Fluents

Defined fluents are fluents that are defined in terms of other fluents. We could write down a successor state axiom for any defined fluent. It would be a compilation of the successor state axioms of the fluents in the definition of the defined fluent that have a situation argument of the form $do(c, s)$. However, the resulting successor state axiom would be larger and more complicated than the defined fluent.

The defined fluent $qa2(s) = z$ means that z is the best estimate of the upper bound on the quantity of water in the boiler. If the water level detection equipment is not defective, the program accepts the value given by that equipment as the best estimate; otherwise, it uses the value calculated by $qc2(s)(t)$ at the time of the action which started the situation. The formula for $qa1$ is similar to this one for $qa2$:

$$\begin{aligned}
qa2(do(c, s)) = z & \equiv \\
defective(water_level, s) \wedge z = qc2(s)(time(c)) \vee & \\
\neg defective(water_level, s) \wedge z = q(do(c, s)) & \quad (8)
\end{aligned}$$

6 The Situation Calculus Simulator

In this section we discuss a PROLOG technology simulator. The simulator can simulate a concurrent situation calculus specification like the steam boiler formalization presented in the previous section.

6.1 The PROLOG Simulator

A situation calculus model defines a tree of situations emanating from the distinguished situation S_0 . Some of the situations in the tree correspond to *legal* situations, and some do not. A legal situation is consistent with the laws of Nature, in that a natural action must occur at the time dictated by natural laws governing the behavior of the system, unless the action is prevented from occurring by an earlier action. Reiter [Rei96] defines the $legal(s)$ predicate to formalize this principle:

$$\begin{aligned}
legal(s) & \equiv \\
S_0 \leq s \wedge & \\
(\forall a, c, s'). natural(a) \wedge Poss(a, s') \wedge & \\
do(c, s') \leq s \supset a \in c \vee time(c) < time(a). & \quad (9)
\end{aligned}$$

Here, \leq is the ordering relation defined by the foundational axioms mentioned earlier. The $legal$ predicate is instrumental in the implementation of a simulator, as will become clear.

A domain of discourse in which all actions are natural is said to comply with Reiter's [Rei96] Natural World Condition (*NWC*). This condition assures a deterministic simulation.

Another concept crucial to the implementation of a simulator is the notion of Reiter's [Rei96] Least Natural Time Points:

$$\begin{aligned} \text{lntp}(s, t) \equiv & \quad (10) \\ & (\exists a)[\text{natural}(a) \wedge \text{Poss}(a, s) \wedge \text{time}(a) = t] \wedge \\ & (\forall a)[\text{natural}(a) \wedge \text{Poss}(a, s) \supset \text{time}(a) \geq t]. \end{aligned}$$

Informally, the least natural time point is the earliest time at which any natural action can possibly occur in a situation. The Least Natural Time Point Condition (*LNTPC*) is the following:

$$(\forall s).(\exists a)[\text{natural}(a) \wedge \text{Poss}(a, s)] \supset (\exists t)\text{lntp}(s, t). \quad (11)$$

This condition states that every situation in which there is a possible natural action has a least natural time point. An example of a world where this condition fails is one in which we have $(\forall a).\text{natural}(a) \equiv (\exists x, t)a = B(x, t)$, where x ranges over the non-zero natural numbers, and $\text{Poss}(B(x, t), s) \equiv t = \text{start}(s) + 1/x$.

Reiter [Rei96] puts this all together with his foundational axioms for the concurrent temporal situation calculus and proves:

$$\begin{aligned} \text{LNTPC} \wedge \text{NWC} \supset \text{legal}(\text{do}(c, s)) \equiv \\ \{ \text{legal}(s) \wedge \text{Poss}(c, s) \wedge \text{start}(s) < \text{time}(c) \wedge \\ (\forall a)[a \in c \equiv \text{Poss}(a, s) \wedge \text{lntp}(s, \text{time}(a))] \} \quad (12) \end{aligned}$$

Formula 12 is the engine for the simulator. The simulator is a PROLOG procedure that takes a situation term s as an argument (initially S_0), prints its argument, constructs a set of actions c such that

$$(\forall a)[a \in c \equiv \text{Poss}(a, s) \wedge \text{lntp}(s, \text{time}(a))],$$

and recursively calls itself with $\text{do}(c, s)$. In so doing, the simulator follows the path of legal situations (there is only one path of legal situations when all actions are natural), simulating the evolution of the system.

Here is the PROLOG code:

```
simulate(S) :-
  nl,nl,print(S),
  setof(A,lntp(S,A),C),
  simulate(do(C,S)).
```

```
lntp(S,A) :-
  natural(A),
  poss(A,S),
  time(A,T),
  not (
    natural(A_prime),
    poss(A_prime,S),
    time(A_prime,T_prime),
    T > T_prime
  ).
```

The version of this code for use with the steam boiler controller needs to add information about incoming messages as the simulation proceeds, so the `simulate(S)` procedure becomes:

```
simulate(S) :-
  setof(A,lntp(S,A),C),
  transmit_messages(C),
  simulate(do(C,S))
;
  read(Transmission),
  receive_messages(Transmission),
  simulate(S).
```

The `transmit_messages(C)` procedure actually transmits any messages, m , from $\text{transmit}(m, t)$ actions that are present in the concurrent action, C . When no more natural actions are possible (when the `setof(A,lntp(S,A),C)` procedure fails), the controller process is blocked by the `read(Transmission)` procedure until a transmission arrives from the steam boiler. Upon receiving a new set of messages, more natural actions are enabled, and control of the steam boiler continues.

6.2 Translating a Model to PROLOG

Clark's completion semantics for logic programming ([Cla78]) admit a translation from the situation calculus axioms to PROLOG clauses. The procedure is to simply make the implication in the axioms go only one way, and write down the clausal form. For example, the PROLOG equivalent of Axiom 6 is

```
mode(do(C,S),M) :-
  poss(C,S),
  (member(switch_to_mode(M,T),C),
  ;
  not member(switch_to_mode(M_prime,T),C),
  mode(S,M)).
```

6.3 Simulation

The situation calculus steam boiler controller is capable of controlling the FZI simulation ([Lot95]) of the Dagstuhl steam boiler. The following situation term (read from bottom to top) denotes the course of action associated with initialization and startup. After the level of water drops below 400, the pumps are turned on. At time 20 water is flowing at the pump controllers, and the level of water in the boiler is rising due to the influx of water.

```
do([receive(level(443.0),20),
  receive(steam(12.0),20),
  receive(PUMP_STATE(1,1),20),...,
  receive(PUMP_CONTROL_STATE(1,1),20)],
do([transmit(MODE(NORMAL),15)],
do([receive(level(375.5),15),
  receive(steam(7.0),15),
  receive(PUMP_STATE(1,1),15),...,
  receive(PUMP_CONTROL_STATE(1,0),15)],
do([transmit(MODE(NORMAL),5),
  transmit(OPEN_PUMP(1),10),...,
```

```

    transmit(OPEN_PUMP(4),10)],
do([receive(level(398.0),10),
    receive(steam(2.0),10),
    receive(PUMP_STATE(1,0),10),...,
    receive(PUMP_CONTROL_STATE(1,0),10)],
do([transmit(MODE(NORMAL),5)],
do([switch_to_mode(normal,5)],
do([receive(PHYSICAL_UNITS_READY,5),
    receive(level(400.0),5),
    receive(steam(0.0),5),
    receive(PUMP_STATE(1,0),5),...,
    receive(PUMP_CONTROL_STATE(1,0),5)],
do([transmit(PROGRAM_READY,0),
    transmit(MODE(INITIALIZATION),0),
do([receive(STEAM_BOILER_WAITING,0)],s0)...)
```

7 Evaluation of the Solution

In this section, we attempt to apply the evaluation criteria given in [ABL95] to this formalization and simulation. These criteria were formulated by participants at the Dagstuhl meeting to evaluate various solutions to the steam boiler problem and to compare the specific merits and drawbacks of the formal methods used in those solutions. We paraphrase the criteria in the following subsections.

7.1 Formality and Rigor

Is the requirements specification of the solution formal and rigorous, and can the functional and architectural designs be formally and rigorously verified against the specification?

The situation calculus solution is especially strong in this regard, since the specification (at least implicitly) constitutes a functional and architectural design, and it is an implementation, executable on a provably correct simulator.

Other solutions to the problem are based on logical formalisms, but those formalisms are separate from the actual implementation. For example, Leßke and Merz ([LM95]) use Lamport's Temporal Logic of Actions (TLA) [Lam94] in their solution, leaving the implementation language open. They consider this a feature, since the implementation language can be chosen to suite a variety of machine architectures. Rischel *et al* ([RCM+95]) use a specification language that has a real-time interval logic semantics for the specification, and they use C code for the implementation.

7.2 Practicality

Has the solution actually been implemented and can it control the FZI simulation [Lot95] of the steam boiler?

The situation calculus solution is also strong in this regard, since an elementary change in syntax of the spec-

ification produces a working implementation. Many of the other solutions produced working implementations.

7.3 Readability and Ease of Use

What level of specialized knowledge is required to read and work with the formalism? How much effort did the solution to the problem require?

The situation calculus is essentially a standard first-order predicate calculus language. Hence, it is conceivable that anyone familiar with the predicate calculus would be able to read the language, even without any prior situation calculus experience.

On the other hand, the situation calculus steam boiler solution is at the implementation level. Other than the general form of a situation calculus specification, the situation calculus has not yet been associated with any well defined methodology involving higher-level abstraction, stepwise refinement, or modularization. This is in contrast to the many of the other solutions, whose formalisms have been designed, at least in part, with ease of use and readability as a primary concern, often as part of a specification methodology.

One such methodology is GrafTab ([SI95]), which uses graphs to describe the flow of the system states, and tables to specify the state condition and actions in the states. A GrafTab solution consists of four distinct documents.

Although readability and ease of use are not the primary design goals of the situation calculus, modeling methodologies and software programs to aid in the development of situation calculus specifications might well receive the attention of researchers in the future.

Acknowledgements

Ray Reiter provided useful comments and important corrections. I have also benefited from discussions with Javier Pinto.

References

- [ABL95] Jean-Raymond Abrial, Egon Boerger, and Hans Langmaack. Preliminary report for the Dagstuhl-seminar 9523: Methods for semantics and specification. Available via WWW at <http://www.informatik.uni-kiel.de/~procos/dag9523/dag9523.html>, 1995.
- [Abr94] Jean-Raymond Abrial. Steam-boiler control specification problem. Distributed to the participants of the Dagstuhl Meeting, "Methods for Semantics and Specification", June 4-9, 1995. This paper,

- and its companion, “Additional information concerning the physical behavior of the steam boiler”, are available via WWW at <http://www.informatik.uni-kiel.de/~procos/dag9523/dag9523.html>, August 1994.
- [Cla78] K. L. Clark. Negation as failure. In Hervé Gallaire and Jack Minker, editors, *Logic and Data Bases*, pages 293–322. Plenum Press, New York, 1978.
- [Kel96] T. G. Kelley. Reasoning about physical systems with the situation calculus. In *COMMON SENSE '96: the third symposium on logical formalizations of common-sense reasoning*, Stanford University, January 1996.
- [Kui86] Benjamin Kuipers. Qualitative simulation. *Artificial Intelligence*, 29:289–338, 1986.
- [Lot95] Annette Lötzbeier. Simulator for the dagstuhl seminar 1995: Steam boiler control specification problem. The README file and tcl/tk source code for the simulator are available via WWW at <http://www.informatik.uni-kiel.de/~procos/dag9523/dag9523.html>, 1995.
- [Lam94] Leslie Lamport. The temporal logic of actions. *ACM Transactions on Programming Languages and Systems*, 16(3):872–923, 1994.
- [LLL⁺96] Yves Lespérance, Hector J. Levesque, Fangzhen Lin, Daniel Marcu, Raymond Reiter, and Richard B. Scherl. Foundations of a logical approach to agent programming. In M. Wooldridge, J. P. Müller, and M. Tambe, editors, *Intelligent Agents Volume II—Proceedings of the 1995 Workshop on Agent Theories, Architectures, and Languages (ATAL-95)*, pages 331–346. Springer-Verlag, Lecture Notes in Artificial Intelligence, 1996. To Appear.
- [LM95] Frank Leßke and Stephan Merz. Steam boiler control specification problem: A tla solution. This paper is available via WWW at <http://www.informatik.uni-kiel.de/~procos/dag9523/dag9523.html>, September 1995.
- [LR94] F. Lin and R. Reiter. State constraints revisited. *Journal of Logic and Computation*, 4(5):655–678, 1994.
- [LRL⁺96] H. J. Levesque, R. Reiter, Y. Lespérance, F. Lin, and R. Scherl. GOLOG: A logic programming language for dynamic domains. *Journal of Logic Programming, Special Issue on Reasoning about Action and Change*, 1996. To appear.
- [MH69] John McCarthy and Patrick Hayes. Some philosophical problems from the standpoint of artificial intelligence. In B. Meltzer and D. Michie, editors, *Machine Intelligence 4*, pages 463–502. Edinburgh University Press, Edinburgh, Scotland, 1969.
- [Pin94] Javier Andrés Pinto. *Temporal Reasoning in the Situation Calculus*. PhD thesis, University of Toronto, Toronto, Ontario, Canada, February 1994.
- [RCM⁺95] Hans Rischel, Jorge Cuellar, Simon Mørk, Anders P. Ravn, and Isolde Wildgruber. Development of safety-critical real-time systems. This paper is available via WWW at <http://www.informatik.uni-kiel.de/~procos/dag9523/dag9523.html>, 1995.
- [Rei91] R. Reiter. The frame problem in the situation calculus: a simple solution (sometimes) and a completeness result for goal regression. In Vladimir Lifschitz, editor, *Artificial Intelligence and Mathematical Theory of Computation: Papers in Honor of John McCarthy*, pages 359–380. Academic Press, San Diego, CA, 1991.
- [Rei93] R. Reiter. Proving properties of states in the situation calculus. *Artificial Intelligence*, 64:337–351, 1993.
- [Rei96] R. Reiter. Natural actions, concurrency and continuous time in the situation calculus. In L. C. Aiello, J. Doyle, and S. C. Shapiro, editors, *Principles of Knowledge Representation and Reasoning: Proceedings of the Fifth International Conference (KR '96)*. Morgan Kaufmann Publishers, San Francisco, CA, 1996.
- [San89] Erik Sandewall. Combining logic and differential equations for describing real-world systems. In *First International Conference on Principles of Knowledge Representation and Reasoning*, San Mateo, CA, 1989. Morgan Kaufmann.
- [SI95] So-Ming So and Mabo R. Ito. Graftab — an innovative requirements specification method. This paper is available via WWW at <http://www.informatik.uni-kiel.de/~procos/dag9523/dag9523.html>, October 1995.
- [SL93] Richard B. Scherl and Hector J. Levesque. The frame problem and knowledge-producing actions. In *Proceedings of the Eleventh National Conference on Artificial Intelligence*, pages 689–695, Washington, DC, July 1993. AAAI Press/The MIT Press.