

Prophet Inequality Matching Meets Probing with Commitment

Allan Borodin *

Calum MacRury †

Akash Rakheja ‡

Abstract

Within the context of stochastic probing with commitment, we consider the online stochastic matching problem for bipartite graphs where edges adjacent to an online node must be probed to determine if they exist, based on known edge probabilities. If a probed edge exists, it must be used in the matching (if possible). In addition to improving upon existing stochastic bipartite matching results, our results can also be seen as extensions to multi-item prophet inequalities. We study this matching problem for given constraints on the allowable sequences of probes adjacent to an online node. Our setting generalizes the patience (or time-out) constraint which limits the number of probes that can be made to edges. The generality of our setting leads to some modelling and computational efficiency issues that are not encountered in previous works. We establish new competitive bounds all of which generalize the standard non-stochastic setting when edges do not need to be probed (i.e., exist with certainty). Specifically, we establish the following competitive ratio results for a general formulation of edge constraints, arbitrary edge weights, and arbitrary edge probabilities:

1. A tight $\frac{1}{2}$ ratio when the stochastic graph is generated from a known stochastic type graph where the $\pi(i)^{th}$ online node is drawn independently from a known distribution $\mathcal{D}_{\pi(i)}$ and π is chosen adversarially. We refer to this setting as the known i.d. stochastic matching problem with adversarial arrivals.
2. A $1 - 1/e$ ratio when the stochastic graph is generated from a known stochastic type graph where the $\pi(i)^{th}$ online node is drawn independently from a known distribution $\mathcal{D}_{\pi(i)}$ and π is a random permutation. This is referred to as the known i.d. stochastic matching problem with random order arrivals.

We note that the known i.d. model generalizes the online stochastic matching model where the stochastic graph (but not the edge probabilities nor the order of online arrivals) is known to the algorithm. Our i.d. model also generalizes the prophet inequality and prophet secretary models to the probing setting.

In deriving our results, we clarify and expand upon previous offline benchmarks, relative to which one defines an appropriate definition of the competitive ratio. In particular, we introduce a new LP relaxation which upper bounds the performance of “an optimum offline probing algorithm”. This new LP allows us to overcome some previous negative results (i.e. stochasticity gaps). While this LP has exponentially many variables, it has polynomially many constraints and we show how it can be solved efficiently (i.e., in polynomial time) under some mild assumptions on the edge probing constraints.

*Department of Computer Science, University of Toronto, Toronto, ON, Canada bor@cs.toronto.edu

†Department of Computer Science, University of Toronto, Toronto, ON, Canada cmacrury@cs.toronto.edu

‡Department of Computer Science, University of Toronto, Toronto, ON, Canada rakhejaakash@gmail.com

1 Introduction

Stochastic probing problems are part of the larger area of decision making under uncertainty and more specifically, stochastic optimization. Unlike more standard forms of stochastic optimization, it is not just that there is some stochastic uncertainty in the set of inputs, stochastic probing problems involve inputs that cannot be determined without probing (at some cost and/or within some constraint). Applications of stochastic probing occur naturally in many settings, such as in matching problems where compatibility cannot be determined without some trial or investigation (for example, in online dating and kidney exchange applications). There is by now an extensive literature for stochastic matching problems. For space efficiency, we will give an extended overview of related work in Appendix C. Research most directly relating to this paper will appear as we proceed.

The *stochastic matching problem*¹ was introduced by Chen et al. [20]. In this problem, we are given an adversarially generated *stochastic graph* $G = (V, E)$ with a probability p_e associated with each edge e and a patience (or timeout) parameter ℓ_v associated with each vertex v . An algorithm probes edges in E within the constraint that at most ℓ_v edges are probed incident to any particular vertex $v \in V$. The patience constraint can be viewed as a simple budgetary constraint, where each probe has unit cost and the patience constraint is the budget. When an edge e is probed, it is guaranteed to exist with probability exactly p_e . If an edge (u, v) is found to exist, then the algorithm must *commit* to the edge – that is, it must be added to the current matching (if possible). The goal is to maximize the expected size of a matching constructed in this way. This problem can be generalized to offline vertices or edges having weights and then the objective is to maximize the expected weight of the matching. Notably, in Chen et al., the algorithm knows the entire stochastic graph in advance.

In addition to generalizing the setting of the results of Chen et al., Bansal et al. [9] introduced an i.i.d. (one-sided) bipartite version of the problem where nodes on one side of the partition arrive online and edges adjacent to that node are then probed. In their model, each online vertex (and its adjacent edges) is drawn independently and identically from a known distribution. That is, the possible “type” of each online node (i.e., the adjacent edge probabilities and edge weights) is known and the input sequence is then determined i.i.d. from this known distribution, where the type of a node is presented to the algorithm upon arrival. In the Bansal et al. model, each offline node has unlimited patience, whereas each online node specifies its patience upon arrival. The match for an online node must be made before the next online arrival. As in the Chen et al. model, if an edge is probed and confirmed to exist, then it must be included in the current matching (if possible). This problem is referred to as the *online stochastic matching problem*² (with patience) and also referred to as the *stochastic rewards problem*.

In more general settings, we will study the (one-sided) online bipartite stochastic matching problem. More specifically, we generalize the patience constraint to apply to any downward-closed set of constraints including a budget constraint³. We first consider the original stochastic matching setting where the algorithm knows the stochastic graph, and the online vertices arrive either in

¹Unfortunately, the term “stochastic matching” is also used to refer to more standard optimization where the input (i.e., edges or vertices) are drawn from some known or unknown distributions but no probing is involved.

²The online stochastic matching problem is sometimes meant to imply unit patience but we will be interested in results which hold for more general probing constraints.

³A budget constraint involves placing a budget $B_v \geq 0$ on $v \in V$ and costs $(c_e)_{e \in \partial(v)}$ on its adjacent edges. The cost of the probed edges then cannot exceed B_v .

adversarial order or in random order (i.e., the ROM model). We then consider the more general i.i.d. distributional setting where the stochastic graph is generated from a known stochastic type graph with each online vertex being generated independently from a known distribution; that is, we consider independent but not (necessarily) identical distributions. When the online vertex order is adversarial, our framework generalizes the prophet inequality matching problem of Alaei et al. [6]. When online vertices arrive in random order, we are generalizing the prophet secretary matching problem of Ehsani et al. [27]. We note that prophet inequalities give rise to (and in some sense are equivalent to) order oblivious posted price mechanisms, as first studied in Hajiaghayi et al. [38] and further developed for multi-parameter settings in Chawla et al. [19] and recently in Correa et al. [21].

We note that these stochastic matching models generalize the corresponding classical non-stochastic worst case and i.i.d input models where edges adjacent to an online node are known upon arrival and do not need to be probed. It follows that any inapproximation results in the classical setting apply to the corresponding stochastic matching setting.

Amongst other applications, the online stochastic matching problem notably models online advertising where the probability of an edge can correspond to the probability of a purchase in online stores or to pay-per-click revenue in online searching. One may also consider a real estate agent (or owner) of several properties working with individual clients each day and first looking at properties online. Each buyer has a value for each property but will not purchase until she has seen the house in person at which time she will decide whether or not to buy. You can only probabilistically estimate the likelihood of the buyer being satisfied. But you have limited patience (or time) to visit properties and usually want to do so in a reasonably efficient way. In these examples, the objective is clearly (respectively) to maximize the revenue of actual sales or clicks and (respectively) to maximize the value of the properties sold.

1.1 Our Results

We now informally point ahead to our main results. Our results will be stated more formally in Section 2 following the relevant definitions. Proofs of the main results will be given in Sections 3 and 4. All of our results apply to general constraints on allowable probing sequences (generalizing patience constraints) and the competitive ratios are with respect to an optimum *offline* probing algorithm (the adaptive benchmark) which we define precisely in Section 2. Our results for the case of a known stochastic graph are subsumed by the analogous results for the known i.i.d. model but we state them here so as to relate these results to previous work.

1. Theorem 2.1 shows that Algorithm 4 is a non-adaptive algorithm with competitive ratio $1 - 1/e$ in the following setting:

- There is a known edge-weighted stochastic graph.
- Online vertices are presented in random order.

Algorithm 4 is non-adaptive in the sense that its probes are a randomized function of the stochastic graph it executes on. In particular, the probes of an arriving online node do not depend on the probed edge states of the previous online nodes. Non-adaptive probing algorithms were first studied in Dean et al. [23] for the stochastic knapsack problem, as they

are conceptually simpler than adaptive probing algorithms, and require far less space to be specified.

The work of Gamlath et al. [32] showed that a $1 - 1/e$ competitive ratio is possible when there are no constraints on the online vertices. Our result can therefore be viewed as an extension of their result to general probing constraints. Our result also shows that the Brubach et al. [15] 0.544 inapproximation bound against the Bansal et al. [9] LP does not hold with respect to our new LP relaxation.

In Theorem 2.2, we provide a negative result which shows that Theorem 2.1 is an optimum result for non-adaptive online probing algorithms⁴. Roughly speaking, in our setting, we define the adaptivity gap to be the worst case ratio of performance between the *optimum* non-adaptive online probing algorithm, and the adaptive benchmark. We conclude that the online stochastic matching has an adaptivity gap of precisely $1 - 1/e$. Adaptivity gaps were initially studied by Dean et al., and have since received lots of attention (see [35, 7, 36, 37, 14] for some of the latest results).

2. Theorem 2.6 shows that Algorithm 6 is a non-adaptive online algorithm with competitive ratio $1 - \frac{1}{e}$ in the following stochastic i.d. setting (improving upon the previously best i.i.d. ratio of 0.46 in [15]).
 - There is a known edge weighted stochastic (type) graph.
 - Online vertices are drawn independently from distributions on the online vertices thereby producing an edge-weighted stochastic graph.
 - The instantiation of the stochastic graph from the type graph is not known to the algorithm. Online vertices are in random order.

In the classical i.i.d. setting with non-integral arrival rates, Manshadi et al. [49] present an example that shows that $1 - 1/e$ is optimal for **classically non-adaptive** online algorithms. Manshadi et al. [49] use the terminology non-adaptive to mean that a (classical) online algorithm in the known i.i.d. setting uses only the *type* of the arriving node to determine its matching decisions. Our definition of non-adaptivity for an online probing algorithm in the known i.d. setting generalizes this classical definition (and well as our definition from the known stochastic graph setting) as we discuss in Subsection 2.1. Since our probing algorithm fits this classical definition, it has an optimal competitive ratio amongst this restricted class of probing algorithms.

3. Theorem 2.7 shows that Algorithm 8 is an online algorithm with competitive ratio $\frac{1}{2}$ in the following stochastic i.d. setting:
 - There is a known edge weighted stochastic (type) graph.
 - Online vertices are drawn independently from distributions on the online vertices thereby producing an edge-weighted stochastic graph.
 - The instantiation of the stochastic graph from the type graph is not known to the algorithm or the adversary who chooses the order of the online vertices.

⁴Our negative result on the adaptivity gap in fact applies to all offline non-adaptive probing algorithms.

This is an optimal competitive ratio following from the inapproximation for the classic single item prophet inequality result due to Krenkel and Sucheston [44]. (See Lucier [47] for a relatively recent review of the prophet inequalities problem and its extensions.)

1.2 Paper Roadmap

In Section 2 we provide the required definitions and precise statements of our main results. In particular, we define the (offline) adaptive benchmark relative to which we state our competitive bounds. We also define the oracles we use to ensure that our algorithms can efficiently abide by the probing constraints.

Section 3 defines a new LP which we use to guide our algorithm for the known stochastic setting. We provide a non-adaptive algorithm that establishes the $1 - 1/e$ competitive ratio in the random order model assuming that the new LP is a relaxation of the adaptive benchmark. Our algorithm makes use of the random order contention scheme (RCRS) for rank 1 matroids utilized by Lee and Singla [46].

Section 4 extends our LP and results to the known i.d. setting. We note that the known i.d. setting subsumes the known stochastic graph setting when each distribution \mathcal{D}_i is a singleton describing the i^{th} online vertex v_i . In this setting we establish a $1 - 1/e$ competitive ratio for the random order model and a $\frac{1}{2}$ ratio for adversarial input sequences. We again use the Lee and Singla [46] RCRS for the ROM setting, and we use the recently studied online contention resolution scheme (OCRS) of Ezra et al. [29] for the adversarial setting.

Section 5 completes the proof that our new LP is a relaxation of the adaptive benchmark (upper bounds the benchmark's value). Note that unlike previously used LP relaxations for probing problems, this fact does not seem to have an easy proof, and thus is a technical contribution.

Finally, Section 6 shows that $1 - 1/e$ is a tight competitive ratio for non-adaptive algorithms in the random order model, even when the stochastic graph is known (as is the case in Theorem 2.1). We do this by establishing an adaptivity gap between the optimal non-adaptive probing algorithm and the adaptive benchmark we are using.

We conclude with a summary of our contributions and some open problems.

2 Models and Preliminaries

The **online stochastic matching problem** generalizes the classical online bipartite setting as follows. An input to the problem consists of a **bipartite stochastic graph**, which is a (simple) bipartite graph $G = (U, V, E)$ with edge weights $(w_e)_{e \in E}$ and edge probabilities $(p_e)_{e \in E}$. We shall refer to U as the **offline** vertices of G and V as its **online** nodes. For each $e \in E$ of $G = (U, V, E)$, the fraction $0 \leq p_e \leq 1$ gives the probability of existence of the edge e . More precisely, each edge $e \in E$ is associated with an independent Bernoulli random variable of parameter p_e , which we denote by $\text{st}(e)$, corresponding to the **state** of the edge. If $\text{st}(e) = 1$, then we say that e is **active**, and otherwise we say that e is **inactive**.

A solution to the online stochastic matching problem is an **online probing algorithm**. In each round, an online node $v \in V$ arrives, and the online probing algorithm sees all the adjacent edges of v , denoted $\partial(v)$, as well as their associated probabilities, $(p_e)_{e \in \partial(v)}$, and weights, $(w_e)_{e \in \partial(v)}$. However, the edge states $(\text{st}(e))_{e \in \partial(v)}$ initially remain hidden to the algorithm. Instead, given $e \in \partial(v)$, the algorithm must perform a **probing operation** on the edge to reveal/expose its

state, $\text{st}(e)$. As in the classical problem, an online algorithm must decide on a possible match for an online node v before seeing the next online node. The algorithm can be **non-greedy** and not match a given $v \in V$ even though some $u \in U$ is still unmatched. The arrival order of V is either chosen **adversarially**, in which case we work in the **adversarial order model** (AOM), or *u.a.r.* (uniformly at random), in which case we work in the **random order model** (ROM). The online stochastic matching problem simplifies to the classical setting in the appropriate order model provided $p_e = 1$ for all $e \in E$.

Our probing algorithms function in the **probe-commit model**, in which there is a **commitment** requirement upon probing an edge. Specifically, if an edge $e = (u, v)$ is probed in the online stochastic matching problem and turns out to be active, then the probing algorithm must make an irrevocable decision as to whether or not to include e in its matching, prior to probing any subsequent edges. If \mathcal{M} is the matching output by the online probing algorithm, then its goal is to maximize $\mathbb{E}[w(\mathcal{M})]$, where $w(\mathcal{M}) := \sum_{e \in \mathcal{M}} w_e$. Note that this definition of commitment is the one considered by Gupta et al. [36]⁵, and while seemingly less strict than the commitment requirement of the Chen et al. [20] matching model, these definitions have equivalent power, as an algorithm may simply pass on probing an edge if it doesn't intend to add the edge to its matching. We describe our positive results in the Gupta et al. [36] model, as it simplifies both the presentation of our probing algorithms as well as the definition of non-adaptivity. All our results can be restated without loss while satisfying the Chen et al. commitment requirement, albeit with a very small change to the definition of non-adaptive.

In past works, each online node v of G is additionally associated with a known **patience parameter** (also called timeout parameter) ℓ_v which bounds the number of probes that can be made to $\partial(v)$. In this work, we provide a generalization of the patience framework. Specifically, for each $v \in V$, suppose that $\partial(v)^{(*)}$ corresponds to the collection of strings (tuples) formed from *distinct* edges of $\partial(v)$. Upon the arrival of v , an **online probing constraint** $\mathcal{C}_v \subseteq \partial(v)^{(*)}$ is presented to the algorithm, which specifies which sequences of edges of $\partial(v)$ can be probed. We make the minimal assumption that \mathcal{C}_v is **substring-closed**; that is, if $e \in \mathcal{C}_v$, then so is any substring of e (thus, the empty string λ is in \mathcal{C}_v by convention). Observe that \mathcal{C}_v is a general enough definition to encode any collection downward-closed constraints one may wish to place on the feasible edge probes incident to v . In particular, it includes the case when v has a patience value ℓ_v , and more generally, when \mathcal{C}_v corresponds to a matroid or budget constraint on $\partial(v)$. That being said, allowing for inputs which impose order on the probes of $\partial(v)$ is clearly desirable, as it allows for precedence relations. For instance, perhaps one wishes to ensure that if distinct edges $e_1, e_2 \in \partial(v)$ are each probed, then e_1 is always probed before e_2 .

The classical online bipartite matching problems (unweighted, vertex weighted, or edge weighted) for adversarial, ROM, and i.i.d. online vertex arrivals all generalize to the online stochastic matching setting. We emphasize that the appropriate online stochastic matching problem generalizes the corresponding classical online problem, even when restricted to the simplest possible probing constraints; for instance, when each $v \in V$ has **unit patience** (i.e., $\ell_v = 1$ for all $v \in V$).

Clearly, in the classical adversarial or ROM settings, if the algorithm knew the input graph G , the online algorithm could compute an optimal solution before seeing the online sequence and use that optimal solution to determine an optimal matching online. But similar to knowing the

⁵Gupta et al. [36] refer to probing algorithms which are required to make irrevocable decisions in this way as “executing online”. We reserve the term “online” to refer to the requirement that the probing algorithm must process the vertices of V one by one, and has no control on their arrival order.

type graph in the classical setting with i.i.d. inputs, an algorithm still lacks the ability to know the states of the edges of G , namely $(\text{st}(e))_{e \in E}$, so the stochastic matching problem is interesting, whether the stochastic graph G is known or unknown to the algorithm. We are left then with a wide selection of problems, depending on whether or not the stochastic graph is known, how input sequences are determined, and whether or not edges or vertices are weighted. To illustrate our techniques, we first focus on the setting of a known stochastic graph with ROM inputs. We then generalize to the known i.d. setting and consider the cases of both adversarial as well as ROM arrivals.

For stochastic probing problems, it is easy to see we cannot hope to obtain a non-trivial competitive bound against the expected value of an optimum matching of the stochastic graph⁶. The standard approach in the literature is to instead benchmark against an *optimum offline probing algorithm*.

A solution to the **offline stochastic matching problem** on the stochastic graph G is an **offline probing algorithm** \mathcal{A} , which is given access to the stochastic graph $G = (U, V, E)$ (and thus $(p_e)_{e \in E}$, $(w_e)_{e \in E}$, and $(\mathcal{C}_v)_{v \in V}$), yet does *not* initially have access to the edges states $(\text{st}(e))_{e \in E}$. Observe then that $(\mathcal{C}_v)_{v \in V}$ induces an **offline probing constraint** $\mathcal{C} \subseteq E^{(*)}$ in the natural way. For a tuple $e \in E^{(*)}$, let e^v be the substring of e formed by restricting the coordinates of e to those edges which contain v . We define \mathcal{C} from $(\mathcal{C}_v)_{v \in V}$, where e is included in \mathcal{C} if and only if $e^v \in \mathcal{C}_v$ for each $v \in V$. In each step $t \geq 1$, \mathcal{A} may perform a probing operation to reveal the state of an edge $e_t = (u_t, v_t) \in E$, subject to the constraint that if (e_1, \dots, e_{t-1}) were the previously probed edges, then $(e_1, \dots, e_{t-1}, e_t) \in \mathcal{C}$. The probing algorithm \mathcal{A} may be **adaptive**; that is, in addition to all the information regarding G , the decision on whether to probe e_t may depend on all the previously probed edges e_1, \dots, e_{t-1} , and their revealed states, $\text{st}(e_1), \dots, \text{st}(e_{t-1})$. It must also respect commitment, in that upon probing $\text{st}(e_t)$ and revealing $\text{st}(e_t) = 1$, it must irrevocably decide whether to include e_t in its matching. Note that an online probing algorithm with access to G is a special case of an offline probing algorithm.

We say that an offline probing algorithm is **non-adaptive**, provided the probes of E are a (randomized) function of G . Equivalently, an offline probing algorithm is non-adaptive if its probes are statistically independent from the edge states of G . Note that a non-adaptive probing algorithm necessarily must still use the previously revealed edge probes to determine which edges to add to its matching. However, it may possibly waste edge probes.

We define the **adaptive benchmark** on the input G as an offline probing algorithm which returns a matching whose expected weight is as large as possible, and denote this value by $\text{OPT}(G)$. More precisely, if $\mathcal{A}(G)$ is the matching returned by an offline probing algorithm \mathcal{A} , then $\text{OPT}(G) := \sup_{\mathcal{A}} \mathbb{E}[w(\mathcal{A}(G))]$, where the supremum is over all offline probing algorithms.

Our first result is a non-adaptive online probing algorithm which attains a competitive ratio against the adaptive benchmark, provided it is given full access to $G = (U, V, E)$, and the vertices of V arrive *u.a.r.*

Theorem 2.1. *Suppose $G = (U, V, E)$ is an arbitrary stochastic graph and Algorithm 4 returns the matching \mathcal{M} when given full access to G . In this case, if the vertices of V arrive *u.a.r.*, then $\mathbb{E}[w(\mathcal{M})] \geq (1 - \frac{1}{e}) \text{OPT}(G)$. Moreover, Algorithm 4 is non-adaptive.*

⁶Consider a single online vertex with patience 1, and n offline (unweighted) vertices where each edge e has probability $\frac{1}{n}$ of being present. The expectation of an online probing algorithm will be at most $\frac{1}{n}$ while the expected size of an optimal matching (over all instantiations of the edge probabilities) will be $1 - (1 - \frac{1}{n})^n \rightarrow 1 - \frac{1}{e}$. This example also clearly shows that no constant ratio is possible if the patience is sub-linear (in $n = |U|$).

The competitive ratio of Algorithm 4 is optimum amongst all *non-adaptive* online probing algorithms in the known stochastic graph setting with ROM arrivals. In fact, in Section 6 we prove a hardness result which applies to *all* non-adaptive probing algorithms (even probing algorithms which execute offline, and thus do not respect the arrival order of V):

Theorem 2.2. *No non-adaptive offline probing algorithm can attain an approximation ratio against the adaptive benchmark which is greater than $1 - 1/e$.*

Not only does Algorithm 4 attain a competitive ratio against the adaptive benchmark, it can also be implemented efficiently under some mild assumptions. Given the stochastic graph $G = (U, V, E)$, observe that the size of \mathcal{C}_v for $v \in V$ may be exponentially large in the size of U . On the other hand, if we denote $|G|$ as the amount of space needed to represent the information associated with G after excluding the constraints $(\mathcal{C}_v)_{v \in V}$, then we wish to find online probing algorithms which execute in time $\text{poly}(|G|)$. Since the probing algorithm must interact with $(\mathcal{C}_v)_{v \in V}$, we either need to work with constraint systems which have representations of size $\text{poly}(|G|)$ (such as patience constraints), or we need to work in an **oracle model**. We take the latter approach, as it allows us to prove more general results.

We consider two oracle models. In the first model, which we refer to as the **membership model**, a probing algorithm may make a **membership query** to any string $e \in \partial(v)^{(*)}$ for $v \in V$. More precisely, in a single operation the probing algorithm may determine whether or not $e \in \partial(v)^{(*)}$ is included in \mathcal{C}_v .

The second model, which we refer to as the **demand oracle model**, allows the probing algorithm far more power. In particular, for any $v \in V$ and any selection of real values, $(\alpha_u)_{u \in N(v)}$, the algorithm may determine in a single operation a solution to the following maximization problem:

$$\text{maximize } \sum_{i=1}^{|e|} (w_{e_i} - \alpha_{u_i}) \cdot p_{e_i} \cdot \prod_{j=1}^{i-1} (1 - p_{e_j}) \quad (2.1)$$

$$\text{subject to } e \in \mathcal{C}_v \quad (2.2)$$

Observe that this definition is closely related to the demand oracle model in the context of the iterative auctions, as originally studied by Blumrosen and Nisan [11, 12]. More precisely, ignoring the edge probabilities $(p_e)_{e \in \partial(v)}$ for now (i.e. $p_e = 1$ for all e), let us suppose a seller is trying to allocate the items of U to a number of buyers. We view the vertex v as a *buyer* who wishes to purchase a subset of items $S \subseteq N(v)$, based on their valuation function $f(S)$. Assume that v has **unit demand**, that is $f(S) := \max_{s \in S} w_{s,v}$. The values $(\alpha_s)_{s \in N(v)}$ are viewed as prices the buyer must pay⁷, and the demand oracle returns a solution to $\max_{S \subseteq N(v)} (f(S) - \sum_{s \in S} \alpha_s)$, thereby maximizing the utility of v . Clearly, for the simple case of a unit-demand buyer, an optimum assignment is the item $u \in N(v)$ for which $w_{u,v} - \alpha_u$ is maximized, and so the notion of a demand oracle is unnecessary. However, often v is *not* a unit-demand buyer, and so f is a much more general valuation function. In this case, a solution to $\max_{S \subseteq N(v)} (f(S) - \sum_{s \in S} \alpha_{s,v})$ may be computationally difficult to find, so the demand oracle assumption is convenient to make.

Even the case of a unit-demand buyer is a non-trivial optimization problem in the stochastic probing framework. Observe that we may view the edge probabilities $(p_e)_{e \in E}$ as modeling the setting when there is uncertainty in whether or not the purchase proposals will succeed; that is,

⁷See Eden et al. [26] for a buyer/seller interpretation of the classical RANKING algorithm [42] for bipartite matching.

$\text{st}(u, v) = 1$, provided the seller agrees to sell item u to buyer v . In this interpretation, (2.1) is the expected utility of the unit-demand buyer v which commits to the first item $u \in N(v)$ such that $\text{st}(u, v) = 1$, at which point v gains utility $w_{u,v} - \alpha_u$. The relevancy of a demand oracle depends on whether or not it is reasonable to assume that each buyer's optimum greedy probing strategy is readily available. In Section 3, we introduce a new LP to design probing algorithms whose efficient solvability is closely tied to the existence of a demand oracle. More precisely, the demand oracle yields a separation oracle for the dual of LP-new, thus allowing the ellipsoid algorithm [53, 33] to run in polynomial time [59, 57, 2, 46].

We say that \mathcal{C}_v is **closed under permutations**, provided if $e \in \mathcal{C}_v$, then any permutation of e is also in \mathcal{C}_v . Observe then that since \mathcal{C}_v is substring-closed by assumption, this condition is equivalent to requiring that \mathcal{C}_v corresponds to a downward-closed family of subsets of $\partial(v)$. We observe then the following reduction:

Proposition 2.3. *If \mathcal{C}_v is both substring-closed and permutation-closed, then for any selection of values $(\alpha_u)_{u \in N(v)}$, (2.1) can be solved efficiently, assuming access to a membership query oracle for \mathcal{C}_v .*

The proof of Proposition 2.3 builds upon the work of Brubach et al. [15] as well as Purohit et al. [52]:

Proof of Proposition 2.3. Compute $\tilde{w}_e := w_e - \alpha_u$ for each $e = (u, v) \in \partial(v)$, and define $P := \{e \in \partial(v) : \tilde{w}_e \geq 0\}$. First observe that if $P = \emptyset$, then (2.1) is maximized by the empty-string λ .

Thus, for now on assume that $P \neq \emptyset$. Since \mathcal{C}_v is closed under substrings, it suffices to consider those $e \in \mathcal{C}_v$ whose edges all lie in P . As such, for notational convenience, let us hereby assume that $\partial(v) = P$.

Now, for any $e \in \mathcal{C}_v$, let e^r be the rearrangement of e , based on the non-increasing order of the weights $(\tilde{w}_e)_{e \in e}$. Since \mathcal{C}_v is closed under permutations, we know that e^r is also in \mathcal{C}_v . Moreover, the evaluation of e^r in (2.1) is at least as large as that of e . Hence, let us order the edges of $\partial(v)$ as e_1, \dots, e_k , such that $\tilde{w}_{e_1} \geq \dots \geq \tilde{w}_{e_k}$, where $k := |\partial(v)|$. Observe then that it suffices to maximize (2.1) over those strings within \mathcal{C}_v which respect the ordering on $\partial(v)$. Stated differently, let us denote \mathcal{I}_v as the family of subsets of $\partial(v)$ induced by \mathcal{C}_v , and define the set function $f : 2^{\partial(v)} \rightarrow [0, \infty)$, where $f(S) := \sum_{i=1}^{|S|} \tilde{w}_{s_i} \cdot p_{s_i} \cdot \prod_{j=1}^{i-1} (1 - p_{s_j})$ for $S = \{s_1, \dots, s_{|S|}\} \subseteq \partial(v)$ (where $\tilde{w}_{s_1} \geq \dots \geq \tilde{w}_{s_{|S|}}$). Our goal is then to efficiently maximize f over the set-system $(\partial(v), \mathcal{I}_v)$. Observe that since \mathcal{C}_v is both substring-closed and permutation-closed, \mathcal{I}_v is downward-closed. Moreover, clearly we can simulate oracle access to \mathcal{I}_v , based on our oracle access to \mathcal{C}_v .

For each $i = 0, \dots, k-1$, denote $\partial(v)^{>i} := \{e_{i+1}, \dots, e_k\}$, and $\partial(v)^{>k} := \emptyset$. Moreover, define the family of subsets $\mathcal{I}_v^{>i} := \{S \subseteq \partial(v)^{>i} : S \cup \{e_i\} \in \mathcal{I}_v\}$ for each $2 \leq i \leq k$, and $\mathcal{I}_v^{>0} := \mathcal{I}_v$. Observe then that $(\partial(v)^{>i}, \mathcal{I}_v^{>i})$ is a downward-closed set system, as \mathcal{I}_v is downward-closed. Moreover, we may simulate oracle access to $\mathcal{I}_v^{>i}$ based on our oracle access to \mathcal{I}_v .

Denote $\text{OPT}(\mathcal{I}_v^{>i})$ as the maximum value of f over constraints $\mathcal{I}_v^{>i}$. Observe then the following recursion:

$$\text{OPT}(\mathcal{I}_v) := \max_{i \in [k]} (p_{e_i} \cdot \tilde{w}_{e_i} + (1 - p_{e_i}) \cdot \text{OPT}(\mathcal{I}_v^{>i})) \quad (2.3)$$

Hence, given access to the values $\text{OPT}(\mathcal{I}_v^{>1}), \dots, \text{OPT}(\mathcal{I}_v^{>k})$, we can compute $\text{OPT}(\mathcal{I}_v)$ efficiently. In fact, it is clear that we can use (2.3) to recover an optimum solution to f , and so the proof follows by an inductive argument on $|\partial(v)|$. □

As we shall see in Sections 3 and 4, solving (2.1) is the key subroutine needed to execute our online probing algorithms efficiently. In particular, we have the following statement in regards to the efficiency of Algorithm 4:

Theorem 2.4. *Suppose that $G = (U, V, E)$ is a stochastic graph with (substring-closed) probing constraints $(\mathcal{C}_v)_{v \in V}$.*

- *In the demand oracle model, Algorithm 4 executes in time $\text{poly}(|G|)$.*
- *In the membership oracle model, Algorithm 4 executes in time $\text{poly}(|G|)$, provided for each $v \in V$, \mathcal{C}_v is also permutation-closed.*

2.1 Known I.D. Arrivals

We now introduce the technical definitions necessary to precisely describe the **online stochastic matching problem with known i.d. arrivals**. We first describe the randomized procedure for generating the input the online probing algorithm operates on. Afterwards, we indicate which information the online algorithm has access to, and the precise benchmark it is compared against.

Let us suppose that $H_{\text{typ}} = (U, B, F)$ where $F \subseteq U \times B$ is an arbitrary stochastic graph with edge weights $(w_f)_{f \in F}$, edge probabilities $(p_f)_{f \in F}$, and online probing constraints $(\mathcal{C}_b)_{b \in B}$. In the known i.d. setting, we refer to H_{typ} as the **stochastic type graph** (or **type graph** when clear), and the vertices of B as the online **type nodes** of H_{typ} . The online probing algorithm does *not* execute on H_{typ} . Instead, the online algorithm operates on an (unknown) stochastic graph $G = (U, V, E)$. Here, each arriving online vertex $v \in V$, together with $(p_e)_{e \in \partial(v)}$, $(w_e)_{e \in \partial(v)}$, and \mathcal{C}_v , is chosen by selecting v from B . In this work, we are interested in the case when these selections are done randomly according to known distributions on B .

More precisely, the adversary fixes parameter $n \geq 1$, indicating the size of V , and thus the number of **rounds** or **arrivals** to occur. The adversary also fixes a sequence of distributions denoted $(\mathcal{D}_i)_{i=1}^n$, which are each supported on B . Using H_{typ} , and $(\mathcal{D}_i)_{i=1}^n$, we construct the **instantiated stochastic graph** $G = (U, V, E)$ by executing the following randomized procedure. Note that technically V and E are each multi-sets, as a type node $b \in B$ may appear multiple times.

- For $i = 1, \dots, n$: draw $v_i \in B$ independently using \mathcal{D}_i , and add a copy of v_i to G , with the relevant edge probabilities, edge weights and online probing constraint.

Remark 2.5. We say that v_i has **type** $b \in B$, provided $v_i = b$. Note that once G is constructed, the edge states $(\text{st}(e))_{e \in E}$ are drawn independently of each other, where in particular, $(\text{st}(e))_{e \in \partial(v_i)}$ and $(\text{st}(e))_{e \in \partial(v_j)}$ are independent, provided $i \neq j$ (even if v_i and v_j have the same type).

We denote that the instantiated stochastic graph $G = (U, V, E)$ is drawn from $(H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n)$ in this way, by writing $G \sim (H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n)$.

An online probing algorithm is given access to H_{typ} and the distributions $(\mathcal{D}_i)_{i=1}^n$, yet initially does *not* have access to G . Instead, a permutation $\pi : [n] \rightarrow [n]$ is chosen upon, and for each $t = 1, \dots, n$, vertex $v_{\pi(t)}$, along with its edge weights, probabilities, and probing constraint are presented to the algorithm. Using all past available information regarding the outcomes of the probes involving $v_{\pi(1)}, \dots, v_{\pi(t-1)}$, together with the edge probabilities and weights adjacent to $v_{\pi(t)}$, the algorithm may probe the edges of $\partial(v_{\pi(t)})$, subject to the probing constraint $\mathcal{C}_{v_{\pi(t)}}$. Once again, the algorithm must operate in the probe-commit model.

The permutation π is either generated *u.a.r.*, independently of all other randomization, or by an adversary. In either case, π is unknown to the online probing algorithm. We emphasize that we work with an **oblivious adversary**, in that π must be depend solely upon the input $(H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n)$. In particular, it cannot depend on the generation of G , nor the decisions of the online probing algorithm. This is the more standard assumption in prophet problems⁸ as recently discussed by Ezra et al. [29].

Suppose that $\mathcal{A}(H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n, \pi)$ is the matching constructed by an online probing algorithm \mathcal{A} when presented the online vertices of $G \sim (H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n)$ in order π . The goal of the online probing algorithm is to maximize the expected weight of $\mathcal{A}(H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n, \pi)$. Specifically, it aims to maximize

$$\mathbb{E}[w(\mathcal{A}(H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n, \pi))],$$

where the expectation is over the construction of G , the edge states $(\text{st}(e))_{e \in E}$, as well as any randomized decisions made by the algorithm. We benchmark against the expected performance of adaptive benchmark on $G \sim (H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n)$, which we denote by $\text{OPT}(H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n)$. More precisely,

$$\text{OPT}(H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n) := \mathbb{E}[\text{OPT}(G)],$$

where the expectation is solely over the randomness in generating G .

The standard in the literature (see [3, 9, 17]) is to prove competitive ratios against $\text{OPT}(H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n)$. That is, in the adversarial order model, the goal is to find an online probing algorithm \mathcal{A} for which the (strict) competitive ratio

$$\inf_{(H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n, \pi)} \frac{\mathbb{E}[w(\mathcal{A}(H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n, \pi))]}{\text{OPT}(H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n)}$$

is as close to 1 as possible. An analogous definition holds in the random order model. We say that an online probing algorithm is **non-adaptive**, provided for each $t \in [n]$, the probes of $\partial(v_{\pi(t)})$ are a (randomized) function of H_{typ} , and the type of arrival $v_{\pi(t)}$. In particular, when probing edges adjacent to the online node $v_{\pi(t)}$, the algorithm does not make use of the previously probed edge states of the online nodes $v_{\pi(1)}, \dots, v_{\pi(t-1)}$ (nor the matching decisions made thus far). The algorithm will therefore possibly waste some probes to edges $(u, v_{\pi(t)})$ but will not violate the matching constraint. Note that this definition is consistent with the definition considered in the known stochastic graph case. It also generalizes the classical definition of Manshadi et al. [49]. We now present our main results:

Theorem 2.6. *Suppose $(H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n)$ is a known i.d. input, which Algorithm 6 is given full access to. If \mathcal{M} is the matching returned by the algorithm when presented the online vertices of $G \sim (H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n)$ in random order, then $\mathbb{E}[w(\mathcal{M})] \geq (1 - \frac{1}{e}) \text{OPT}(H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n)$. Moreover, Algorithm 6 is non-adaptive.*

Theorem 2.7. *Suppose $(H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n)$ is a known i.d. input, which Algorithm 8 is given full access to. If $\mathcal{M}(\pi)$ is the matching returned by the algorithm when presented the online vertices of $G \sim (H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n)$ in an adversarial order $\pi : [n] \rightarrow [n]$, then $\mathbb{E}[w(\mathcal{M}(\pi))] \geq \frac{1}{2} \text{OPT}(H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n)$.*

⁸Other works, for instance Feldman et al. [31], consider an **almighty adversary** which has access to the instantiations of all the random variables when generating π . This definition is far too strong for stochastic probing problems, as it allows the benchmark to forgo making edge probes.

Remark 2.8. This is a tight bound since the problem generalizes the classical single item prophet inequality for which $\frac{1}{2}$ is an optimal competitive ratio.

Theorem 2.9. Suppose that $(H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n)$ is a known i.d. input, where $H_{\text{typ}} = (U, B, F)$ has (substring-closed) probing constraints $(\mathcal{C}_b)_{b \in B}$. If $|H_{\text{typ}}|$ is the size of H_{typ} (excluding $(\mathcal{C}_b)_{b \in B}$), and $|\mathcal{D}_i|$ is the amount of space needed to encode the distribution \mathcal{D}_i , then the following claims holds:

- In the demand oracle model, Algorithms 6 and 8 execute in time $\text{poly}(|H_{\text{typ}}|, (|\mathcal{D}_i|)_{i=1}^n)$.
- In the membership oracle model, Algorithms 6 and 8 execute in time $\text{poly}(|H_{\text{typ}}|, (|\mathcal{D}_i|)_{i=1}^n)$, provided for each $b \in B$, \mathcal{C}_b is also permutation-closed.

Remark 2.10. $|H_{\text{typ}}|$ may be exponentially large in the size of $G \sim (H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n)$, however for each $\varepsilon > 0$, our results can be made to run in time $\text{poly}(|G|, \log(1/\varepsilon))$ using Monte Carlo simulation (at a loss of $(1 - \varepsilon)$ in performance), assuming we have oracle access to samples drawn from $(\mathcal{D}_i)_{i=1}^n$.

3 Online Probing with a Known Stochastic Graph

In order to prove our positive results, we require a means to devise online probing algorithms which do reasonably well compared to the adaptive benchmark, and yet are efficient. In this section, we develop the tools needed to devise such algorithms. We focus on the known stochastic graph setting of Theorem 2.1. In the following section, we generalize our techniques to handle the more general problem of known i.d. arrivals.

Our goal is to find an online probing algorithm \mathcal{A} , such that for each stochastic graph $G = (U, V, E)$, we have that $\mathbb{E}[w(\mathcal{A}(G))] \geq (1 - 1/e)\text{OPT}(G)$, provided the vertices of V arrive in random order. Towards this goal, we introduce some notation which allows us to derive a new configuration LP. For each $\mathbf{e} = (e_1, \dots, e_{|\mathbf{e}|}) \in E^{(*)}$, define $g(\mathbf{e}) := \prod_{i=1}^{|\mathbf{e}|} (1 - p_{e_i})$. Notice that $g(\mathbf{e})$ corresponds to the probability that all the edges of \mathbf{e} are inactive, where $g(\lambda) := 1$ for the empty string λ . We also define $\mathbf{e}_{<e_i} := (e_1, \dots, e_{i-1})$ for each $2 \leq i \leq |\mathbf{e}|$, which we denote by $\mathbf{e}_{<i}$ when clear. By convention, $\mathbf{e}_{<1} := \lambda$. Observe then that $\text{val}(\mathbf{e}) := \sum_{i=1}^{|\mathbf{e}|} p_{e_i} w_{e_i} \cdot g(\mathbf{e}_{<i})$ corresponds to the expected weight of the first active edge revealed if \mathbf{e} is probed in order of indices.

For each $v \in V$, we introduce a decision variable denoted $x_v(\mathbf{e})$. With this notation, we can express the following LP:

$$\text{maximize} \quad \sum_{v \in V} \sum_{\mathbf{e} \in \mathcal{C}_v} \text{val}(\mathbf{e}) \cdot x_v(\mathbf{e}) \quad (\text{LP-new})$$

$$\text{subject to} \quad \sum_{v \in V} \sum_{\substack{\mathbf{e} \in \mathcal{C}_v: \\ (u,v) \in \mathbf{e}}} p_{u,v} \cdot g(\mathbf{e}_{<(u,v)}) \cdot x_v(\mathbf{e}) \leq 1 \quad \forall u \in U \quad (3.1)$$

$$\sum_{\mathbf{e} \in \mathcal{C}_v} x_v(\mathbf{e}) = 1 \quad \forall v \in V, \quad (3.2)$$

$$x_v(\mathbf{e}) \geq 0 \quad \forall v \in V, \mathbf{e} \in \mathcal{C}_v \quad (3.3)$$

Crucially, LP-new is a **relaxation** of the adaptive benchmark. Moreover, it can be solved efficiently under the assumptions of Theorem 2.1, however we defer the discussion on how this can be done to the end of the section (Theorem 3.10).

Theorem 3.1. *For any stochastic graph $G = (U, V, E)$ with substring-closed probing constraints, $\text{OPT}(G) \leq \text{LPOPT}(G)$.*

In order to prove Theorem 3.1, the natural approach is to define $x_v(\mathbf{e})$ to be the probability that the adaptive benchmark probes the edges of \mathbf{e} in order, where $v \in V$ and $\mathbf{e} \in \mathcal{C}_v$. Let us suppose that hypothetically we could make the following assumption regarding the adaptive benchmark:

- (P₁) If $e = (u, v)$ is probed and $\text{st}(e) = 1$, then e is included in the matching, provided v is currently unmatched.
- (P₂) For each $v \in V$, the edge probes involving $\partial(v)$ are made independently of the edge states $(\text{st}(e))_{e \in \partial(v)}$.

Observe then that (P₁) and (P₂) would imply the expected weight of the edge assigned to v is $\sum_{\mathbf{e} \in \mathcal{C}_v} \text{val}(\mathbf{e}) \cdot x_v(\mathbf{e})$. Moreover, the left-hand side of (3.1) would correspond to the probability $u \in U$ is matched, so $(x_v(\mathbf{e}))_{v \in V, \mathbf{e} \in \mathcal{C}_v}$ corresponds to a feasible solution to LP-new, and so we could upper bound $\text{OPT}(G)$ by $\text{LPOPT}(G)$. Now, if we knew that the adaptive benchmark adhered to some adaptive vertex ordering π on V (i.e., it chooses $v_{\pi(i)}$ based on $v_{\pi(1)}, \dots, v_{\pi(i-1)}$, and probes the edges of $v_{\pi(i)}$ before moving to $v_{\pi(i+1)}$), then it is clear that one could assume (P₁) and (P₂) simultaneously⁹ *w.l.o.g.*. However, clearly a probing algorithm with this restriction is in general less powerful than the adaptive benchmark. As such, the natural interpretation of the variables of LP-new does not seem to easily lend itself to a proof of Theorem 3.1.

In order to get around these issues and prove Theorem 3.1, we do *not* directly compare the adaptive benchmark to $\text{LPOPT}(G)$. Instead, we introduce a **combinatorial relaxation** of the offline stochastic matching problem, which we define to be a new stochastic probing problem on G whose optimum probing algorithm has value no worse than $\text{OPT}(G)$. Specifically, given a stochastic graph $G = (U, V, E)$, we define the **relaxed stochastic matching problem**. A solution to this problem is a **relaxed probing algorithm** \mathcal{A} , which operates in the previously described framework of an (offline) probing algorithm. That is, \mathcal{A} is firstly given access to a stochastic graph $G = (U, V, E)$. Initially, the edge states $(\text{st}(e))_{e \in E}$ are unknown to \mathcal{A} , and \mathcal{A} must adaptively probe these edges to reveal their states, while respecting the substring-closed probing constraints $(\mathcal{C}_v)_{v \in V}$. Once again, \mathcal{A} returns a subset $\mathcal{A}(G)$ of its active probes, and its goal is to maximize $\mathbb{E}[w(\mathcal{A}(G))]$, where $w(\mathcal{A}(G)) := \sum_{e \in \mathcal{A}(G)} w_e$. However, unlike before where the output of the probing algorithm was required to be a matching of G , we relax the required properties of $\mathcal{A}(G)$:

1. Each $v \in V$ appears in at most one edge of $\mathcal{A}(G)$.
2. If N_u counts the number of edges of $\partial(u)$ which are included in $\mathcal{A}(G)$, then $\mathbb{E}[N_u] \leq 1$ for each $u \in U$.

We refer to $\mathcal{A}(G)$ as a **one-sided matching** of the online nodes. In constructing $\mathcal{A}(G)$, \mathcal{A} must operate in the previously described probe-commit model. We define the **relaxed benchmark** as an optimum relaxed probing algorithm, and denote its evaluation on G by $\text{OPT}_{\text{rel}}(G)$. Observe that since any offline probing algorithm is a relaxed probing algorithm, we have that

$$\text{OPT}(G) \leq \text{OPT}_{\text{rel}}(G). \tag{3.4}$$

⁹It is clear that we may assume the adaptive benchmark satisfies (P₁) *w.l.o.g.*, but not (P₂).

We say that \mathcal{A} is **non-adaptive**, provided the probes are a (randomized) function of G . Equivalently, \mathcal{A} is non-adaptive if the probes of \mathcal{A} are statistically independent from $(st(e))_{e \in E}$. Unlike the offline stochastic matching problem, there exists a relaxed probing algorithm which is optimum, and yet non-adaptive:

Lemma 3.2. *For any stochastic graph $G = (U, V, E)$ with (substring-closed) probing constraints $(\mathcal{C}_v)_{v \in V}$, there exists an optimum relaxed probing algorithm \mathcal{B} which satisfies the following properties:*

(Q₁) *If $e = (u, v)$ is probed and $st(e) = 1$, then e is included in $\mathcal{B}(G)$, provided v is currently unmatched.*

(Q₂) *\mathcal{B} is non-adaptive on G .*

We defer the proof of Lemma 3.2 to Section A. Observe that by considering \mathcal{B} of Lemma 3.2, and defining $x_v(\mathbf{e})$ as the probability that \mathcal{B} probes the edges of \mathbf{e} in order for $v \in V$ and $\mathbf{e} \in \mathcal{C}_v$, properties (Q₂) and (Q₁) ensure that $(x_v(\mathbf{e}))_{v \in V, \mathbf{e} \in \mathcal{C}_v}$ is a feasible solution to LP-new, such that

$$\mathbb{E}[w(\mathcal{B}(G))] = \sum_{v \in V} \sum_{\mathbf{e} \in \mathcal{C}_v} \text{val}(\mathbf{e}) \cdot x_v(\mathbf{e}).$$

Thus, the optimality of \mathcal{B} implies that $\text{OPT}_{\text{rel}}(G) \leq \text{LPOPT}(G)$, and so together with (3.4), Theorem 3.1 follows.

In fact, we claim the following equivalence between LP-new and the relaxed stochastic matching problem, whose proof we defer to Appendix A:

Theorem 3.3. *For any stochastic graph G with substring-closed probing constraints, $\text{OPT}_{\text{rel}}(G) = \text{LPOPT}(G)$.*

We shall now show how to use LP-new to design online probing algorithms which have access to the stochastic graph $G = (U, V, E)$. Suppose that we are presented a feasible solution, say $(x_v(\mathbf{e}))_{v \in V, \mathbf{e} \in \mathcal{C}_v}$, to LP-new for G . For each $e \in E$, define

$$\tilde{x}_e := \sum_{\substack{\mathbf{e}' \in \mathcal{C}_v: \\ e \in \mathbf{e}'}} g(\mathbf{e}'_{<e}) \cdot p_e \cdot x_v(\mathbf{e}'). \quad (3.5)$$

In order to simplify our notation in the later sections, we refer to the values $(\tilde{x}_e)_{e \in E}$ as the **(induced) edge variables** of the solution $(x_v(\mathbf{e}))_{v \in V, \mathbf{e} \in \mathcal{C}_v}$. Observe that constraint (3.1) ensures that $\sum_{e \in \partial(u)} \tilde{x}_e \leq 1$ for each $u \in U$.

If we now fix $s \in V$, then we can easily leverage constraint (3.2) to argue that each edge of $\partial(s)$ can be matched with probability exactly equal to \tilde{x}_s . Specifically, we may execute a *fixed vertex* probing algorithm, which we refer to as VERTEXPROBE. We describe its inputs in general notation, as we also use the algorithm in the known i.d. setting of Section 4.

Algorithm 1 VertexProbe

Input: an online vertex s of a stochastic graph, $\partial(s)$, and probabilities $(z(e))_{e \in \mathcal{C}_s}$ such that $\sum_{e \in \mathcal{C}_s} z(e) = 1$.

Output: an active edge \mathcal{N} of $\partial(s)$.

```
1: Initialize  $\mathcal{N} \leftarrow \emptyset$ .
2: Draw  $e'$  from  $\mathcal{C}_s$  with probability  $z(e')$ .
3: if  $e' = \lambda$  then                                      $\triangleright$  the empty string is drawn.
4:   return  $\mathcal{N}$ .
5: else
6:   Denote  $e' = (e'_1, \dots, e'_k)$  for  $k := |e'| \geq 1$ .
7:   for  $i = 1, \dots, k$  do                                $\triangleright$  probe the edges of  $e'$  in order and return the first active edge
8:     Probe the edge  $e'_i$ .
9:     if  $\text{st}(e'_i) = 1$ , and  $s$  is not matched by  $\mathcal{N}$  then
10:      Add  $e'_i$  to  $\mathcal{N}$ .
11:    end if
12:  end for
13: end if
14: return  $\mathcal{N}$ .
```

Observe the following claim, which follows immediately from the definition of the edge variables, $(\tilde{x}_e)_{e \in E}$:

Lemma 3.4. *Let $G = (U, V, E)$ be a stochastic graph with LP-new solution $(x_v(e))_{v \in V, \partial(v)}$, and whose induced edge variables we denote $(\tilde{x}_e)_{e \in E}$. If the VERTEXPROBE algorithm is passed a fixed node $s \in V$, then each $e \in \partial(s)$ is returned by the algorithm with probability \tilde{x}_e .*

Remark 3.5. We say that VERTEXPROBE **commits** to the edge e , provided the algorithm outputs this edge when executing on the fixed node $s \in V$.

To clearly illustrate how we use LP-new in conjunction with VERTEXPROBE to design probing algorithms, we first consider a simpler algorithm which attains a competitive ratio of $1/2$, provided the vertices of $G = (U, V, E)$ arrive in random order. Afterwards, we modify this algorithm via a non-greedy contention resolution scheme considered by Lee and Singla [46], allowing us to improve the competitive ratio to $1 - 1/e$, thus proving Theorem 2.1

Algorithm 2 Known Stochastic Graph

Input: a stochastic graph $G = (U, V, E)$.

Output: a matching \mathcal{M} of active edges of G .

```
1:  $\mathcal{M} \leftarrow \emptyset$ .
2: Compute an optimum solution of LP-new for  $G$ , say  $(x_v(e))_{v \in V, e \in \mathcal{C}_v}$ .
3: for  $s \in V$  in u.a.r. order do
4:   Set  $e \leftarrow \text{VERTEXPROBE}(s, \partial(s), (x_s(e))_{e \in \mathcal{C}_s})$ .
5:   if  $e = (u, s)$  for some  $u \in U$ , and  $u$  is unmatched then        $\triangleright$  rule out when  $e = \emptyset$ 
6:     Add  $e$  to  $\mathcal{M}$ .
7:   end if
8: end for
9: return  $\mathcal{M}$ .
```

Remark 3.6. Technically, line (6) should occur within the VERTEXPROBE subroutine to adhere to the probe-commit model, however we express our algorithms in this way for brevity.

Proposition 3.7. *If \mathcal{M} is the matching returned by Algorithm 2 when executing on the stochastic graph $G = (U, V, E)$, then $\mathbb{E}[w(\mathcal{M})] \geq \frac{1}{2}OPT(G)$, provided the vertices of V arrive u.a.r.. Moreover, the analysis of Algorithm 2 is tight.*

In order to prove Proposition 3.7, and to later derive the $1 - 1/e$ -competitive ratio of Theorem 2.1, we review contention resolution schemes, restricted to the simplest case of rank 1 matroids. Given $k \geq 1$, consider the ground set $[k] := \{1, \dots, k\}$. Fix $\mathbf{z} \in [0, 1]^k$, and let $R(\mathbf{z}) \subseteq [k]$ denote the random set, where each $i \in [k]$ is included in $R(\mathbf{z})$ independently with probability z_i . Let us denote $\mathcal{P} := \{\mathbf{z} \in [0, 1]^k : \sum_{i=1}^k z_i \leq 1\}$. Note that \mathcal{P} is the convex relaxation of the constraint imposed by the rank 1 matroid on $[k]$ (i.e., at most one element of $[k]$ may be selected).

Definition 1 (Contention Resolution Scheme – Rank 1 Matroid). A **contention resolution scheme** (CRS) for the rank 1 matroid on $[k]$ is a (randomized) algorithm ψ , which given $\mathbf{z} \in \mathcal{P}$ and $S \subseteq [k]$ as inputs, returns a single element $\psi_{\mathbf{z}}(S)$ of S . Given $c \in [0, 1]$, ψ is said to be **c -selectable**, provided for all $i \in [k]$ and $\mathbf{z} \in \mathcal{P}$,

$$\mathbb{P}[i \in \psi_{\mathbf{z}}(R(\mathbf{z})) \mid i \in R(\mathbf{z})] \geq c, \tag{3.6}$$

where the probability is over the generation of $R(\mathbf{z})$, and the potential randomness used by ψ .

Remark 3.8. Observe that if $f : 2^{[k]} \rightarrow \mathbb{R}$ is a monotone linear function, then for any $\mathbf{z} \in \mathcal{P}$, executing a c -selectable CRS ψ yields an element $\psi_{\mathbf{z}}(R(\mathbf{z})) \in R(\mathbf{z})$, such that $\mathbb{E}[f(\psi_{\mathbf{z}}(R(\mathbf{z})))] \geq c \cdot \mathbb{E}[f(R(\mathbf{z}))]$. Thus, c -selectable CRS are useful for designing approximation algorithms, in which one works with a convex relaxation of the constraint system on $[k]$ (in our case, a rank 1 matroid). Much more general results hold, and we refer the reader to the seminal paper by Chekuri, Vondrak, and Zenklusen [57].

Feldman et al. [31] considered a more restricted class of contention resolution schemes, called **online contention resolution schemes** (OCRS). These are schemes in which $R(\mathbf{z})$ is *not* known to the scheme ahead of time. Instead, the elements of $[k]$ are presented to the scheme ψ in adversarial order, where in each step, an arriving $i \in [k]$ reveals if it is in $R(\mathbf{z})$, at which point ψ must make an irrevocable decision as to whether it wishes to return i as its output. Lee and Singla [46], as well as Adamczyk and Włodarczyk [4], considered an extension of this definition to the setting where the elements of $[k]$ arrive in random order, thus defining **random order contention resolution schemes** (RCRS). Both order variants continue to allow ψ to depend on \mathbf{z} , and the notion of selectability extends, where in the case of a RCRS, the random order is incorporated into the probabilistic computation of (3.6).

We can view Algorithm 2 as executing a concurrent contention resolution scheme on each of the offline vertices. More precisely, given a fixed $u \in U$, observe that Algorithm 2 commits to each edge $e = (u, v) \in \partial(u)$, independently with probability \tilde{x}_e . Thus, from the perspective of u , Algorithm 2 can be viewed as executing a *greedy* RCRS in which the edges of $\partial(u)$ are considered uniformly at random, and the first one which commits to u is included in \mathcal{M} . This greedy RCRS is $1/2$ -selectable, which thereby proves Proposition 3.7. We improve the competitive ratio of Algorithm 2 by executing a more sophisticated contention resolution scheme, as considered by Lee and Singla [46]. Given the ground set $[k] = \{1, \dots, k\}$, draw $Y_i \sim [0, 1]$ u.a.r and independently for $i = 1, \dots, k$.

Algorithm 3 RCRS – Lee and Singla [46]

Input: $\mathbf{z} \in \mathcal{P}$, where $\mathcal{P} \subseteq [0, 1]^k$.

Output: at most one element of $[k]$.

- 1: **for** $i \in [k]$ in increasing order of Y_i **do**
- 2: **if** $i \in R(\mathbf{z})$ **then**
- 3: **return** i independently with probability $\exp(-Y_i \cdot z_i)$
- 4: **end if**
- 5: **end for**
- 6: **return** \emptyset .

▷ pass on returning an element of $[k]$.

Theorem 3.9 (Lee and Singla [46]). *Algorithm 3 is a $1 - 1/e$ -selectable RCRS for the case of a rank 1 matroid.*

We are now ready to modify Algorithm 2 to attain the desired competitive ratio. For each $v \in V$, draw $\tilde{Y}_v \in [0, 1]$ independently and uniformly at random. We assume the vertices of V are presented to Algorithm 2 in non-decreasing order, based upon the values $(\tilde{Y}_v)_{v \in V}$.

Algorithm 4 Known Stochastic Graph – Modified

Input: a stochastic graph $G = (U, V, E)$.

Output: a matching \mathcal{M} of G of active edges.

- 1: $\mathcal{M} \leftarrow \emptyset$.
 - 2: Compute an optimum solution of LP-new for G , say $(x_v(e))_{v \in V, e \in \mathcal{C}_v}$.
 - 3: **for** $s \in V$ in increasing order of \tilde{Y}_s **do**
 - 4: Set $e \leftarrow \text{VERTEXPROBE}(s, \partial(s), (x_s(e))_{e \in \mathcal{C}_s})$.
 - 5: **if** $e = (u, s)$ for some $u \in U$, and u is unmatched **then**
 - 6: Add e to \mathcal{M} independently with probability $\exp(-\tilde{Y}_s \cdot \tilde{x}_{u,s})$.
 - 7: **end if**
 - 8: **end for**
 - 9: **return** \mathcal{M} .
-

Proof of Theorem 2.1. Given $u \in U$, let $\mathcal{M}(u)$ denote the edge matched to u by \mathcal{M} , where $\mathcal{M}(u) := \emptyset$ if no such edge exists.

Observe now that if $C(e)$ corresponds to the event in which VERTEXPROBE commits to $e \in \partial(u)$, then $\mathbb{P}[C(e)] = \tilde{x}_e$ by Lemma 3.4. Moreover, the events $(C(e))_{e \in \partial(u)}$ are independent, and satisfy

$$\sum_{e \in \partial(u)} \mathbb{P}[C(e)] = \sum_{e \in \partial(u)} \tilde{x}_e \leq 1, \quad (3.7)$$

by constraint (3.1) of LP-new. As such, denote $\mathbf{z} := (z_e)_{e \in \partial(u)}$ where $z_e := \tilde{x}_e$, and observe that (3.7) ensures that $\mathbf{z} \in \mathcal{P}$, where \mathcal{P} is the convex relaxation of the rank 1 matroid on $\partial(u)$. Let us denote $R(\mathbf{z})$ as those $e \in \partial(u)$ for which $C(e)$ occurs.

For each $e = (u, v) \in \partial(u)$, define $Y_{u,v} := \tilde{Y}_v$. Observe then that the random variables $(Y_e)_{e \in \partial(u)}$ are independent and drawn *u.a.r.* from $[0, 1]$. Thus, if ψ is the RCRS defined in Algorithm 3, then we may pass \mathbf{z} to ψ , and process the edges of $\partial(u)$ in non-increasing order based on $(Y_e)_{e \in \partial(u)}$. Denote the resulting output by $\psi_{\mathbf{z}}(R(\mathbf{z}))$. By coupling the random draws of lines (3) and (6) of

Algorithms 3 and 4, respectively, we get that

$$w(\mathcal{M}(u)) = \sum_{e \in \partial(u)} w_e \cdot \mathbf{1}_{[e \in R(\mathbf{z})]} \cdot \mathbf{1}_{[e \in \psi_{\mathbf{z}}(R(\mathbf{z}))]}$$

Thus, after taking expectations,

$$\mathbb{E}[w(\mathcal{M}(u))] = \sum_{e \in \partial(u)} w_e \cdot \mathbb{P}[e \in \psi_{\mathbf{z}}(R(\mathbf{z})) \mid e \in R(\mathbf{z})] \cdot \mathbb{P}[e \in R(\mathbf{z})].$$

Now, Theorem 3.9 ensures that for each $e \in \partial(u)$, $\mathbb{P}[e \in \psi_{\mathbf{z}}(R(\mathbf{z})) \mid e \in R(\mathbf{z})] \geq (1 - \frac{1}{e})$. It follows that $\mathbb{E}[w(\mathcal{M}(u))] \geq (1 - \frac{1}{e}) \sum_{e \in \partial(u)} w_e \tilde{x}_e$, for each $u \in U$. Thus,

$$\begin{aligned} \mathbb{E}[w(\mathcal{M})] &= \sum_{u \in U} \mathbb{E}[w(\mathcal{M}(u))] \\ &\geq \left(1 - \frac{1}{e}\right) \sum_{e \in \partial(u)} w_e \tilde{x}_e = \left(1 - \frac{1}{e}\right) \text{LPOPT}(G), \end{aligned}$$

where the equality follows since $(x_v(\mathbf{e}))_{v \in V, \mathbf{e} \in \mathcal{C}_v}$ is an optimum solution to LP-new. On the other hand, $\text{LPOPT}(G) \geq \text{OPT}(G)$ by Theorem 3.1, and so the proof is complete. \square

We conclude the section by showing how LP-new be solved efficiently under the assumptions of Theorem 2.4. Since the remaining steps of Algorithm 4 can clearly be implemented efficiently, this will prove Theorem 2.4.

Theorem 3.10. *Suppose that $G = (U, V, E)$ in a stochastic graph with (substring-closed) probing constraints $(\mathcal{C}_v)_{v \in V}$.*

- *In the demand oracle model, LP-new is efficiently solvable in $|G|$.*
- *In the membership oracle model, LP-new is efficiently solvable in $|G|$, provided for each $v \in V$, \mathcal{C}_v is also permutation-closed.*

We prove Theorem 3.10 by first considering the dual of LP-new. Note, that in the below LP formulation, if $\mathbf{e} = (e_1, \dots, e_k) \in \mathcal{C}_v$, then we set $e_i = (u_i, v)$ for $i = 1, \dots, k$ for convenience.

$$\text{minimize} \quad \sum_{u \in U} \alpha_u + \sum_{v \in V} \beta_v \quad (\text{LP-new-dual})$$

$$\text{subject to} \quad \beta_v + \sum_{j=1}^{|\mathbf{e}|} p_{e_j} \cdot g(\mathbf{e}_{<j}) \cdot \alpha_{u_j} \geq \sum_{j=1}^{|\mathbf{e}|} p_{e_j} \cdot w_{e_j} \cdot g(\mathbf{e}_{<j}) \quad \forall v \in V, \mathbf{e} \in \mathcal{C}_v \quad (3.8)$$

$$\alpha_u \geq 0 \quad \forall u \in U \quad (3.9)$$

$$\beta_v \in \mathbb{R} \quad \forall v \in V \quad (3.10)$$

Observe that to prove Theorem 3.10, it suffices to show that LP-new-dual has a (deterministic) polynomial time separation oracle, as a consequence of how the ellipsoid algorithm [53, 33] executes (see [59, 57, 2, 46] for more detail).

Suppose that we are presented a particular selection of dual variables, say $(\alpha_u)_{u \in U}$ and $(\beta_v)_{v \in V}$, which may or may not be a feasible solution to LP-new-dual. Our separation oracle must determine efficiently whether these variables satisfy all the constraints of LP-new-dual. In the case in which the solution is *infeasible*, the oracle must additionally return a constraint which is violated.

It is clear that we can accomplish this for the non-negativity constraints, so let us fix a particular $v \in V$ in what follows. We wish to determine whether there exists some $\mathbf{e} = (e_1, \dots, e_{|\mathbf{e}|}) \in \mathcal{C}_v$, such that if $e_i = (u_i, v)$ for $i = 1, \dots, k$, then

$$f(\mathbf{e}) := \sum_{j=1}^{|\mathbf{e}|} (w_{e_j} - \alpha_{u_j}) \cdot p_{e_j} \cdot g(\mathbf{e}_{<j}) > \beta_v, \quad (3.11)$$

where $f(\mathbf{e}) := 0$ if $\mathbf{e} = \lambda$. In order to make this determination, it clearly suffices to maximize the function f efficiently. The complexity of this problem depends on whether we are working in demand oracle model or the membership oracle model.

Lemma 3.11. *In the demand oracle model, there exists an efficient deterministic algorithm for checking whether $f(\mathbf{e}') > \beta_v$ for some $\mathbf{e}' \in \mathcal{C}_v$, provided \mathcal{C}_v is substring-closed. Moreover, if such a tuple exists, then it can be found efficiently. The same result holds in the membership oracle model, provided \mathcal{C}_v is also permutation-closed.*

Proof. We first consider the case of the demand oracle model. In this setting, we can pass the values $(\alpha_u)_{u \in N(v)}$ to the oracle, and it will return a string $\mathbf{e}' \in \mathcal{C}_v$ for which

$$f(\mathbf{e}') = \sum_{j=1}^{|\mathbf{e}'|} (w_{e'_j} - \alpha_{u_j}) \cdot p_{e'_j} \cdot g(\mathbf{e}'_{<j}) \quad (3.12)$$

is maximized over \mathcal{C}_v . Thus, if $f(\mathbf{e}') > \beta_v$, then we have found a string $\mathbf{e} \in \mathcal{C}_v$ which satisfies $f(\mathbf{e}) > \beta_v$. On the other hand, if $f(\mathbf{e}') \leq \beta_v$, then no such string \mathbf{e} exists, as

$$f(\mathbf{e}) \leq f(\mathbf{e}') \leq \beta_v$$

for all $\mathbf{e} \in \mathcal{C}_v$.

Let us now consider the membership oracle model when \mathcal{C}_v is also permutation-closed. Observe that by Proposition 2.3, the demand oracle model can be simulated by the membership oracle model, and so an optimum solution to (3.12) can be found efficiently. The remainder of the proof thus follows as above. \square

Lemma 3.11 guarantees the existence of efficient separation oracles for LP-new-dual in the appropriate query oracle models, and so the cases of Theorem 3.10 follow immediately.

4 Online Probing with Known I.D. Arrivals

Suppose that $(H_{\text{typ}}, (\mathcal{D}_t)_{t=1}^n)$ is a known *i.d.* input, where $H_{\text{typ}} = (U, B, F)$ has online probing constraints $(\mathcal{C}_b)_{b \in B}$. For each $t \in [n]$, denote $r_t(b)$ as the probability that a vertex drawn from \mathcal{D}_t is equal to $b \in B$. Recall the definition of the instantiated graph $G \sim (H_{\text{typ}}, (\mathcal{D}_t)_{t=1}^n)$, where $G = (U, V, E)$ has vertices $V = \{v_1, \dots, v_n\}$, and $\mathbb{P}[v_t = b] = r_t(b)$ for each $t \in [n]$ and $b \in B$.

As in LP-new, let $g(\mathbf{e}) := \prod_{i=1}^{|\mathbf{e}|} (1 - p_{e_i})$ for $\mathbf{e} \in F^{(*)}$ (where $g(\lambda) := 1$). Similarly, let $\text{val}(\mathbf{e})$ correspond to the expected weight of the first active edge amongst \mathbf{e} (where $\text{val}(\mathbf{e}) := 0$). We can now generalize LP-new to account for the distributions $(\mathcal{D}_t)_{t=1}^n$. For each $t \in [n]$, $b \in B$ and $\mathbf{e} \in \mathcal{C}_b$, we introduce a decision variable $x_t(\mathbf{e} \parallel b)$ to encode the probability that v_t has type b and \mathbf{e} corresponds to the edges of $\partial(v_t)$ which are probed in order by the *relaxed* benchmark.

$$\text{maximize} \quad \sum_{t \in [n], b \in B} \sum_{\mathbf{e} \in \mathcal{C}_b} \text{val}(\mathbf{e}) \cdot x_t(\mathbf{e} \parallel b) \quad (\text{LP-new-id})$$

$$\text{subject to} \quad \sum_{t \in [n], b \in B} \sum_{\substack{\mathbf{e} \in \mathcal{C}_b: \\ (u,b) \in \mathbf{e}}} p_{u,b} \cdot g(\mathbf{e}_{<(u,b)}) \cdot x_t(\mathbf{e} \parallel b) \leq 1 \quad \forall u \in U \quad (4.1)$$

$$\sum_{\mathbf{e} \in \mathcal{C}_b} x_t(\mathbf{e} \parallel b) = r_t(b) \quad \forall b \in B, t \in [n] \quad (4.2)$$

$$x_t(\mathbf{e} \parallel b) \geq 0 \quad \forall b \in B, \mathbf{e} \in \mathcal{C}_b, t \in [n] \quad (4.3)$$

Let us denote $\text{LPOPT}(H_{\text{typ}}, (\mathcal{D}_t)_{t=1}^n)$ as the value of an optimum solution to LP-new-id. We claim that $\text{LPOPT}(H_{\text{typ}}, (\mathcal{D}_t)_{t=1}^n)$ upper bounds $\text{OPT}(H_{\text{typ}}, (\mathcal{D}_t)_{t=1}^n)$. One way to see this is to use Lemma 3.2 and the above interpretation of the decision variables to show that $\text{LPOPT}(H_{\text{typ}}, (\mathcal{D}_t)_{t=1}^n)$ is equal to $\mathbb{E}[\text{OPT}_{\text{rel}}(G)]$, where $\text{OPT}_{\text{rel}}(G)$ is the value of the relaxed benchmark on $G \sim (H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n)$. Alternatively, this follows by considering an optimum solution of LP-new with respect to G . The claim then follows via a conditioning argument in conjunction with an application of Theorem 4.1, and so we defer the proof to Appendix B.

Theorem 4.1. *For any known i.d instance $(H_{\text{typ}}, (\mathcal{D}_t)_{t=1}^n)$, it holds that $\text{OPT}(H_{\text{typ}}, (\mathcal{D}_t)_{t=1}^n) \leq \text{LPOPT}(H_{\text{typ}}, (\mathcal{D}_t)_{t=1}^n)$.*

Now, given a feasible solution to LP-new-id, say $(x_t(\mathbf{e} \parallel b))_{t \in [n], b \in B, \mathbf{e} \in \mathcal{C}_b}$, for each $u \in U, t \in [n]$ and $b \in B$ define

$$\tilde{x}_{u,t}(b) := \sum_{\substack{\mathbf{e} \in \mathcal{C}_b: \\ (u,b) \in \mathbf{e}}} g(\mathbf{e}_{<(u,b)}) \cdot p_{u,b} \cdot x_t(\mathbf{e} \parallel b). \quad (4.4)$$

Suppose now that we fix $t \in [n]$ and $b \in B$, and consider the variables, $(x_t(\mathbf{e} \parallel b))_{\mathbf{e} \in \mathcal{C}_b}$. Observe that (4.2) ensures that

$$\frac{\sum_{\mathbf{e} \in \mathcal{C}_b} x_t(\mathbf{e} \parallel b)}{r_t(b)} = 1.$$

Hence, if v_t is drawn from \mathcal{D}_t , then VERTEXPROBE may be passed the input $(v_t, \partial(v_t), (x_t(\mathbf{e} \parallel v_t)/r_t(v_t))_{\mathbf{e} \in \mathcal{C}_{v_t}})$, no matter which type node v_t is instantiated as. As such, if we define $C(u, v_t)$ as the event in which VERTEXPROBE outputs the edge (u, v_t) , then observe the following extension of Lemma 3.4:

Lemma 4.2. *If VERTEXPROBE is passed $(v_t, \partial(v_t), (x_t(\mathbf{e} \parallel v_t)/r_t(v_t))_{\mathbf{e} \in \mathcal{C}_{v_t}})$, then*

$$\mathbb{P}[C(u, v_t) \mid v_t = b] = \frac{\tilde{x}_{u,t}(b)}{r_t(b)}$$

Remark 4.3. As in Lemma 3.4, if $C(u, v_t)$ occurs, then we say that VERTEXPROBE commits to the edge (u, v_t) .

Suppose now that each vertex v_t has an arrival time, say $Y_t \in [0, 1]$, drawn *u.a.r.* and independently for $t \in [n]$. The values $(Y_t)_{t=1}^n$ again indicate the increasing order in which the vertices of $G \sim (H_{\text{typ}}, (\mathcal{D}_t)_{t=1}^n)$ arrive. We first consider the following online probing algorithm, without any sophisticated CRS:

Algorithm 5 Known I.D. – ROM

Input: a known i.d. input $(H_{\text{typ}}, (\mathcal{D}_t)_{t=1}^n)$.

Output: a matching \mathcal{M} of active edges of $G \sim (H_{\text{typ}}, (\mathcal{D}_t)_{t=1}^n)$.

- 1: $\mathcal{M} \leftarrow \emptyset$.
 - 2: Compute an optimum solution of LP-new-id for $(H_{\text{typ}}, (\mathcal{D}_t)_{t=1}^n)$, say $(x_t(e \parallel b))_{t \in [n], b \in B, e \in \mathcal{C}_b}$.
 - 3: **for** $t \in [n]$ in increasing order of Y_t **do**
 - 4: Set $e \leftarrow \text{VERTEXPROBE}(v_t, \partial(v_t), (x_t(e \parallel v_t)/r_t(v_t))_{e \in \mathcal{C}_{v_t}})$.
 - 5: **if** $e = (u, v_t)$ for some $u \in U$, and u is unmatched **then**
 - 6: Add e to \mathcal{M} .
 - 7: **end if**
 - 8: **end for**
 - 9: **return** \mathcal{M} .
-

Similarly, to Algorithm 2 of Proposition 3.7, one can show that Algorithm 5 attains a competitive ratio of $1/2$. Interestingly, if the distributions $(\mathcal{D}_t)_{t=1}^n$ are identical – that is, we work in the known i.i.d. model – then it is easy to show that this algorithm’s competitive ratio improves to $1 - 1/e$.

Proposition 4.4. *If Algorithm 5 is presented a known i.i.d. input, say the type graph H_{typ} together with the (fixed) distribution \mathcal{D} , then $\mathbb{E}[w(\mathcal{M})] \geq (1 - 1/e) \text{OPT}(H_{\text{typ}}, \mathcal{D})$.*

In order to prove Theorems 2.6 and 2.7, we again must apply more sophisticated forms of contention resolution. Observe that for each $u \in U$, in the execution of Algorithm 5, the probability that $\text{VERTEXPROBE}(v_t, \partial(v_t), (x_t(e \parallel v_t)/r_t(v_t))_{e \in \mathcal{C}_{v_t}})$ commits to the edge (u, v_t) is precisely,

$$z_{u,t} := \sum_{b \in B} \tilde{x}_{u,t}(b) = \sum_{b \in B} \sum_{\substack{e \in \mathcal{C}_b: \\ (u,b) \in e}} p_{u,b} \cdot g(e_{\langle (u,b) \rangle}) \cdot x_t(e \parallel b) \quad (4.5)$$

Moreover, the events $(C(u, v_t))_{t=1}^n$ are independent. Thus, it is again natural to again apply contention resolution on each vertex $u \in U$, as done in Algorithm 4.

Algorithm 6 Known I.D. – ROM – Modified

Input: a known i.d. input $(H_{\text{typ}}, (\mathcal{D}_t)_{t=1}^n)$.

Output: a matching \mathcal{M} of active edges of $G \sim (H_{\text{typ}}, (\mathcal{D}_t)_{t=1}^n)$.

- 1: $\mathcal{M} \leftarrow \emptyset$.
 - 2: Compute an optimum solution of LP-new-id for $(H_{\text{typ}}, (\mathcal{D}_t)_{t=1}^n)$, say $(x_t(e \parallel b))_{t \in [n], b \in B, e \in \mathcal{C}_b}$.
 - 3: **for** $t \in [n]$ in increasing order of Y_t **do**
 - 4: Set $e \leftarrow \text{VERTEXPROBE}(v_t, \partial(v_t), (x_t(e \parallel v_t)/r_t(v_t))_{e \in \mathcal{C}_{v_t}})$.
 - 5: **if** $e = (u, v_t)$ for some $u \in U$, and u is unmatched **then**
 - 6: Add e to \mathcal{M} independently with probability $\exp(-Y_t \cdot z_{u,t})$.
 - 7: **end if**
 - 8: **end for**
 - 9: **return** \mathcal{M} .
-

Proof of Theorem 2.6. Analyzing Algorithm 6 follows in the same way as in the proof of Theorem 2.1, with the only change being that the performance of Algorithm 6 is compared against $\text{LPOPT}(H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n)$, and thus the adaptive benchmark $\text{OPT}(H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n)$ via an application of Theorem 4.1. \square

More interesting is how we can adapt Algorithm 5 in the case of adversarial arrivals. For this, we again make use of existing contention resolution schemes. In particular, we adapt the OCRS used by Ezra et al. [29].

Given the ground set $[k] = \{1, \dots, k\}$, suppose the elements of $[k]$ are presented according to some permutation $\pi : [k] \rightarrow [k]$ (i.e., $\pi(1), \dots, \pi(k)$), and $\mathbf{z} \in [0, 1]^k$ satisfies $\sum_{i=1}^k z_i \leq 1$. Upon the arrival of element $\pi(t) \in [k]$, compute

$$q_t := \frac{1}{2 - \sum_{i=1}^{t-1} z_{\pi(i)}}.$$

Observe that $0 \leq q_t \leq 1$, as $0 \leq \sum_{i=1}^k z_i \leq 1$.

We consider the scheme of Ezra et al. [29], restricted to the case of a rank 1 matroid. Note that this scheme is similar to the OCRS considered by Lee and Singla [46], however it has the benefit of not requiring the adversary to present the arrival order of $[k]$ to the algorithm upfront.

Algorithm 7 OCRS – Ezra et al. [29]

Input: $\mathbf{z} \in \mathcal{P}$, where $\mathcal{P} \subseteq [0, 1]^k$.

$\triangleright \mathcal{P}$ is the convex relaxation of the rank 1 matroid

Output: at most one element of $[k]$.

- 1: **for** $t = 1, \dots, k$ **do**
 - 2: **if** $\pi(t) \in R(\mathbf{z})$ **then** $\triangleright \pi(t)$ is in $R(\mathbf{z})$ with probability $z_{\pi(t)}$
 - 3: Compute q_t , based on the arrivals $\pi(1), \dots, \pi(t-1)$.
 - 4: **return** $\pi(t)$ independently with probability q_t .
 - 5: **end if**
 - 6: **end for**
 - 7: **return** \emptyset . \triangleright pass on returning an element of $[k]$
-

Theorem 4.5 (Ezra et al. [46]). *Algorithm 7 is an OCRS for a rank 1 matroid which is 1/2-selectable.*

We return to the problem of designing a modification of Algorithm 5 that works for adversarial vertex arrivals. Assume vertices v_1, \dots, v_n are presented to the online probing algorithm using the permutation $\pi : [n] \rightarrow [n]$ (i.e., $v_{\pi(1)}, \dots, v_{\pi(n)}$). For each $t \in [n]$ and $u \in U$, define

$$q_{u,t} := \frac{1}{2 - \sum_{i=1}^{t-1} z_{u,\pi(i)}}, \tag{4.6}$$

where we recall $z_{u,j} := \sum_{b \in B} \tilde{x}_{u,j}(b)$. Clearly, $\sum_{j \in [n]} z_{u,j} \leq 1$, by constraint (4.1) of LP-new-id, and so we get the following online probing algorithm:

Algorithm 8 Known I.D. – AOM – Modified

Input: a known i.d. input $(H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n)$.

Output: a matching \mathcal{M} of active edges of $G \sim (H_{\text{typ}}, (\mathcal{D}_t)_{t=1}^n)$.

- 1: $\mathcal{M} \leftarrow \emptyset$.
 - 2: Compute an optimum solution of LP-new-id for $(H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n)$, say $(x_i(e \parallel b))_{i \in [n], b \in B, e \in \mathcal{C}_b}$.
 - 3: **for** $t = 1, \dots, n$ **do**
 - 4: Based on the previous arrivals $v_{\pi(1)}, \dots, v_{\pi(t-1)}$ before $v_{\pi(t)}$, compute values $(q_{u,t})_{u \in U}$.
 - 5: Set $e \leftarrow \text{VERTEXPROBE}(v_t, \partial(v_t), (x_t(e \parallel v_t)/r_t(v_t))_{e \in \mathcal{C}_{v_t}})$.
 - 6: **if** $e = (u, v_t)$ for some $u \in U$, and u is unmatched **then**
 - 7: Add e to \mathcal{M} independently with probability $q_{u,t}$.
 - 8: **end if**
 - 9: **end for**
 - 10: **return** \mathcal{M} .
-

Proof of Theorem 2.7. Analysing Algorithm 8 follows the proof of Theorem 2.1. □

We conclude the section by noting that LP-new-id can be solved in time $\text{poly}(|H_{\text{typ}}|, (r_t(b))_{t \in [n], b \in B})$ in both the membership and demand oracle models, under the assumptions of Theorem 2.9. The argument follows as in the proof of Theorem 3.10, with a slight adjustment to handle the values $(r_t(b))_{t \in [n], b \in B}$ and so we defer the details. The efficiency of Algorithms 6 and 8 thereby follows, as claimed in Theorem 2.9.

5 Relaxing the Adaptive Benchmark: Proving Lemma 3.2

Let us suppose that $G = (U, V, E)$ is a stochastic graph with substring-closed probing constraints $(\mathcal{C}_v)_{v \in V}$. In order to prove Lemma 3.2, we must show that there exists an optimum relaxed probing algorithm which is non-adaptive and satisfies (Q_1) . Our high level approach is to consider an optimum relaxed probing algorithm \mathcal{A} which satisfies (Q_1) , and then to construct a new non-adaptive algorithm \mathcal{B} by *stealing* the strategy of \mathcal{A} , without any loss in performance. More specifically, we construct \mathcal{B} by writing down for each $v \in V$ and $e \in \mathcal{C}_v$ the probability that \mathcal{A} probes the edges of e in order. These probabilities necessarily satisfy certain inequalities which we make use of in designing \mathcal{B} . In order to do so, we need a technical randomized rounding procedure whose precise relevance will become clear in the proof of Lemma 3.2.

Suppose that $e \in E^{(*)}$, and for each $j \geq 0$, denote e_j as the j^{th} edge of e , where $e_j := \lambda$ if $j = 0$ or $j > |e|$ (recall that λ is the empty-string). Let us now assume that $(y_v(e))_{e \in \mathcal{C}_v}$ is a collection of values which satisfies $y_v(\lambda) = 1$, and

$$\sum_{\substack{e \in \partial(v): \\ (e', e) \in \mathcal{C}_v}} y_v(e', e) \leq y_v(e'), \quad (5.1)$$

for each $e' \in \mathcal{C}_v$.

Proposition 5.1. *Given a collection of values $(y_v(e))_{e \in \mathcal{C}_v}$ which satisfy (5.1), there exists a distribution \mathcal{D}^v supported on \mathcal{C}_v , such that if $\mathbf{Y} \sim \mathcal{D}^v$, then for each $e \in \mathcal{C}_v$ with $k := |e| \geq 1$, it holds*

that

$$\mathbb{P}[(\mathbf{Y}_1, \dots, \mathbf{Y}_k) = (\mathbf{e}_1, \dots, \mathbf{e}_k)] = y_v(\mathbf{e}), \quad (5.2)$$

where $\mathbf{Y}_1, \dots, \mathbf{Y}_k$ are the first k edges of \mathbf{Y} .

Proof. Observe first that for each $\mathbf{e}' \in E^{(*)}$, we have that

$$\sum_{\substack{e \in \partial(v): \\ (\mathbf{e}', e) \in \mathcal{C}_v}} \frac{y_v(\mathbf{e}', e)}{y_v(\mathbf{e}')} \leq 1 \quad (5.3)$$

as a result of (5.1) (recall that $y_v(\lambda) := 1$). We thus define for each $\mathbf{e}' \in \mathcal{C}_v$,

$$z_v(\mathbf{e}') := 1 - \sum_{\substack{e \in \partial(v): \\ (\mathbf{e}', e) \in \mathcal{C}_v}} \frac{y_v(\mathbf{e}', e)}{y_v(\mathbf{e}')}, \quad (5.4)$$

which we observe has the property that $0 \leq z_v(\mathbf{e}') \leq 1$. This leads to the following randomized rounding algorithm, which we claim outputs a random string \mathbf{Y} which satisfies the desired properties:

Algorithm 9 VertexRound

Input: a collection of values $(y_v(\mathbf{e}))_{\mathbf{e} \in \mathcal{C}_v}$ satisfying (5.1).

Output: a random string $\mathbf{Y} = (Y_0, Y_1, \dots, Y_{|U|})$ supported on \mathcal{C}_v .

- 1: Set $\mathbf{e}' \leftarrow \lambda$.
 - 2: Initialize $Y_i = \lambda$ for each $i = 0, \dots, |U| - 1$.
 - 3: **for** $i = 0, \dots, |U|$ **do**
 - 4: Exit the “for loop” with probability $z_v(\mathbf{e}')$. ▷ pass with a certain probability – see (5.4)
 - 5: Draw $e \in \partial(v)$ satisfying $(\mathbf{e}', e) \in \mathcal{C}_v$ with probability $y_v(\mathbf{e}', e)/(y_v(\mathbf{e}') (1 - z_v(\mathbf{e}')))$.
 - 6: Set $Y_i = e$.
 - 7: $\mathbf{e}' \leftarrow (\mathbf{e}', e)$.
 - 8: **end for**
 - 9: **return** $\mathbf{Y} = (Y_0, Y_1, \dots, Y_{|U|})$. ▷ concatenate the edges in order and return the resulting string
-

Clearly, the random string \mathbf{Y} is supported on \mathcal{C}_v , thanks to line 5 of Algorithm 9. We now show that (5.2) holds. As such, let us first assume $k = 1$, and $e \in \partial(v)$ satisfies $(e) \in \mathcal{C}_v$. Observe that

$$\mathbb{P}[Y_1 = e] = (1 - z_v(\lambda)) \frac{y_v(e)}{1 - z_v(\lambda)} = y_v(e),$$

as the algorithm exits the “for loop” with probability $z_v(\lambda) = 1 - y_v(\lambda) = 0$, and then draws e with probability $y_v(e)$.

In general, take $k \geq 2$, and assume that for each $\mathbf{e}' \in \mathcal{C}_v$ with $|\mathbf{e}'| < k$, it holds that

$$\mathbb{P}[(Y_1, \dots, Y_k) = \mathbf{e}'] = y_v(\mathbf{e}').$$

If we now fix $\mathbf{e} = (e_1, \dots, e_k) \in \mathcal{C}_v$ with $|\mathbf{e}| = k$, observe that $\mathbf{e}_{<k} := (e_1, \dots, e_{k-1}) \in \mathcal{C}_v$, as \mathcal{C}_v is substring-closed. Moreover,

$$\begin{aligned} \mathbb{P}[(Y_1, \dots, Y_k) = \mathbf{e}] &= \mathbb{P}[Y_k = e_k \mid (Y_1, \dots, Y_{k-1}) = \mathbf{e}_{<k}] \cdot \mathbb{P}[(Y_1, \dots, Y_{k-1}) = \mathbf{e}_{<k}] \\ &= \mathbb{P}[Y_k = e_k \mid (Y_1, \dots, Y_{k-1}) = \mathbf{e}_{<k}] \cdot y_v(\mathbf{e}_{<k}), \end{aligned}$$

where the last line follows by the induction hypothesis since $e_{<k} \in \mathcal{C}_v$ is of length $k - 1$. We know however that

$$\mathbb{P}[Y_k = e_k \mid (Y_1, \dots, Y_{k-1}) = e_{<k}] = (1 - z_v(e_{<k})) \frac{y_v(e_{<k}, e_k)}{y_v(e_{<k})(1 - z_v(e_{<k}))} = \frac{y_v(e_{<k}, e_k)}{y_v(e_{<k})}.$$

This is because once we condition on the event $(Y_1, \dots, Y_{k-1}) = e_{<k}$, we know that the algorithm passes with probability $1 - z_v(e_{<k})$, and then selects $e_k \in \partial(v)$ with probability $y_v(e_{<k}, e_k)/(y_v(e_{<k})(1 - z_v(e_{<k})))$ (provided a pass does *not* occur), since $(e_{<k}, e_k) \in \mathcal{C}_v$ by assumption. As such, we have that

$$\mathbb{P}[(Y_1, \dots, Y_k) = e] = y_v(e),$$

and so the proof is complete. \square

We are now ready to prove Lemma 3.2.

Proof of Lemma 3.2. Suppose that \mathcal{A} is an optimum relaxed probing algorithm which returns the one-sided matching \mathcal{M} after executing on the stochastic graph $G = (U, V, E)$. In a slight abuse of terminology, we say that e is matched by \mathcal{A} , provided e is included in \mathcal{M} . We shall also make the simplifying assumption that $p_e < 1$ for each $e \in E$, as the proof can be clearly adapted to handle the case when certain edges have $p_e = 1$.

Observe that since \mathcal{A} is optimum, it is clear that we may assume the following properties hold without loss of generality: For each $e \in E$,

1. e is probed only if e can be added to the currently constructed one-sided matching.
2. If e is probed and $\text{st}(e) = 1$, then e is included in \mathcal{M} .

Thus, in order to prove the lemma, we must find an alternative algorithm \mathcal{B} which is non-adaptive, yet continues to remain optimum. To this end, we shall first express $\mathbb{E}[w(\mathcal{M}(v))]$ in a convenient form for each $v \in V$, where $w(\mathcal{M}(v))$ is the weight of the edge matched to v (which is 0 if no match occurs).

Given $v \in V$ and $1 \leq i \leq |U|$, we define X_i^v to be the i^{th} edge which includes v that is probed by \mathcal{A} . This is set equal to λ by convention, provided no such edge exists. We may then define $\mathbf{X}^v := (X_1^v, \dots, X_{|U|}^v)$. Moreover, given $e = (e_1, \dots, e_k) \in E^{(*)}$, define $S(e)$ to be the event in which e_k is the only active edge amongst e_1, \dots, e_k . Observe then that (1) and (2) ensure that

$$\mathbb{E}[w(\mathcal{M}(v))] = \sum_{e=(e_1, \dots, e_k) \in \mathcal{C}_v} w_{e_k} \mathbb{P}[S(e) \cap \{\mathbf{X}_{\leq k}^v = e\}],$$

where $\mathbf{X}_{\leq k}^v := (X_1^v, \dots, X_k^v)$. Moreover, (1) and (2) imply that if $e = (e_1, \dots, e_k) \in \mathcal{C}_v$, then

$$\mathbb{P}[\{\text{st}(e_k) = 1\} \cap \{\mathbf{X}_{\leq k}^v = e\}] = \mathbb{P}[S(e) \cap \{\mathbf{X}_{\leq k}^v = e\}]. \quad (5.5)$$

Thus,

$$\begin{aligned} \mathbb{E}[w(\mathcal{M}(v))] &= \sum_{e=(e_1, \dots, e_k) \in \mathcal{C}_v} w_{e_k} \mathbb{P}[S(e) \cap \{\mathbf{X}_{\leq k}^v = e\}] \\ &= \sum_{e=(e_1, \dots, e_k) \in \mathcal{C}_v} w_{e_k} \mathbb{P}[\{\text{st}(e_k) = 1\} \cap \{\mathbf{X}_{\leq k}^v = e\}] \\ &= \sum_{e=(e_1, \dots, e_k) \in \mathcal{C}_v} w_{e_k} p_{e_k} \mathbb{P}[\mathbf{X}_{\leq k}^v = e], \end{aligned}$$

where the final equality holds since \mathcal{A} must decide on whether to probe e_k prior to revealing $\text{st}(e_k)$. As a result, after summing over $v \in V$,

$$\mathbb{E}[w(\mathcal{M})] = \sum_{v \in V} \sum_{\mathbf{e}=(e_1, \dots, e_k) \in \mathcal{C}_v} w_{e_k} p_{e_k} \mathbb{P}[\mathbf{X}_{\leq k}^v = \mathbf{e}]. \quad (5.6)$$

Our goal is to find a non-adaptive relaxed probing algorithm which matches the value of (5.6). Thus, for each $v \in V$ and $\mathbf{e} = (e_1, \dots, e_k) \in \mathcal{C}_v$, define

$$x_v(\mathbf{e}) := \mathbb{P}[\mathbf{X}_{\leq k}^v = \mathbf{e}],$$

where $x_v(\lambda) := 1$. This gives us a collection of values, namely $(x_v(\mathbf{e}))_{\mathbf{e} \in \mathcal{C}_v}$, for which the following conditions hold: For each $\mathbf{e}' \in \mathcal{C}_v$,

$$\sum_{\substack{e \in \partial(v): \\ (\mathbf{e}', e) \in \mathcal{C}_v}} x_v(\mathbf{e}', e) \leq (1 - p_e) x_v(\mathbf{e}'). \quad (5.7)$$

Now, given $\mathbf{e} = (e_1, \dots, e_k) \in \mathcal{C}_v$, define

$$y_v(\mathbf{e}) := \frac{x_v(\mathbf{e})}{\prod_{j=1}^{|\mathbf{e}|-1} (1 - p_{e_j})}. \quad (5.8)$$

Observe that (5.7) ensures that for each $\mathbf{e}' \in \mathcal{C}_v$

$$\sum_{\substack{e \in \partial(v): \\ (\mathbf{e}', e) \in \mathcal{C}_v}} y_v(\mathbf{e}', e) \leq y_v(\mathbf{e}'). \quad (5.9)$$

As a result, Proposition 5.1 implies that for each $v \in V$, there exists a distribution \mathcal{D}^v such that if $\mathbf{Y}^v \sim \mathcal{D}^v$, then for each $\mathbf{e} \in \mathcal{C}_v$ with $|\mathbf{e}| = k \geq 1$,

$$\mathbb{P}[\mathbf{Y}_{\leq k}^v = \mathbf{e}] = y_v(\mathbf{e}). \quad (5.10)$$

Moreover, \mathbf{Y}^v is drawn independently from the edge states, $(\text{st}(e))_{e \in E}$. Consider now the following algorithm \mathcal{B} , which clearly satisfies the desired properties (Q_1) and (Q_2) of Lemma 3.2:

Algorithm 10 Algorithm \mathcal{B}

Input: a stochastic graph $G = (U, V, E)$.

Output: a one-sided matching \mathcal{N} of G of active edges.

- 1: Set $\mathcal{N} \leftarrow \emptyset$.
 - 2: Draw $(\mathbf{Y}^v)_{v \in V}$ according to the product distribution $\prod_{v \in V} \mathcal{D}^v$.
 - 3: **for** $v \in V$ **do**
 - 4: **for** $i = 1, \dots, |\mathbf{Y}^v|$ **do**
 - 5: Set $e \leftarrow \mathbf{Y}_i^v$.
 - 6: Probe the edge e , revealing $\text{st}(e)$.
 - 7: **if** $\text{st}(e) = 1$ and v is unmatched by \mathcal{N} **then**
 - 8: Add e to \mathcal{N} .
 - 9: **end if**
 - 10: **end for**
 - 11: **end for**
 - 12: **return** \mathcal{N} .
-

Using (5.10) and the non-adaptivity of \mathcal{B} , it is clear that for each $v \in V$,

$$\begin{aligned}
\mathbb{E}[w(\mathcal{N}(v))] &= \sum_{\mathbf{e}=(e_1, \dots, e_k) \in \mathcal{C}_v} w_{e_k} \mathbb{P}[S(\mathbf{e})] \cdot \mathbb{P}[\mathbf{Y}_{\leq k}^v = \mathbf{e}] \\
&= \sum_{\mathbf{e}=(e_1, \dots, e_k) \in \mathcal{C}_v} w_{e_k} p_{e_k} \prod_{j=1}^{|\mathbf{e}|-1} (1 - p_{e_j}) y_v(\mathbf{e}) \\
&= \sum_{\mathbf{e}=(e_1, \dots, e_k) \in \mathcal{C}_v} w_{e_k} p_{e_k} x_v(\mathbf{e}) \\
&= \mathbb{E}[w(\mathcal{M}(v))].
\end{aligned}$$

Thus, after summing over $v \in V$, it holds that $\mathbb{E}[w(\mathcal{N})] = \mathbb{E}[w(\mathcal{M})] = \text{OPT}_{\text{rel}}(G)$, and so in addition to satisfying (Q_1) and (Q_2) , \mathcal{B} is optimum. Finally, it is easy to show that each $u \in U$ is matched by \mathcal{N} at most once in expectation, and so \mathcal{B} is a relaxed probing algorithm which is optimum and satisfies the required properties of Lemma 3.2. \square

6 A Tight Adaptivity Gap

Similarly, to the definition of the adaptive benchmark, we define the **non-adaptive benchmark**, as the optimum performance of a non-adaptive probing algorithm on G . That is, $\text{OPT}_{\text{n-adap}}(G) := \sup_{\mathcal{B}} \mathbb{E}[w(\mathcal{B}(G))]$, where the supremum is over all offline non-adaptive probing algorithms. The upper bound (negative result) of Theorem 2.2 can thus be viewed a statement regarding the power of adaptivity. More precisely, we define the **adaptivity gap** of the bipartite stochastic matching problem, as the ratio

$$\inf_G \frac{\text{OPT}_{\text{n-adap}}(G)}{\text{OPT}(G)}, \quad (6.1)$$

where the infimum is over all bipartite stochastic graphs G .

We can therefore restate Theorem 2.2 in the following terminology:

Theorem 6.1. *The adaptivity gap of the bipartite stochastic matching problem is no smaller than $1 - 1/e$.*

Theorem 6.1 follows by considering a sequence of stochastic graphs. In particular, given $n \geq 1$, consider functions $p = p(n)$ and $s = s(n)$ which satisfy the following:

1. $p \ll 1/\sqrt{n}$ and $s \rightarrow \infty$ as $n \rightarrow \infty$.
2. $s \leq pn$ and $s = (1 - o(1))pn$.

Consider now a an unweighted stochastic graph $G_n = (U, V, E)$ with unit patience values, and which satisfies $|U| = s$ and $|V| = n$. Moreover, assume that $p_{u,v} = p$ for all $u \in U$ and $v \in V$. Observe that G_n corresponds to the bipartite Erdős-Rényi random graph $\mathbb{G}(s, n, p)$.

Lemma 6.2. *The adaptive benchmark returns a matching of size asymptotically equal to s when executing on G_n ; that is, $\text{OPT}(G_n) = (1 + o(1))s$.*

We defer the proof of Lemma 6.2, as it is routine analysis of the Erdős–Rényi random graph $\mathbb{G}(s, n, p)$. Instead, we focus on proving the following lemma, which together with Lemma 6.2 implies the upper bound of Theorem 6.1:

Lemma 6.3. *The non-adaptive benchmark returns in expectation a matching of size at most $(1 + o(1))\left(1 - \frac{1}{e}\right)s$ when executing on G_n . That is,*

$$OPT_{n\text{-adp}}(G) \leq (1 + o(1)) \left(1 - \frac{1}{e}\right) s.$$

Proof. Let \mathcal{A} be a non-adaptive probing algorithm, which we may assume is deterministic without loss of generality. As the probes of \mathcal{A} are determined independently of the random variables $(\text{st}(e))_{e \in E}$, we can define $x_e \in \{0, 1\}$ for each $e \in E$ to indicate whether or not \mathcal{A} probes the edge e .

Now, if $\mathcal{A}(G)$ is the matching returned by \mathcal{A} , then using the independence of the edge states $(\text{st}(e))_{e \in E}$, we get that

$$\mathbb{P}[u \text{ matched by } \mathcal{A}(G)] = \mathbb{P} \left[\bigcup_{v \in V: x_{u,v}=1} \text{st}(u, v) = 1 \right] \quad (6.2)$$

$$\geq 1 - \prod_{v \in V} (1 - px_{u,v}) \quad (6.3)$$

and so,

$$\mathbb{E}[|\mathcal{A}(G)|] \leq s - \sum_{u \in U} \prod_{v \in V} (1 - px_{u,v}).$$

As such, if we can show that

$$\sum_{u \in U} \prod_{v \in V} (1 - px_{u,v}) \geq (1 - o(1)) \frac{s}{e},$$

then this will imply that

$$\mathbb{E}[|\mathcal{A}(G)|] \leq (1 + o(1)) \left(1 - \frac{1}{e}\right) s.$$

To see this, first observe that since $p(n) \rightarrow 0$ as $n \rightarrow \infty$, we know that

$$1 - px_{u,v} = (1 + o(1)) \exp(-px_{u,v})$$

for each $v \in V$. In fact, since $px_{u,v} \leq p$ for all $v \in V$, the asymptotics are uniform across V . More precisely, there exists $C > 0$, such that for n sufficiently large,

$$1 - px_{u,v} \geq (1 - Cp^2) \exp(-px_{u,v})$$

for all $v \in V$. As a result,

$$\begin{aligned} \prod_{v \in V} (1 - px_{u,v}) &\geq (1 - Cp^2)^n \exp \left(- \sum_{v \in V} px_{u,v} \right) \\ &= (1 + o(1)) \exp \left(- \sum_{v \in V} px_{u,v} \right), \end{aligned}$$

where the second line follows since $p \ll 1/\sqrt{n}$ by assumption. On the other hand, Jensen’s inequality ensures that

$$\sum_{u \in U} \frac{\exp\left(-\sum_{v \in V} px_{u,v}\right)}{s} \geq \exp\left(-\frac{\sum_{u \in U, v \in V} px_{u,v}}{n}\right).$$

However, $\sum_{u \in U} x_{u,v} \leq 1$ for each $v \in V$. Thus, $\sum_{u \in U, v \in V} px_{u,v} \leq pn$, and so

$$\exp\left(-\frac{\sum_{u \in U, v \in V} px_{u,v}}{s}\right) \geq \exp\left(-\frac{pn}{s}\right) \geq \frac{1}{e},$$

where the last line follows since $pn \leq s$. It follows that

$$\sum_{u \in U} \prod_{v \in V} (1 - px_{u,v}) \geq (1 + o(1)) \frac{s}{e},$$

and so

$$\mathbb{E}[|\mathcal{A}(G)|] \leq (1 + o(1)) \left(1 - \frac{1}{e}\right) s.$$

As the asymptotics hold uniformly across each deterministic non-adaptive algorithm \mathcal{A} , this completes the proof. □

Theorems 2.1 and 6.1 exactly characterize the adaptivity gap of the bipartite stochastic matching problem:

Corollary 6.4. *The adaptivity gap of the bipartite stochastic matching problem is $1 - 1/e$.*

7 Conclusion and open problems

We have considered the stochastic bipartite matching problem (with probing constraints) in a few settings. As discussed, our results generalize both the classical bipartite matching problem that does not have probing constraints and the prophet inequality and prophet secretary problems. Our algorithms are polynomial time assuming a mild assumption on the probing constraints which, in particular, generalizes the standard patience constraints.

Our main results concern stochastic graphs generated from i.i.d. distributions for which we obtain an optimal $\frac{1}{2}$ competitive ratio for adversarial input sequences and a $1 - 1/e$ competitive ratio for random order input sequences. While the i.i.d. setting subsumes the known stochastic graph setting, this latter problem is of independent interest as this is the probing model studied by Chen et al. [20]. Unlike the classical setting, it is not clear if the Karande et al. [41] result that “ROM implies known (and unknown) i.i.d” holds in the known stochastic graph model.

There are some basic questions that are unresolved. Perhaps the most basic question which is also unresolved in the classical setting is to bridge the gap between the positive $1 - 1/e$ competitive ratio and inapproximations in the context of random order input sequences. In terms of the single item prophet secretary problem (without probing), Correa et al. [22] obtain a .669 competitive ratio following Azar et al. [8] who were the first to surpass the $1 - 1/e$ “barrier”. Note that in an i.i.d. setting there is no difference between adversarial input sequences and random order sequences. Correa et al. [22] also establish a .732 inapproximation. Our adaptivity gap proves the

optimality of the $1 - 1/e$ competitive ratio for non-adaptive algorithms. Can we surpass $1 - 1/e$ in the probing setting for i.d. input sequences or for the the special case of i.i.d. input sequences? Is there a provable difference between stochastic bipartite matching (with probing constraints) and the classical online settings? Can we obtain the same competitive results against an optimal offline *non-committal* benchmark which respects the probing constraints but not the commitment constraint.

One interesting extension of the probing model is to allow non-Bernoulli edge random variables to describe edge uncertainty. Even for a single online vertex with full patience, this problem is interesting and has been studied significantly less (see, PROBLEMMAX in Segev and Singla [54]). A general understanding of edge uncertainty suggests a possible relation between stochastic probing and online algorithms with ML (untrusted) advice (see, for example, Lavastida et al. [45]).

References

- [1] Marek Adamczyk. Improved analysis of the greedy algorithm for stochastic matching. *Inf. Process. Lett.*, 111(15):731–737, 2011.
- [2] Marek Adamczyk, Fabrizio Grandoni, Stefano Leonardi, and Michal Włodarczyk. When the optimum is also blind: a new perspective on universal optimization. In *ICALP*, 2017.
- [3] Marek Adamczyk, Fabrizio Grandoni, and Joydeep Mukherjee. Improved approximation algorithms for stochastic matching. In Nikhil Bansal and Irene Finocchi, editors, *Algorithms - ESA 2015 - 23rd Annual European Symposium, Patras, Greece, September 14-16, 2015, Proceedings*, volume 9294 of *Lecture Notes in Computer Science*, pages 1–12. Springer, 2015.
- [4] Marek Adamczyk and Michał Włodarczyk. Random order contention resolution schemes. In *2018 IEEE 59th Annual Symposium on Foundations of Computer Science (FOCS)*, pages 790–801. IEEE, 2018.
- [5] Gagan Aggarwal, Gagan Goel, Chinmay Karande, and Aranyak Mehta. Online vertex-weighted bipartite matching and single-bid budgeted allocations. In *Proceedings of the Twenty-Second Annual ACM-SIAM Symposium on Discrete Algorithms, SODA 2011, San Francisco, California, USA, January 23-25, 2011*, pages 1253–1264, 2011.
- [6] Saeed Alaei, MohammadTaghi Hajiaghayi, and Vahid Liaghat. Online prophet-inequality matching with applications to ad allocation. In *Proceedings of the 13th ACM Conference on Electronic Commerce, EC '12*, page 18–35, New York, NY, USA, 2012. Association for Computing Machinery.
- [7] Arash Asadpour and Hamid Nazerzadeh. Maximizing stochastic monotone submodular functions. *Management Science*, 62(8):2374–2391, 2016.
- [8] Yossi Azar, Ashish Chiplunkar, and Haim Kaplan. Prophet secretary: Surpassing the $1-1/e$ barrier. In Éva Tardos, Edith Elkind, and Rakesh Vohra, editors, *Proceedings of the 2018 ACM Conference on Economics and Computation, Ithaca, NY, USA, June 18-22, 2018*, pages 303–318. ACM, 2018.

- [9] Nikhil Bansal, Anupam Gupta, Jian Li, Julián Mestre, Viswanath Nagarajan, and Atri Rudra. When LP is the cure for your matching woes: Improved bounds for stochastic matchings. *Algorithmica*, 63(4):733–762, 2012.
- [10] Alok Baveja, Amit Chavan, Andrei Nikiforov, Aravind Srinivasan, and Pan Xu. Improved bounds in stochastic matching and optimization. *Algorithmica*, 80(11):3225–3252, Nov 2018.
- [11] Liad Blumrosen and Noam Nisan. On the computational power of iterative auctions. In John Riedl, Michael J. Kearns, and Michael K. Reiter, editors, *Proceedings 6th ACM Conference on Electronic Commerce (EC-2005), Vancouver, BC, Canada, June 5-8, 2005*, pages 29–43. ACM, 2005.
- [12] Liad Blumrosen and Noam Nisan. On the computational power of demand queries. *SIAM J. Comput.*, 39(4):1372–1391, 2009.
- [13] Allan Borodin, Calum MacRury, and Akash Rakheja. Greedy approaches to online stochastic matching. *CoRR*, abs/2008.09260, 2020.
- [14] Domagoj Bradac, Sahil Singla, and Goran Zuzic. (near) optimal adaptivity gaps for stochastic multi-value probing. In Dimitris Achlioptas and László A. Végh, editors, *Approximation, Randomization, and Combinatorial Optimization. Algorithms and Techniques, APPROX/RANDOM 2019, September 20-22, 2019, Massachusetts Institute of Technology, Cambridge, MA, USA*, volume 145 of *LIPICs*, pages 49:1–49:21. Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 2019.
- [15] Brian Brubach, Nathaniel Grammel, and Aravind Srinivasan. Vertex-weighted online stochastic matching with patience constraints. *CoRR*, abs/1907.03963, 2019.
- [16] Brian Brubach, Karthik Abinav Sankararaman, Aravind Srinivasan, and Pan Xu. New algorithms, better bounds, and a novel model for online stochastic matching. In *24th Annual European Symposium on Algorithms, ESA 2016, August 22-24, 2016, Aarhus, Denmark*, pages 24:1–24:16, 2016.
- [17] Brian Brubach, Karthik Abinav Sankararaman, Aravind Srinivasan, and Pan Xu. Attenuate locally, win globally: Attenuation-based frameworks for online stochastic matching with timeouts. *Algorithmica*, 82(1):64–87, 2020.
- [18] Shuchi Chawla, Kira Goldner, Anna R. Karlin, and J. Benjamin Miller. Non-adaptive matroid prophet inequalities. *CoRR*, abs/2011.09406, 2020.
- [19] Shuchi Chawla, Jason D. Hartline, David L. Malec, and Balasubramanian Sivan. Multi-parameter mechanism design and sequential posted pricing. In Leonard J. Schulman, editor, *Proceedings of the 42nd ACM Symposium on Theory of Computing, STOC 2010, Cambridge, Massachusetts, USA, 5-8 June 2010*, pages 311–320. ACM, 2010.
- [20] Ning Chen, Nicole Immorlica, Anna R. Karlin, Mohammad Mahdian, and Atri Rudra. Approximating matches made in heaven. In *Proceedings of the 36th International Colloquium on Automata, Languages and Programming: Part I, ICALP '09*, pages 266–278, 2009.

- [21] José R. Correa, Patricio Foncea, Dana Pizarro, and Victor Verdugo. From pricing to prophets, and back! *Oper. Res. Lett.*, 47(1):25–29, 2019.
- [22] José R. Correa, Raimundo Saona, and Bruno Ziliotto. Prophet secretary through blind strategies. In *Proceedings of the Thirtieth Annual ACM-SIAM Symposium on Discrete Algorithms, SODA 2019, San Diego, California, USA, January 6-9, 2019*, pages 1946–1961, 2019.
- [23] Brian C. Dean, Michel X. Goemans, and Jan Vondrák. Adaptivity and approximation for stochastic packing problems. In *Proceedings of the Sixteenth Annual ACM-SIAM Symposium on Discrete Algorithms, SODA 2005, Vancouver, British Columbia, Canada, January 23-25, 2005*, pages 395–404, 2005.
- [24] Brian C. Dean, Michel X. Goemans, and Jan Vondrák. Approximating the stochastic knapsack problem: The benefit of adaptivity. *Math. Oper. Res.*, 33(4):945–964, 2008.
- [25] Nikhil R. Devanur, Kamal Jain, and Robert D. Kleinberg. Randomized primal-dual analysis of ranking for online bipartite matching. In *Proceedings of the Twenty-fourth Annual ACM-SIAM Symposium on Discrete Algorithms, SODA '13*, pages 101–107, Philadelphia, PA, USA, 2013. Society for Industrial and Applied Mathematics.
- [26] Alon Eden, Michal Feldman, Amos Fiat, and Kineret Segal. An economic-based analysis of RANKING for online bipartite matching. *CoRR*, abs/1804.06637, 2018.
- [27] Soheil Ehsani, MohammadTaghi Hajiaghayi, Thomas Kesselheim, and Sahil Singla. Prophet secretary for combinatorial auctions and matroids. In *Proceedings of the Twenty-Ninth Annual ACM-SIAM Symposium on Discrete Algorithms, SODA '18*, page 700–714, USA, 2018. Society for Industrial and Applied Mathematics.
- [28] Hossein Esfandiari, Mohammad Taghi Hajiaghayi, Brendan Lucier, and Michael Mitzenmacher. Online pandora’s boxes and bandits. In *The Thirty-Third AAAI Conference on Artificial Intelligence, AAAI 2019, The Thirty-First Innovative Applications of Artificial Intelligence Conference, IAAI 2019, The Ninth AAAI Symposium on Educational Advances in Artificial Intelligence, EAAI 2019, Honolulu, Hawaii, USA, January 27 - February 1, 2019*, pages 1885–1892, 2019.
- [29] Tomer Ezra, Michal Feldman, Nick Gravin, and Zhihao Gavin Tang. Online stochastic max-weight matching: Prophet inequality for vertex and edge arrival models. In *Proceedings of the 21st ACM Conference on Economics and Computation, EC '20*, page 769–787, New York, NY, USA, 2020. Association for Computing Machinery.
- [30] Jon Feldman, Aranyak Mehta, Vahab S. Mirrokni, and S. Muthukrishnan. Online stochastic matching: Beating $1-1/e$. In *50th Annual IEEE Symposium on Foundations of Computer Science, FOCS 2009, October 25-27, 2009, Atlanta, Georgia, USA*, pages 117–126, 2009.
- [31] Moran Feldman, Ola Svensson, and Rico Zenklusen. Online contention resolution schemes. In Robert Krauthgamer, editor, *Proceedings of the Twenty-Seventh Annual ACM-SIAM Symposium on Discrete Algorithms, SODA 2016, Arlington, VA, USA, January 10-12, 2016*, pages 1014–1033. SIAM, 2016.

- [32] Buddhima Gamlath, Sagar Kale, and Ola Svensson. Beating greedy for stochastic bipartite matching. In *Proceedings of the Thirtieth Annual ACM-SIAM Symposium on Discrete Algorithms, SODA '19*, page 2841–2854, USA, 2019. Society for Industrial and Applied Mathematics.
- [33] Bernd Gärtner and Jiri Matousek. *Understanding and using linear programming*. Universitext. Springer, 2007.
- [34] Vineet Goyal and Rajan Udwani. Online matching with stochastic rewards: Optimal competitive ratio via path based formulation. In Péter Biró, Jason Hartline, Michael Ostrovsky, and Ariel D. Procaccia, editors, *EC '20: The 21st ACM Conference on Economics and Computation, Virtual Event, Hungary, July 13-17, 2020*, page 791. ACM, 2020.
- [35] Anupam Gupta and Viswanath Nagarajan. A stochastic probing problem with applications. In Michel X. Goemans and José R. Correa, editors, *Integer Programming and Combinatorial Optimization - 16th International Conference, IPCO 2013, Valparaíso, Chile, March 18-20, 2013. Proceedings*, volume 7801 of *Lecture Notes in Computer Science*, pages 205–216. Springer, 2013.
- [36] Anupam Gupta, Viswanath Nagarajan, and Sahil Singla. Algorithms and adaptivity gaps for stochastic probing. In Robert Krauthgamer, editor, *Proceedings of the Twenty-Seventh Annual ACM-SIAM Symposium on Discrete Algorithms, SODA 2016, Arlington, VA, USA, January 10-12, 2016*, pages 1731–1747. SIAM, 2016.
- [37] Anupam Gupta, Viswanath Nagarajan, and Sahil Singla. Adaptivity gaps for stochastic probing: Submodular and XOS functions. In Philip N. Klein, editor, *Proceedings of the Twenty-Eighth Annual ACM-SIAM Symposium on Discrete Algorithms, SODA 2017, Barcelona, Spain, Hotel Porta Fira, January 16-19*, pages 1688–1702. SIAM, 2017.
- [38] Mohammad Taghi Hajiaghayi, Robert D. Kleinberg, and Tuomas Sandholm. Automated online mechanism design and prophet inequalities. In *Proceedings of the Twenty-Second AAAI Conference on Artificial Intelligence, July 22-26, 2007, Vancouver, British Columbia, Canada*, pages 58–65. AAAI Press, 2007.
- [39] Zhiyi Huang, Zhihao Tang, Xiaowei Wu, and Yuhao Zhang. Online vertex-weighted bipartite matching: Beating $1-1/e$ with random arrivals. *ACM Transactions on Algorithms*, 15, 04 2018.
- [40] Zhiyi Huang and Qiankun Zhang. Online primal dual meets online matching with stochastic rewards: Configuration lp to the rescue. In *Proceedings of the 52nd Annual ACM SIGACT Symposium on Theory of Computing, STOC 2020*, page 1153–1164, New York, NY, USA, 2020. Association for Computing Machinery.
- [41] Chinmay Karande, Aranyak Mehta, and Pushkar Tripathi. Online bipartite matching with unknown distributions. In *Proceedings of the 43rd ACM Symposium on Theory of Computing, STOC 2011, San Jose, CA, USA, 6-8 June 2011*, pages 587–596, 2011.
- [42] Richard M. Karp, Umesh V. Vazirani, and Vijay V. Vazirani. An optimal algorithm for online bipartite matching. In *Proceedings of the 22nd Annual ACM Symposium on Theory of Computing, May 13-17, 1990, Baltimore, Maryland, USA*, pages 352–358, 1990.

- [43] Thomas Kesselheim, Klaus Radke, Andreas Tönnis, and Berthold Vöcking. An optimal online algorithm for weighted bipartite matching and extensions to combinatorial auctions. In Hans L. Bodlaender and Giuseppe F. Italiano, editors, *Algorithms – ESA 2013*, pages 589–600, Berlin, Heidelberg, 2013. Springer Berlin Heidelberg.
- [44] Ulrich Krenzel and Louis Sucheston. Semiamarts and finite values. *Bulletin of the American Mathematical Society*, 83(4):745–747, 1977.
- [45] Thomas Lavastida, Benjamin Moseley, R. Ravi, and Chenyang Xu. Learnable and instance-robust predictions for online matching, flows and load balancing. *CoRR*, abs/2011.11743, 2020.
- [46] Euiwoong Lee and Sahil Singla. Optimal Online Contention Resolution Schemes via Ex-Ante Prophet Inequalities. In Yossi Azar, Hannah Bast, and Grzegorz Herman, editors, *26th Annual European Symposium on Algorithms (ESA 2018)*, volume 112 of *Leibniz International Proceedings in Informatics (LIPIcs)*, pages 57:1–57:14, Dagstuhl, Germany, 2018. Schloss Dagstuhl–Leibniz-Zentrum fuer Informatik.
- [47] Brendan Lucier. An economic view of prophet inequalities. *SIGecom Exch.*, 16(1):24–47, 2017.
- [48] Mohammad Mahdian and Qiqi Yan. Online bipartite matching with random arrivals: An approach based on strongly factor-revealing lps. In *Proceedings of the Forty-third Annual ACM Symposium on Theory of Computing*, STOC '11, pages 597–606, New York, NY, USA, 2011. ACM.
- [49] Vahideh H. Manshadi, Shayan Oveis Gharan, and Amin Saberi. Online stochastic matching: Online actions based on offline statistics. *Math. Oper. Res.*, 37(4):559–573, 2012.
- [50] Aranyak Mehta. Online matching and ad allocation. *Foundations and Trends in Theoretical Computer Science*, 8(4):265–368, 2013.
- [51] Aranyak Mehta and Debmalya Panigrahi. Online matching with stochastic rewards. In *53rd Annual IEEE Symposium on Foundations of Computer Science, FOCS 2012, New Brunswick, NJ, USA, October 20-23, 2012*, pages 728–737. IEEE Computer Society, 2012.
- [52] Manish Purohit, Sreenivas Gollapudi, and Manish Raghavan. Hiring under uncertainty. In Kamalika Chaudhuri and Ruslan Salakhutdinov, editors, *Proceedings of the 36th International Conference on Machine Learning*, volume 97 of *Proceedings of Machine Learning Research*, pages 5181–5189. PMLR, 09–15 Jun 2019.
- [53] D. Seese. Groetschel, m., l. lovasz, a. schrijver: Geometric algorithms and combinatorial optimization. (algorithms and combinatorics. eds.: R. l. graham, b. korte, l. lovasz. vol. 2), springer-verlag 1988, xii, 362 pp., 23 figs., dm 148,-. isbn 3–540–13624-x. *Biometrical Journal*, 32(8):930–930, 1990.
- [54] Danny Segev and Sahil Singla. Efficient approximation schemes for stochastic probing and prophet problems. *CoRR*, abs/2007.13121, 2020.
- [55] Zhihao Gavin Tang, Xiaowei Wu, and Yuhao Zhang. A simple $1-1/e$ approximation for oblivious bipartite matching. *CoRR*, abs/2002.06037, 2020.

- [56] Zhihao Gavin Tang, Xiaowei Wu, and Yuhao Zhang. Towards a better understanding of randomized greedy matching. In *Proceedings of the 52nd Annual ACM SIGACT Symposium on Theory of Computing, STOC 2020, Chicago, IL, USA, June 22-26, 2020*, pages 1097–1110, 2020.
- [57] Jan Vondrák, Chandra Chekuri, and Rico Zenklusen. Submodular function maximization via the multilinear relaxation and contention resolution schemes. In *Proceedings of the Forty-Third Annual ACM Symposium on Theory of Computing, STOC '11*, page 783–792, New York, NY, USA, 2011. Association for Computing Machinery.
- [58] Martin Weitzman. Optimal search for the best alternative. *Econometrica*, 47:641–654, 1979.
- [59] David P. Williamson and David B. Shmoys. *The Design of Approximation Algorithms*. Cambridge University Press, USA, 1st edition, 2011.

A Section 3 Additions

Suppose that we are given an arbitrary stochastic graph $G = (U, V, E)$. Let us restate LP-new for convenience:

$$\text{maximize} \quad \sum_{v \in V} \sum_{e \in \mathcal{C}_v} \text{val}(e) \cdot x_v(e) \quad (\text{LP-new})$$

$$\text{subject to} \quad \sum_{v \in V} \sum_{\substack{e \in \mathcal{C}_v: \\ (u,v) \in e}} p_{u,v} \cdot g(e_{<(u,v)}) \cdot x_v(e) \leq 1 \quad \forall u \in U \quad (\text{A.1})$$

$$\sum_{e \in \mathcal{C}_v} x_v(e) \leq 1 \quad \forall v \in V, \quad (\text{A.2})$$

$$x_v(e) \geq 0 \quad \forall v \in V, e \in \mathcal{C}_v \quad (\text{A.3})$$

Proof of Theorem 3.3. Suppose we are presented a feasible solution $(x_v(e))_{v \in V, e \in \mathcal{C}_v}$ to LP-new. Consider then the following relaxed probing algorithm:

1. $\mathcal{M} \leftarrow \emptyset$.
2. For each $v \in V$, set $e \leftarrow \text{VERTEXPROBE}(v, \partial(v), (x_v(e))_{e \in \mathcal{C}_v})$. If $e \neq \emptyset$, then let $e = (u, v)$ and set $\mathcal{M}(v) = u$.
3. Return \mathcal{M} .

Using Lemma 3.4, it is clear that

$$\mathbb{E}[w(\mathcal{M})] = \sum_{v \in V} \sum_{e \in \mathcal{C}_v} \text{val}(e) \cdot x_v(e).$$

Moreover, each vertex $u \in U$ is matched by \mathcal{M} at most once in expectation, as a consequence of constraint (A.1) of LP-new.

In order to complete the proof, it remains to show that if \mathcal{A} is an optimum relaxed probing algorithm, then there exists a solution to LP-new whose value is equal to $\mathbb{E}[w(\mathcal{A}(G))]$. Observe

that *w.l.o.g.* we may assume that \mathcal{A} satisfies properties (Q_1) and (Q_2) of Lemma 3.2. Now, for each $v \in V$ and $\mathbf{e} = (e_1, \dots, e_k) \in \mathcal{C}_v$ with $k := |\mathbf{e}|$ we can define

$$x_v(\mathbf{e}) := \mathbb{P}[\mathcal{A} \text{ probes the edges } (e_i)_{i=1}^k \text{ in order}].$$

Setting $\mathcal{M} = \mathcal{A}(G)$ for convenience, observe that if $w(\mathcal{M}(v))$ corresponds to the weight of the edge assigned to v (which is 0 if no assignment is made), then

$$\mathbb{E}[w(\mathcal{M}(v))] = \sum_{\mathbf{e} \in \mathcal{C}_v} \text{val}(\mathbf{e}) \cdot x_v(\mathbf{e}),$$

by properties (Q_1) and (Q_2) . Similarly, for each $u \in U$,

$$\sum_{v \in V} \sum_{\substack{\mathbf{e} \in \mathcal{C}_v: \\ (u,v) \in \mathbf{e}}} p_{u,v} \cdot g(\mathbf{e}_{<(u,v)}) \cdot x_v(\mathbf{e}) \leq 1$$

by once again using properties (Q_2) and (Q_1) . The proof is therefore complete. \square

B Section 4 Additions

Proof of Theorem 4.1. Suppose that $(H_{\text{typ}}, (\mathcal{D}_t)_{t=1}^n)$ is a known i.d. instance, where $H_{\text{typ}} = (U, B, F)$. Recall that \mathcal{C}_b corresponds to the online probing constraint of each type node $b \in B$. For convenience, we denote $\mathcal{I} := \sqcup_{b \in B} \mathcal{C}_b$. We can then define the following collection of random variables, denoted $(X_t(\mathbf{e}))_{t \in [n], \mathbf{e} \in \mathcal{I}}$, based on the following randomized procedure:

- Draw the instantiated graph $G \sim (H_{\text{typ}}, (\mathcal{D}_t)_{t=1}^n)$, whose vertex arrivals we denote by v_1, \dots, v_n .
- Compute an optimum solution of LP-new for G , which we denote by $(x_{v_t}(\mathbf{e}))_{t \in [n], \mathbf{e} \in \mathcal{C}_{v_t}}$.
- For each $t = 1, \dots, n$ and $\mathbf{e} \in \mathcal{I}$, set $X_t(\mathbf{e}) = x_{v_t}(\mathbf{e})$ if $\mathbf{e} \in \mathcal{C}_{v_t}$, otherwise set $X_t(\mathbf{e}) = 0$.

Observe then that since by definition $(X_{v_t}(\mathbf{e}))_{t \in [n], \mathbf{e} \in \mathcal{C}_{v_t}}$ is a feasible solution to LP-new for G , it holds that for each $t = 1, \dots, n$

$$\sum_{\mathbf{e} \in \mathcal{I}} X_t(\mathbf{e}) = 1, \tag{B.1}$$

and

$$\sum_{t \in [n], b \in B} \sum_{\substack{\mathbf{e} \in \mathcal{I}: \\ (u,b) \in \mathbf{e}}} p_{u,b} \cdot g(\mathbf{e}_{<(u,b)}) \cdot X_t(\mathbf{e}) \leq 1, \tag{B.2}$$

for each $u \in U$. Moreover, $(X_t(\mathbf{e}))_{t \in [n], \mathbf{e} \in \mathcal{C}_{v_t}}$ is a optimum solution to LP-new for G , so Theorem 3.1 implies that

$$\text{OPT}(G) \leq \text{LPOPT}_{\text{new}}(G) = \sum_{t=1}^n \sum_{\mathbf{e} \in \mathcal{I}} \text{val}(\mathbf{e}) \cdot X_t(\mathbf{e}). \tag{B.3}$$

In order to make use of these inequalities in the context of the type graph H_{typ} , let us first fix a type node $b \in B$ and a string $\mathbf{e} \in \mathcal{C}_b$. For each $t \in [n]$, we can then define

$$x_t(\mathbf{e} \parallel b) := \mathbb{E}[X_t(\mathbf{e}) \cdot \mathbf{1}_{[v_t=b]}], \tag{B.4}$$

where the randomness is over the generation of G . Observe that by definition of the $(X_t(\mathbf{e}))_{t \in [n], \mathbf{e} \in \mathcal{I}}$ values,

$$x_t(\mathbf{e} \parallel b) = 0,$$

provided $\mathbf{e} \notin \mathcal{C}_b$.

We claim that $(x_t(\mathbf{e} \parallel b))_{b \in B, t \in [n], \mathbf{e} \in \mathcal{C}_b}$ is a feasible solution to LP-new-id. To see this, first observe that if we multiply (B.1) by the indicator random variable $\mathbf{1}_{[v_t=b]}$, then we get that

$$\sum_{\mathbf{e} \in \mathcal{I}} X_t(\mathbf{e}) \cdot \mathbf{1}_{[v_t=b]} = \mathbf{1}_{[v_t=b]}.$$

As a result, if we take expectation over this inequality,

$$\begin{aligned} \sum_{\mathbf{e} \in \mathcal{I}} x_t(\mathbf{e} \parallel b) &= \sum_{\mathbf{e} \in \mathcal{I}} \mathbb{E}[X_t(\mathbf{e}) \cdot \mathbf{1}_{[v_t=b]}] \\ &= \mathbb{P}[v_t = b] \\ &=: r_t(b), \end{aligned}$$

for each $b \in B$ and $t \in [n]$. Let us now fix $u \in U$. Observe since $X_t(\mathbf{e}) \cdot \mathbf{1}_{[v_t=b]} = X_t(\mathbf{e})$ for each $\mathbf{e} \in \mathcal{C}_b$, (B.2) ensures that

$$\sum_{t \in [n], b \in B} \sum_{\substack{\mathbf{e} \in \mathcal{C}_b: \\ (u,b) \in \mathbf{e}}} p_{u,b} \cdot g(\mathbf{e}_{<(u,b)}) \cdot X_t(\mathbf{e}) \cdot \mathbf{1}_{[v_t=b]} = \sum_{t \in [n], b \in B} \sum_{\substack{\mathbf{e} \in \mathcal{C}_b: \\ (u,b) \in \mathbf{e}}} p_{u,b} \cdot g(\mathbf{e}_{<(u,b)}) \cdot X_t(\mathbf{e}) \leq 1 \quad (\text{B.5})$$

Thus, after taking expectation over (B.5),

$$\sum_{t \in [n], b \in B} \sum_{\substack{\mathbf{e} \in \mathcal{C}_b: \\ (u,b) \in \mathbf{e}}} p_{u,b} \cdot g(\mathbf{e}_{<(u,b)}) \cdot x_t(\mathbf{e} \parallel b) \leq 1,$$

for each $u \in U$.

Since $(x_t(\mathbf{e} \parallel b))_{t \in [n], b \in B, \mathbf{e} \in \mathcal{C}_b}$ satisfies these inequalities, and the variables are clearly all non-negative, it follows that $(x_t(\mathbf{e} \parallel b))_{t \in [n], b \in B, \mathbf{e} \in \mathcal{C}_b}$ is a feasible solution to LP-new-id.

In order to complete the proof, let us express the right-hand side of (B.3) as in (B.5) and take expectations. We then get that

$$\mathbb{E}[\text{OPT}(G)] \leq \sum_{b \in B, t \in [n]} \sum_{\mathbf{e} \in \mathcal{I}} \text{val}(\mathbf{e}) \cdot x_t(\mathbf{e} \parallel b).$$

Now, $\text{OPT}(H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n) = \mathbb{E}[\text{OPT}(G)]$ by definition, so since $(x_t(\mathbf{e} \parallel b))_{b \in B, t \in [n], \mathbf{e} \in \mathcal{C}_b}$ is feasible, it holds that

$$\text{OPT}(H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n) \leq \text{LPOPT}_{\text{new-id}}(H_{\text{typ}}, (\mathcal{D}_i)_{i=1}^n),$$

thus completing the proof. □

C Extended Related Works

Our results pertain to the online stochastic matching problem which (loosely speaking) is online bipartite matching where edges are associated with their probabilities of existence. There is a substantial body of research pertaining to the “classical” (i.e. non stochastic) online bipartite model in the fully adversarial online model, the random order model, and the i.i.d. input model. The ever growing interest in various online bipartite matching problems is a reflection of the importance of online advertising but there are many other natural applications. The literature concerning competitive analysis¹⁰ of online bipartite matching is too extensive to do justice to many important papers. We refer the reader to the excellent 2013 survey by Mehta [50] with emphasis on online variants relating to ad-allocation. Given the continuing interest in ad-allocation, the survey is not current but does describe the basic results.

The seminal result for unweighted online bipartite matching is due to Karp, Vazirani, and Vazirani [42]. They gave the randomized Ranking algorithm that achieves competitive ratio $1 - 1/e$ in the adversarial online setting which they show is the best possible ratio for any randomized algorithm. There have been many proofs of this seminal result, such as the primal-dual approach due to Devanur et al. [25]. Any greedy algorithm (i.e., one that always makes a match when possible) has a 0.5 ratio, and this is the best possible a deterministic algorithm can attain. The Ranking algorithm can also be viewed as a deterministic algorithm in the ROM input model. In the ROM model, Madhian and Yan [48] show that the randomized Ranking algorithm achieves competitive ratio 0.696. For the case of weighted offline vertices and adversarial input sequences, Aggarwal et al. [5] were able to achieve a randomized $1 - 1/e$ competitive ratio by their Perturbed Ranking algorithm. Huang et al. [39] show that the Perturbed Ranking algorithm obtains a .6534 competitive ratio in the ROM input model.

Feldman et al. [30] introduced online bipartite matching in the i.i.d. model in which each online vertex is independently and identically generated from some known distribution. In this model, they were able to beat the $1 - 1/e$ inapproximation for bipartite matching that applies to the fully adversarial online model. The i.i.d. online bipartite model has been studied for the unweighted and edge weighted models. The most recent competitive ratios for integral arrival rates are due to Brubach et al. [16] in which they derive a 0.7299 ratio for the (offline) vertex weighted case and a 0.705 ratio for edge weighted graphs. Karande et al. [41] show that any competitive ratio for the ROM model applies to the unknown (and therefore known) i.i.d. models. It follows that any inapproximation for the known i.i.d. model applies to the ROM model. Kesselheim et al. [43] extend the classical secretary result and established the optimal $1/e$ ROM ratio for bipartite matching with edge weights.

An early example of stochastic probing without commitment is the Pandora’s box problem attributed to Weitzman [58]. In Weitzman’s Pandora’s box problem, a set of boxes is given, where each box contains a stochastic value from a known distribution and a cost for opening (i.e., probing) the box. The algorithm has the option at any time of accepting the value of any opened box and pays the total cost of all opened boxes. This is an offline probing problem in that boxes can be opened in any order. An online version of the Pandora’s box problem has recently been studied in

¹⁰Initially, competitive analysis referred to the relative performance (i.e., the competitive ratio) of an online algorithm as compared to an optimal solution (in the worst case over all input sequences determined adversarially). We extend the meaning of the competitive ratio to also refer to input sequences generated in the ROM model as well as sequences generated i.i.d. from a known or unknown distribution; that is, whenever the algorithm has no control over the order of input arrivals.

Esfandiari et al. [28]. Stochastic probing with commitment has been studied for various packing problems, most notably for the knapsack problem, as studied in Dean et al. [23, 24]. In the stochastic knapsack setting, the stochastic inputs are items whose values are known but whose sizes are stochastic and not known until the algorithm probes the item. As soon as the knapsack capacity is exceeded by a probed item, the algorithm terminates. Dean et al. also introduced the offline issue of measuring the benefit of adaptively choosing probes versus having a fixed order of probes.

Turning back to matching problems, Chen et al. [20] introduced the stochastic matching problem assuming a known stochastic graph and algorithms that can probe any edge in any order. They obtained a 4-approximation¹¹ greedy algorithm in the unweighted case for arbitrary patience values. They conjectured that their greedy algorithm was a 2-approximation. Subsequently, Adamczyk [1] confirmed that the greedy algorithm is a 2-approximation for the unweighted problem and that this approximation is tight. Bansal et al. [9] established a 4-approximation for the edge weighted case with arbitrary patience and a 3-approximation for the special case of bipartite graphs. Adamczyk et al. [3] improved the Bansal et al. bounds providing an approximation algorithm with a ratio of 2.845 for bipartite graphs and an algorithm with a ratio of 3.709 for general graphs. Baveja et al. [10] recently improved the analysis of the original algorithm of Bansal et al., yielding an approximation ratio of 3.224 for general graphs.

Of particular importance to our paper is the known stochastic matching framework with ROM arrivals, as defined precisely in Section 2. Gamlath et al. [32] presented a probing algorithm which is a $1 - \frac{1}{e}$ -approximation for the bipartite case in the *full patience setting*; that is, when there are no patience restrictions for nodes on either side of the bipartition. The full patience setting is closely related to the bipartite matching algorithm studied by Ehsani et al. [27], which they prove is a $1 - \frac{1}{e}$ -approximation as a corollary of their work in the more general *combinatorial auctions prophet secretary problem*. While not explicitly stated in [27], their bipartite matching algorithm can be interpreted as an adaptive probing algorithm in the known stochastic matching framework with ROM arrivals, attaining the same $1 - \frac{1}{e}$ non-adaptive approximation ratio as Gamlath et al.. Very recently, Tang et al. [55] provided an alternative algorithm also attaining the same approximation ratio of $1 - \frac{1}{e}$ in the more general *oblivious bipartite matching* setting, however their algorithm does not execute in an online fashion, and so is incomparable. See also Tang et al. [56] for an online greedy algorithm achieving a 0.501 ratio for a known stochastic graph with edge weights.

Mehta and Panigrahi [51] adapted the stochastic matching problem to the online setting problem with unit patience where the stochastic graph is not known to the algorithm. They specifically considered the unweighted case for unit patience (for the online nodes) and uniform edge probabilities (i.e., for every edge e , $p_e = p$ for some fixed probability p). They showed that every greedy algorithm has competitive ratio $\frac{1}{2}$. In the same online setting, they provided a greedy algorithm that achieves competitive ratio $\frac{1}{2}(1 + (1 - p)^{2/p})$ which limits to $\frac{1}{2}(1 + e^{-2}) \approx 0.567$ as $p \rightarrow 0$. They also show that against a “standard linear programming (LP)” benchmark, that the best possible ratio is $0.621 < 1 - \frac{1}{e}$. However, this does not preclude a $1 - \frac{1}{e}$ competitive ratio for a stricter LP bound on an optimal stochastic probing algorithm. Preceding the Mehta and Panigrahi work is a result in Bansal et al. [9] where they consider a known stochastic (type) graph with a distribution on the online nodes. This can be called the stochastic matching problem with known i.i.d. inputs.

¹¹Unfortunately, approximation and competitive bounds for maximization problems are sometimes represented both as ratios > 1 and as fractions < 1 . We shall report these ratios as stated in the relevant papers. Our results will be stated as fractions.

Bansal et al. achieve a 7.92 competitive ratio (or approximately, 0.13 as a fraction) in this stochastic i.i.d. model. This was improved to 0.24 by Adamczyk [3] and most recently, by Brubach et al. [17] where they obtain a 0.46 competitive ratio and a $1 - \frac{1}{e}$ inapproximation against a standard LP.

Returning to the unknown stochastic graph setting, there are recent independent papers by Goyal and Udwani [34] and Brubach et al. [15]. Goyal and Udwani consider the vertex weighted unit patience problem and establish a (best possible) $1 - \frac{1}{e}$ competitive ratio against an LP that acts as an upper bound on an optimum offline probing algorithm (the adaptive benchmark) under the assumption that the edge probabilities are decomposable (i.e., $p_{u,v} = p_u \cdot p_v$) and a .596 competitive ratio for vanishingly small edge probabilities. In a recent paper, Huang and Zhang [40] provide a randomized algorithm for unit patience and offline vertex weights in the online stochastic matching framework. In the limit as edge probabilities decrease, their algorithm achieves a .572 competitive ratio. Brubach et al. use and motivate the “ideal stochastic benchmark” (for arbitrary patience) and an LP relaxation for that ideal benchmark. They establish a best possible deterministic $\frac{1}{2}$ competitive ratio against their LP for the vertex weighted online stochastic matching problem. In [13], the authors generalized the patience setting of Brubach et al. to the case of a downward-closed set system on an online node’s allowable sequences of edge probes, thereby attaining the same $1/2$ competitive ratio. We also analysed the same algorithm in the vertex-weighted ROM setting, achieving a competitive ratio of $1 - 1/e$ for a number of settings. Finally, we showed that an (optimal) asymptotic competitive ratio of $1/e$ holds for downward-closed set systems in the edge weighted ROM setting.