Separate Compilation and Makefiles

Reading:

- King, chapter 15
- on cdf: file ~dianeh/228/C/Howto.make
- on cdf: example code in ~dianeh/228/C/sepcomp

Separate Compilation

Say we have a program broken into two files (prog.c and sub.c), and each begins with

```
#include "incl.h"
```

We can compile the program in one line:

```
eddie% gcc prog.c sub.c
```

Or we can compile the parts separately:

```
eddie% gcc -c prog.c
eddie% gcc -c sub.c
eddie% gcc prog.o sub.o
```


There's not much point to doing it separately, *except* when only parts of the program need to be recompiled.

E.g., say I've changed sub.c and nothing else. I don't need to recompile prog.c.

```
eddie% gcc -c sub.c
eddie% gcc prog.o sub.o
```

This becomes really valuable when we have many files. But then it becomes hard to keep track of what needs to be recompiled.

This is what makefiles help us with.

Makefiles

General format: A makefile consists of pairs of lines as follows:

label: *item1* ... *itemk*
command

Meaning: To ensure that *label* is up to date:

1. Recursively ensure that *item1* ... *itemk* are themselves up to date.
2. If file *label* is older than any of the files *item1* ... *itemk*, then file *label* is out of date. Execute *command* to bring it up to date.

Example:

```
pgm: prog.o sub.o
        gcc -o pgm prog.o sub.o
prog.o: incl.h prog.c
        gcc -c prog.c
sub.o: incl.h sub.c
        gcc -c sub.c
```

Running make

```
Script started on Sun Jan 19 17:13:22 1997
eddie% ls
README          makefile        prog.c          typescript
incl.h          pgm             sub.c

eddie% make
gcc -c prog.c
gcc -c sub.c
gcc -o pgm prog.o sub.o

eddie% pgm
hi
hi
hi
there
there
there

eddie% vi prog.c
eddie% ls -l
total 15
-rw-r--r--   1 dianeh        364 Sep 13  1994 README
-rw-r--r--   1 dianeh        406 Sep 13  1994 incl.h
-rw-r--r--   1 dianeh        477 Sep 13  1994 makefile
-rwx------   1 dianeh       5844 Jan 19 17:13 pgm
-rw-r--r--   1 dianeh       1247 Jan 19 17:14 prog.c
-rw-------   1 dianeh       1416 Jan 19 17:13 prog.o
-rw-r--r--   1 dianeh        774 Jan 19 16:34 sub.c
-rw-------   1 dianeh        844 Jan 19 17:13 sub.o
-rw-------   1 dianeh          0 Jan 19 17:13 typescript
```



```
eddie% make
gcc -c prog.c
gcc -o pgm prog.o sub.o

eddie% make
'pgm' is up to date.

eddie% vi incl.h

eddie% make
gcc -c prog.c
gcc -c sub.c
gcc -o pgm prog.o sub.o

eddie% make
'pgm' is up to date.

eddie% make sub.c
'sub.c' is up to date.
```


Makefile for holder program

```
myprog: holderDriver.o thing.o
        g++ -o myprog holderDriver.o thing.o
holderDriver.o: holder.h holderImp.h holderDriver.
        g++ -c holderDriver.cxx
thing.o: thing.h thing.cxx
        g++ -c thing.cxx
```