

Non-Functional Requirements (NFRs)

Define global constraints on a software system, such as development costs, operational costs, performance, reliability, maintainability, portability, robustness etc.
Should not be confused with functional requirements, which impose requirements on the function of a system
Are generally stated informally, are often contradictory, difficult to enforce during development and to evaluate for the customer prior to delivery

How do we measure them?
How do we take them into account during development?

Types of NFRs

Interface requirements -- describe how the information system is to interface with its environment, users and other systems; include user interfaces and their qualities (e.g., "user-friendliness")

Performance requirements -- describe performance constraints involving

time/space bounds, such as workloads, response time, throughput and available storage space, e.g., "system must handle 1,000 transactions per second"),

reliability involving the availability of components and integrity of information maintained and supplied to the system, e.g., "system must have less than 1hr downtime per three months"

security, such as permissible information flows

survivability, such as system will survive fire, natural catastrophes

Operating requirements -- include physical constraints (size, weight), personnel availability, skill level considerations, accessibility for maintenance, environmental conditions...


Types of NFRs


Lifecycle requirements -- can be classified under two subcategories:


Quality of the design such as maintenability, enhanceability, portability expected market or product lifespan,...(these don't affect initial system but may lead to increased maintenance costs or early obsolescence)


Limits on development, other software lifecycle phases, such as development time limitations, resource availability, methodological standards etc.


Economic requirements -- immediate and/or long-term costs















Reliability

Reliability

Reliability of a software system is defined as the ability of the system to behave consistently in a user-acceptable manner when operating within the environment for which it was intended.

Reliability can be defined in terms of a percentage (say, 99.999%) may have different meaning for different system:

- for a telephone, it might mean that the telephone should break down, on average, 1hr per year
- for a patient monitoring system, it may mean that the system may fail for up to 1hr/year, but in those cases doctors/nurses should be alerted of the failure



Reliability: Counting Bugs

Sometimes reliability requirements take the form: "The software shall have no more than X bugs per thousand lines of code"

"But how do we measure bugs at delivery time?

Use bebugging: just before testing, a number of seeded bugs are introduced to the software system, then testing is done and bugs are uncovered (seeded or otherwise)

Number of bugs = # of seeded bugs × # of detected bugs in system # of detected seeded bugs

The theoretical underpinnings of the approach are founded in Monte Carlo statistical analysis techniques for random events.

"BUT, not all bugs are equally important!

Reliability Metrics

Reliability requirements have to be tied to the loss incurred by software system failure eq. destruction of manking destruction of a city.

Reliability requirements have to be tied to the loss incurred by software system failure, eg., destruction of mankind, destruction of a city, destruction of some people, injury to some people, major financial loss, major embarrassment, minor financial loss. Different metrics are more appropriate in different situations:

- Probability of failure on demand. This measures the likelihood that the system will behave in an unexpected way when some demand is made of it. This is most relevant to safety-critical systems.
- Rate of Failure Occurrence (ROCOF). This measures the frequency of unexpected behaviour. For example, ROCOF=2/100 means that 2 failures are likely to occur within every 100 time units.
- Mean Time to Failure (MTTF). Discussed earlier.
- Availability. Measures the likelihood that the system will be available for use. This is a good measure for applications such as telecommunications, where the repair/restart time is significant and the loss of service is important.

12 John Mylopoulos Non-Functional

Failure Classes ■ One way to qualify reliability requirements is to characterize system √ Transient -- occur only with certain inputs ✓ Permanent -- occur with all inputs ✓ Recoverable -- system can recover with no human intervention ✓ Unrecoverable -- operator intervention needed for recovery; ✓ Non-corrupting -- failure doesn't corrupt data
 ✓ Corrupting -- failure corrupts data For an Automated Money Machine (AMM) example Failure class Example Reliability Can't read card magnetic strip 1/100K transactions Permanent Transient, non-corr Failure to read mag strip on one card 1/10K Transient, corr Cards issued by foreign bank corrupt DB 1/20M Recoverable, corr Loss of user input 1/50K Recoverable, corr Loss of mag strip data 1/5K

Reliability in Perspective

The best that can be done in terms of reliability requirements is something like:

"...No more than X bugs per 10KLOC may be detected during integration and testing; no more than Y bugs per 10KLOC may remain in the system after delivery, as calculated by the Monte Carlo seeding technique of appendix Z; the system must be 100% operation..."

Reliability requirements have to be tied to the loss incurred by software system failure, eg., destruction of mankind, destruction of a city, destruction of some people, injury to some people, major financial loss, major embarrassment, minor financial loss [Musa87]


| Software efficiency refers to the level at which a software system uses scarce computational resources, such as CPU cycles, memory, disk space, buffers and communications channels
| Efficiency can be characterized along a number of dimensions: Capacity -- maximum number of users/terminals/transactions/... the system can handle without performance degradation


"...The system shall handle up to and including 20 simultaneous terminals and users performing any activities without degradation of service below that defined in section X.Y.Z.; other systems may make short requests, at a maximum rate of 50/hr and long requests at the rate of 1/hr..."


Degradation of service -- what happens when a system with capacity X widgets per time-unit receives X+1 widgets? We don't want the system to simply crash! Rather, we may want to stipulate that the system should handle the load, perhaps with degraded performance


Efficiency: Timing Requirements


Let stimulus refer to an action performed by the user/environment, response is a system-generated action.
Four types of timing requirements [Dasarathy85]:
Stimulus-response -- e.g., "...the system will generate a dial tone within 2secs from the time the phone is picked up...", or "...the system will arm the alarm no sooner than 1min after the 'alarm on' button is pressed..."
Response-response -- e.g., "...the system will commit an ATM transaction no later than 1min after it is completed..."
Stimulus-stimulus -- e.g., "...the user will type her password within 15secs from typing her login name..."
Response-stimulus -- e.g., "...user must dial phone number within 1min from getting dial tone..."














Other Non-Functional Requirements

- Human factors -- building a user-friendly system requires expertise that most of us do not have; [Mantei88] describes cost-benefit tradeoffs of human factors.
- Testability **Testability** (closely related to **Understandability** and **Modifiability**) -- Usually defined in terms of **cohesion** and coupling

cohesion -- measures how well the components of a module fit

coupling -- measures the strength of interconnections between program units

Requirements for testability can be given in terms of a minimum for cohesion for any one module and a minimally acceptable average for the whole system. Maximum coupling standards may also be set for any two modules or, a maximally acceptable standard might be set for the whole system

The Automated Money Machine (AMM)

- Consider the problem of building a software system which drives an Automated Money Machine (aka cash machine or bank machine.)

 The next the control of the control of
- The system takes as input a user transaction (e.g., deposit. withdraw, check balance,...) and sends the information to the central bank account system, receives acknowledgement that the transaction has been processed, and responds to the user (e.g., acknowledge deposit, dispense cash, give account

Example NFRs for the AMM

■ Maintainability Requirements

The AMM System shall exhibit a Mean Time To Repair (MTTR) of not more than 2 hours. The MTTR is defined as the sum of the time required for fault isolation, correction, and restoration to service for each failure divided by the number of failures.

Availability Requirements

The AMM System shall exhibit an availability of not less than 95 percent

Reliability Requirements

The AMM System shall exhibit a system Mean Time Between Failure (MTBF) of not less than 96 hours. MTBF is defined as the quotient of the total number of operating hours divided by the total number of

■ Expandability Requirements

The AMM System shall be designed in such a manner as to allow for future addition of 4 user buttons and 4 additional banking services

Security Requirements

Access to account transactions shall be restricted to holders of valid banking cards and personal identification number

Cash withdrawals shall not exceed 500 dollars. Cash deposits shall not exceed \$2,000.

The AMM System shall shutdown upon detection of any device error or fatal software error.

error or ratal sonware error.

The AMM System shall shutdown upon loss of the link to the People's Bank Computer System.

The AMM System shall record all transactions in its daily log.

Developer will be responsible for ensuring the security of the physical cabinet and hardware devices.

People's Bank will be responsible for the security of the account information contained on the People's Bank Computer System.

More Examples

■ Restart Requirements

The AMM System shall perform an automatic restart in the event of a fatal software error, to be completed within 5 minutes

The AMM System shall perform a cold start within 15 minutes. Cold start is defined as the process whereby the system is installed, configured, and started. Each site shall have specific configuration files which contain site specific parameters, such as site name and site address. The cold start procedure shall initialize the system from the site configuration file.

■ Backup Requirements

The AMM System has no backup requirements as the banker account information is stored on the People's Bank Computer System

The AMM System shall terminate the current transaction and shutdown in the event of a fatal device error, repeatable fatal software error, or network failure. The AMM System will not be operational again until the maintenance crew has investigated the failure

Platform Requirements

The AMM System shall operate with not more than 4 MB RAM. 1 MB RAM shall be reserved for local data structures. 3 MB RAM shall be reserved for the operating system.

The AMM System shall operate with not more than 80 MB hard disk space. 3MB hard disk space is reserved for banking service files and

The AMM System will execute under the Microsoft Windows Version 3.0 or later operating system. There are no Windows requirements for the human-machine interface

The AMM System will operate on a 80386 processor or better.

Performance Requirements

The AMM System will be allocated 1.0 MB main memory to accommodate local data structures.

The AMM System will be allocated 3 MB hard disk space to accommodate any AMM banking files or configuration files.

The AMM System will respond to all banker requests in less than 10 seconds. This time shall be allocated as follows:

Banking Applications Subsystem: 0.5 seconds

Network Manager Subsystem: 0.5 seconds

People's Bank Computer System / Network: 9 seconds

Timing analysis will be performed through out the design and implementation of the subsystem to ensure that timing allocations are not being exceeded.

Additional Readings

I [Dasarathy85] Dasarathy, B., "Timing Constraints of Real-Time Systems: Constructs for Expressing Them, Methods for Evaluating Them", IEEE Transactions on Software Engineering 11(1), January 1985.

I [Mantei88] Mantei, M. and Teorey, T., "Cost-Benefit for Incorporating Human Factors in the Software Lifecycle", Communications of the ACM 31(4), 1988.

I [Musa87] Musa, J. et al Software Reliability, McGraw-Hill, 1987.

I [Thayer90] Thayer, R. and Dorfman, M., System and Software Requirements Engineering, IEEE Computer Society Press, 1990.

I [Roman85] Roman, G-C., "A Taxonomy of Current Issues in Requirements Engineering", IEEE Computer, April 1985.