CSC148 *Intro. to Computer Science*

Lecture 3: *designing classes, special methods, composition, inheritance, Stack, Sack*

Amir H. Chinaei, Summer 2016

Office Hours: R 10-12 BA4222

ahchinaei@cs.toronto.edu
http://www.cs.toronto.edu/~ahchinaei/

Course page:
http://www.cs.toronto.edu/~ahchinaei/teaching/20165/csc148/

Recall

- Use all resources available to you
  - Before it becomes too late!
- What resources?
  - Office Hours: R 10-12 BA4222
  - The course web page and its many hyperlinks!
  - The CS Help Centre
  - The course forum
  - The TAs mailing list: csc148ta @ cdf.toronto.edu
  - Email ahchinaei @ cs.torotno.edu
- Note:
  - Today, May 26, the Bahen building is among some other buildings that will be closed from ~9pm to May 27, due to a power turn-off. It will NOT affect our lecture though.

Review

- So far
  - Recap of basic Python (see ramp_up slides)
  - Introduction to OO D/P
  - Special methods
  - Manage attributes
  - Introduction to composition and inheritance
- Today
  - Managing attributes
  - More on composition and inheritance
  - Inheriting, extending, and overriding
  - Stack and Sack ADTs

Key terms

- *Class: (abstract/advanced/compound) data type*
  - It models a thing or concept (let's call it object), based on its common (or important) attributes and actions in a specific project
  - In other words, it bundles together attributes and methods that are relevant to each instance of those objects
- In OO world, objects are often **active** agents
  - In other words, actions are invoked on objects
  - e.g. you invoke an action on your phone to dial a number
  - e.g. you invoke an action on your alarm to wake you up
  - e.g. you invoke an action on your fridge to get you ice

OOP Features

- Encapsulation
  - Hiding instance attributes from clients
    - by making them **private**
  - Pythonic way of thinking of attributes is
    - to leave them **public**
  - However, if you wish, you can make them **kind of private**
    - *and use getters, setters, and properties to access them*
    - *This is useful when you think their implementation can change in future—without changing their interface*

Encapsulation (by getters, setters, properties)

- Recall the Rational class:
  - We had two public attributes there:
    - num and denom
  - Let's see how we can make them kind of private

```
class Rational:
    """
    A rational number

    Public Attributes:
    ==================
    :type num: int
       the numerator of the rational number
    :type denom: int
       the denominator of the rational number
    """
```

Encapsulation (by getters, setters, properties)

- Recall the Rational class:
  - We had two public attributes there:
    - num and denom
  - Let's see how we can make them kind of private

```
class Rational:
    """
    A rational number
    """
    # Public Attributes:
    # ==================
    # :type num: int
    #   the numerator of the rational number
    # :type denom: int
    #   the denominator of the rational number
```


Getter to manage _num

```
def _get_num(self):
    # """
    # Return numerator num.
    #
    # :rtype: int
    #
    # >>> Rational(3, 4)._get_num()
    # 3
    # """
    return self._num
```


Setter to manage _num

```
def _set_num(self, num):
    # """
    # Set numerator of Rational self to num.
    #
    # :param num: the numerator of Rational self
    # :type num: int
    # :rtype: None
    # """
    self._num = int(num)

num = property(_get_num, _set_num)
```


Getter to manage _denom

```
def _get_denom(self):
    # """
    # Return denominator of Rational self.
    #
    # :rtype: int
    #
    # >>> Rational(3, 4)._get_denom()
    # 4
    # """
    return self._denom
```


Setter to manage _denom

```
def _set_denom(self, denom):
    # """
    # Set denominator of Rational self to denom.
    #
    # :param denom: the denominator of Rational self
    # :type denom: int
    # :rtype: None
    # """
    if denom == 0:
        raise Exception("Zero denominator!")
    else:
        self._denom = int(denom)

denom = property(_get_denom, _set_denom)
```


OOP Features

- Encapsulation
  - So, *num* and *denom* are now managed attributes,
    - kind of private!
    - clients should not use them directly
  - If you want to make an attribute *read-only*, do not provide the setter for it.
  - If you want to make an attribute really private, use __ as its name prefix, but not as its name postfix

Let's move on to other OOP Features

OOP Features

- Composition and Inheritance
  - A rectangle has some vertices (points)
  - A triangle has some vertices (points)
  - A triangle is a shape
  - A rectangle is a shape
- has_a vs is_a relationship
- a shape has a perimeter
  - A rectangle can inherit the perimeter from a shape
  - A triangle too
- a shape has an area
  - Can be area of a rectangle (or triangle) easily abstracted to the shape level?

More specific example

- Assume you are reading a project specification which is about defining, drawing, and animating some geometrical shapes …
- For now, assume it concerns only two shapes: **squares** and **right angled triangles**.

Square

Squares have four vertices (corners), have a perimeter, an area, can move themselves by adding an offset point to each corner, and can draw themselves.

Right angled triangle

Right angled triangles have three vertices (corners), have a perimeter, an area, can move themselves by adding an offset point to each corner, and can draw themselves.

Abstraction

- Obviously, we need to define two classes
  - Square and RightAngledTriangle

  before rushing to do so, let's rethink …
- Squares and RightAngledTriangles have something in common:
  - composed of some corners (points)
  - also, some common features (actions) are applicable to them: *perimeter*, *area*, *move*, *draw*
- That can be abstracted to a more general class, let's call it Shape

Shape class

- Develop the common features into an abstract class Shape
  - Points, perimeter, area
- Remember to follow the *class design recipe*
  - Read the project specification carefully
  - Define the class with a short description and some client code examples to show how to use it …
  - Develop API of all methods including the special ones, __eq__, __str__, …
    - Remember to follow the *function design recipe*, just don't implement it until your API is (almost) complete
  - Then, implement it

developing Shape API

```
from point import Point
from turtle import Turtle

class Shape:
    """
    A Shape shape that can draw itself, move, and
    report area and perimeter.

    === Attributes ===
    :type corners: list[Point]
        corners that define this Shape
    :type area: float
        area of this Shape
    :type perimeter: float
        perimeter of this Shape
    """
if __name__ == "__main__":
    import doctest
    doctest.testmod()
    s = Shape([Point(0, 0)])
```


developing Shape API

```
…

class Shape:
    """
    …
    """

    def __init__(self, corners):
        """
        Create a new Shape self with defined by its
        corners.

        :param corners: corners that define shape self
        :type corners: list [Points]
        :rtype: None
        """
        pass
```


API, then, implementation

- continue with API of
  - __eq__(self, other)
  - __str__(self)
  - _set_perimeter(self)
  - _get_perimeter(self)
  - _set_area(self)
  - _get_area(self)
  - move_by(self, offset_point)
  - draw(self)
- then, start implementing it; however …

Shape implementation

- So far, we implemented the common features of Square and RightAngledTriangle
- However, how about differences?
  - For instance, the area of a Square is calculated differently than that of a RightAngledTriangle
- In class Shape, do not implement _set_area; instead, put a place-holder


```
def _set_area(self):
    # """
    # Set the area of Shape self to the Shape of
    # its sides.
    #
    # :rtype: None
    # """
    # impossible area to satisfy PyCharm...
    self._area = -1.0
    raise NotImplementedError("Set area in subclass!!!")

def _get_area(self):
    # """
    # Return the area of Shape self.
    #
    # :rtype: float
    #
    # >>> Shape([Point(1, 1), Point(2, 1), Point(2, 2), Point(1, 2)]).area
    # 1.0
    # """
    return self._area

# area is immutable --- no setter method in property
area = property(_get_area)
```


Inheritance

- So, we developed a super class that is abstract
  - it defines the common features of subclasses
  - but it's missing some features that must be defined in subclasses
- Square and RightAngledTriangle are two subclass examples of Shape from which inheriting the identical features

  class Square(Shape): …
  class RightAngledTriangle(Shape): …

- Develop Square and RightAngledTriangle
  - Remember to follow the recipes

developing Square

```
from shape import Shape

class Square(Shape):
    """
    A square Shape.
    """

if __name__ == '__main__':
    import doctest
    doctest.testmod()
    s = Square([Point(0, 0)])
```


developing Square

```
…
    def __init__(self, corners):
        """
        Create Square self with vertices corners.

        Assume all sides are equal and corners are square.

        Extended from Shape.

        :param corners: corners that define this Square
        :type corners: list[Point]

        >>> s = Square([Point(0, 0), Point(1, 0), Point(1, 1), Point(0, 1)])
        """
        Shape.__init__(self, corners)
```


developing Square

```
…
    def _set_area(self):
        """
        Set Square self's area.

        Overrides Shape._set_area

        :rtype: float

        >>> s = Square([Point(0,0), Point(10,0),
                        Point(10,10), Point(0,10)])
        >>> s.area
        100.0
        """
        self._area = self.corners[-1].distance(self.corners[0])**2
```


Discussion summary

- A Shape is a composition of some Points
- Square and RightAngledTriangle inherit from Shape
  - They inherit the perimeter, area, move and draw from Shape
  - They (slightly) extend the constructor of Shape
  - They override the _set_area of Shape

  ==========
- The client code can use subclasses Square and RightAngledTriangle, to construct different objects (instances), get their perimeter and area, move them around, and draw them
- What other subclasses can inherit from Shape?

Final note

- Don't maintain documentation in two places, e.g. superclass and subclass, unless there's no other choice:
  - Inherited methods, attributes
    - no need to document again
  - extended methods
    - document that they are extended and how
  - overridden methods, attributes
    - document that they are overridden and how

Let's move on to another topic

Stack definition

A stack contains items of various sorts. New items are added onto the top of the stack, items may only be removed from the top of the stack. It's a mistake to try to remove an item from an empty stack, so we need to know if it is empty. We can tell how big a stack is.

Stack definition

A stack contains items of various sorts. New items are added on to the top of the stack, items may only be removed from the top of the stack. It's a mistake to try to remove an item from an empty stack, so we need to know if it is empty. We can tell how big a stack is.

developing Stack API

```
class Stack:
    """
    Last-in, first-out (LIFO) stack.
    """

if __name__ == "__main__":
    import doctest
    doctest.testmod()
    s = Stack()
    s.add(5)
```


developing Stack API

```
class Stack:
    …
    def __init__(self):
        """
        Create a new, empty Stack self.

        """
        pass
    def add(self, obj):
        """
        Add object obj to top of Stack self.

        :param obj: object to place on Stack
        :type obj: Any
        :rtype: None
        """
        pass
```


developing Stack API

```
class Stack:
    …
    …

    def remove(self):
        """
        Remove and return top element of Stack self.

        Assume Stack self is not empty.

        :rtype: object

        >>> s = Stack()
        >>> s.add(5)
        >>> s.add(7)
        >>> s.remove()
        7
        """
        pass
```


developing Stack API

```
class Stack:
    …
    …
    …

    def is_empty(self):
        """
        Return whether Stack self is empty.

        :rtype: bool
        """
        pass

if __name__ == "__main__":
    import doctest
    doctest.testmod()
    s = Stack()
    s.add(5)
```

Sack (or bag) definition

sack contains items of various sorts. New items are added on to a random place in the sack, so the order items are removed from the sack is completely unpredictable. It's a mistake to try to remove an item from an empty sack, so we need to know if it is empty. We can tel l how big a sack is

Sack (bag) definition

sack contains items of various sorts. New items are added on to a random place in the sack, so the order items are removed from the sack is completely unpredictable. It's a mistake to try to remove an item from an empty sack, so we need to know if it is empty. We can tell how big a sack is

developing Sack API

```
class Sack:
    """
    A Sack with elements in no particular order.
    """

if __name__ == "__main__":
    import doctest
    doctest.testmod()
    s = Sack()
    s.add(5)
```


developing Sack API

```
class Sack:
    …
    def __init__(self):
        """
        Create a new, empty Sack self.

        """
        pass

    def add(self, obj):
        """
        Add object obj to some random location of Sack self.

        :param obj: object to place on Sack
        :type obj: Any
        :rtype: None
        """
        pass
```


developing Sack API

```
class Sack:
    …
    …

    def remove(self):
        """
        Remove and return some random element of Sack self.

        Assume Sack self is not empty.

        @param Sack self: this Sack
        @rtype: object

        >>> s = Sack()
        >>> s.add(7)
        >>> s.remove()
        7
        """
        pass
```



```
class Sack:
    …
    …
    …

    def is_empty(self):
        """
        Return whether Sack self is empty.

        :rtype: bool
        """
        pass

if __name__ == "__main__":
    import doctest
    doctest.testmod()
    s = Sack()
    s.add(5)
```

Compare Slides 33-36 with 39-42

What are the similarities and the differences?

Implementation thoughts

- The public interface should be constant, but inside we could implement Stack and Sack in various ways
  - Use a python list, which has certain methods that can be used in certain ways to be useful for Stack or Sack needs.
  - Use a python dictionary, with integer keys 0, 1, … , keeping track of the indexes in certain ways to satisfy Stack or Sack needs

Next

- How Stack and Sack can be abstracted to a more general Container
- More on *testing*
- …