# **Constructing Decision Trees**

Alice Gao Lecture 19

Based on work by K. Leyton-Brown, K. Larson, and P. van Beek



Learning Goals

#### Choosing the most important feature

Revisiting the Learning goals

By the end of the lecture, you should be able to

- Compute the entropy of a probability distribution.
- Compute the expected information gain for selecting a feature.
- Describe/trace/implement the ID3 algorithm.

#### Jeeves the valet - training set

Day	Outlook	Temp	Humidity	Wind	Tennis?
1	Sunny	Hot	High	Weak	No
2	Sunny	Hot	High	Strong	No
3	Overcast	Hot	High	Weak	Yes
4	Rain	Mild	High	Weak	Yes
5	Rain	Cool	Normal	Weak	Yes
6	Rain	Cool	Normal	Strong	No
7	Overcast	Cool	Normal	Strong	Yes
8	Sunny	Mild	High	Weak	No
9	Sunny	Cool	Normal	Weak	Yes
10	Rain	Mild	Normal	Weak	Yes
11	Sunny	Mild	Normal	Strong	Yes
12	Overcast	Mild	High	Strong	Yes
13	Overcast	Hot	Normal	Weak	Yes
14	Rain	Mild	High	Strong	No

#### Jeeves the valet - the test set

Day	Outlook	Temp	Humidity	Wind	Tennis?
1	Sunny	Mild	High	Strong	No
2	Rain	Hot	Normal	Strong	No
3	Rain	Cool	High	Strong	No
4	Overcast	Hot	High	Strong	Yes
5	Overcast	Cool	Normal	Weak	Yes
6	Rain	Hot	High	Weak	Yes
7	Overcast	Mild	Normal	Weak	Yes
8	Overcast	Cool	High	Weak	Yes
9	Rain	Cool	High	Weak	Yes
10	Rain	Mild	Normal	Strong	No
11	Overcast	Mild	High	Weak	Yes
12	Sunny	Mild	Normal	Weak	Yes
13	Sunny	Cool	High	Strong	No
14	Sunny	Cool	High	Weak	No

#### Constructing the "best" decision tree

We want a decision tree to be

- Consistent with all the training examples and
- As small (shallow) as possible.

Unfortunately, it is intractable to find the smallest consistent decision tree.

Thus, we will use heuristics to find a small consistent tree.

#### The decision tree learning algorithm

- A greedy divide-and-conquer approach.
- Test the most important feature at each step.
- Solve the sub-problems recursively.

# The ID3 algorithm

#### Algorithm 1 ID3 Algorithm (Features, Examples)

- 1: If all examples are positive, return a leaf node with decision yes.
- 2: If all examples are negative, return a leaf node with decision no.
- 3: If no features left, return a leaf node with the majority decision of the examples.
- 4: If no examples left, return a leaf node with the majority decision of the examples in the parent.
- 5: else
- 6: choose the most important feature f
- 7: **for** each value v of feature f **do**
- 8: add arc with label v
- 9: add subtree  $ID3(F f, s \in S | f(s) = v)$

10: end for

Base cases of the ID3 algorithm

No features left:

No examples left:

#### CQ: Entropy of a distribution

**CQ:** What is the entropy of the distribution (0.5, 0.5)?

#### CQ: Entropy of a distribution

**CQ:** What is the entropy of the distribution (0.01, 0.99)?

**CQ:** What is the entropy of the examples before we select a feature for the root node of the tree?

**CQ:** What is the expected information gain if we select **Outlook** as the root node of the tree?

**CQ:** What is the expected information gain if we select **Temp** as the root node of the tree?

**CQ:** At the subtree starting with **Outlook = Sunny**, what is the entropy of the examples before selecting a feature?

**CQ:** At the subtree starting with **Outlook = Sunny**, what is the expected information gain if we select **Temp** as the root node of the subtree?

```
(A) [0,0.2)
(B) [0.2,0.4)
(C) [0.4,0.6)
(D) [0.6,0.8)
(E) [0.8,1]
```

By the end of the lecture, you should be able to

- Compute the entropy of a probability distribution.
- Compute the expected information gain for selecting a feature.
- Describe/trace/implement the ID3 algorithm.